


## HIGH TENSILE STEEL BOLT CUTTERS WITH INSULATED FIBERGLASS HANDLES


- Suitable for cutting hard material
- Short cutting edge for high tensile steel, bolts, wire, rods, chain links, and case hardened chains
- Handles are filled with unicellular foam core
- Same fiberglass used in all HASTINGS Hot Sticks



10-765



CENTER CUT



CLIPPER CUT

BOLT CUTTERS				MAXIMUM CUTTING CAPACITY DIAMETER				HEAD ONLY	
STYLE OF HEAD	CAT NO	HANDLE	OVERALL CUTTER LENGTH	HRC - BRINELL 140 49.6kg/mm 32 tons/sq. in. REINFORCEMENT STEEL	HRC 20 BRINELL 230 77.5kg/mm 50 tons/sq. in. BAR STEEL	HRC 40 BRINELL 370 133kg/mm 85 tons/sq. in. STEEL WIRE	HRC 48 BRINELL 450 162kg/mm 105 tons/sq. in. MUSIC WIRE		
CLIPPER CUT	10-365	12"	18"	7mm / 1/4"	6mm / 1/4"	5mm / 3/16"	5mm / 3/16"	A11010	
	10-367	8"	14"					A11010	
	10-465	18"	25"	8mm / 5/16"		6mm / 1/4"	5.5mm / 7/32"	A11011	
	10-467	11"	18"					A11011	
CENTER CUT	10-665	24"	32"	10mm / 3/8"	8mm / 5/16"	8mm / 5/16"	7mm / 9/32"	A11012	
	10-666	12"	20"					A11012	
	10-667	16"	24"					A11012	
	10-669	14"	22"	A11012					
	10-765	24"	33"	13mm / 1/2"		10mm / 3/8"	9mm / 11/32"	8mm / 5/16"	A11013
	10-767	21"	30"						A11013
	10-965	26"	36"	16mm / 5/8"		12mm / 5/32"	10mm / 3/8"	9mm / 11/32"	A11014