

HYDRAULIC IMPACT WRENCH EXTENSIONS

- Impact wrench extensions provide isolation between the impact wrench and potential voltages
- Male end has a retainer pin for sockets. Both male and female ends are heat treated for impact operation

CAT NO	DIMENSIONAL REFERENCE		LBS
	A	B	
10-198	15 7/16"	6"	5.0
10-199	27 7/16"	18"	5.0
10-200	39 7/16"	30"	6.0
10-201	51 7/16"	42"	5.5
10-167	75 7/16"	66"	9.0

FLEXIBLE HEAD INSULATED SOCKET WRENCH

- For hardware tightening operations
- The optional female ratchet handle is reversible
- Bottom end is 1/2" male square drive

CAT NO	DESCRIPTION	LBS
10765	1 1/2" x 6' SOCKET WRENCH	5.5
10768	1 1/2" x 8' SOCKET WRENCH	8.0
SA50A	RATCHET HANDLE - FEMALE 1/2" DRIVE	2.0

12 POINT WRENCH SOCKETS

- Chrome plated steel sockets
- 3 1/4" long with 1/2" square drive

CAT NO	SOCKET SIZE	LBS
5764-8	1/2"	0.3
5764-9	9/16"	0.3
5764-10	5/8"	0.3
5764-11	11/16"	0.4
5764-12	3/4"	0.5
5764-13	13/16"	1.0
5764-14	7/8"	0.6
5764-15	15/16"	0.7
5764-16	1"	0.8
5764-18	1 1/8"	0.9
5764-20	1 1/4"	1.1
5764-25	COMPLETE SET (1 EACH OF ABOVE)	7.0

MAGNETIC WRENCH SOCKET

- Magnet holds washer/nut in place for replacement on insulator pin

CAT NO	FOR	LBS
5765-13	5/8" SQUARE NUT	1.4
5765-19	3/4" SQUARE NUT	0.8

4 POINT WRENCH SOCKETS

- Deep well single square wrench sockets are 3 1/4" long
- Bronze alloy
- For line hardware square bolts and nuts 1/2" square drive

CAT NO	BOLT SIZE	FLATS WIDTH	LBS
5765-4	5/8"	1 1/8"	0.5
5765-6	3/4"	1 9/32"	0.7

