



6799

HOT STICK TESTER

- Test hot sticks wet or dry. The tester has a selector switch for wet or dry tests and a dual range scale which gives the operator leakage current values in micro amps.
- Utilizing a 2,500 volt output, the meter is calibrated to indicate the leakage values that would be present if 75KVAC were applied to a 12” section of the fiberglass tool for the wet test and 100KVAC per foot for the dry test.
- Portable and lightweight for easy use. Two models available 120 volt or 220 volt systems. The tester is designed to protect the operator while in use.
- The tester comes complete with a padded carrying case and directions for proper use. A testing bar is also provided to ensure the tester is working properly.
- Application and training video included with purchase.

CAT NO	DESCRIPTION	LBS
6799	HOT STICK TESTER COMPLETE WITH CARRYING CASE AND TEST BAR OPERATES ON 120 VOLT SYSTEM	5.3
6781	HOT STICK TESTER COMPLETE WITH CARRYING CASE AND TEST BAR OPERATES ON 220 VOLT SYSTEMS	8.2



6790

AMMETER

- Designed for use with universal hot sticks.
- Large digital display, numbers are 1” high and 1/2” wide, can be seen 30’ to 40’ away. Has lighted background for night use.
- For use on low voltage and high voltage lines (tested to 345KV).
- The hold feature captures current readings when applied with telescoping hot sticks from distances.
- 0 - 2000 amp range
- Large digital display, numbers are 1” high and 1/2” wide
- Displays either Hold or Free Run readings
- Accuracy is ± 1%
- Wide temperature operation -4°F to 104°F (-20°C to 40°C)
- Snap in and out adapter enables the ammeter to be used on conductors up to 2” O.D.
- Low battery indicator
- Weather proof aluminum housing

CAT NO	DESCRIPTION	LBS
6790	AMMETER COMPLETE WITH PADDED CASE	2.4