

# Vigilant® H2 Series LED High Bay

## Ordering Information and Mounting Accessories

Part Number	Fixture Lumen	Watt	LPW	Wet Location	Voltage	CCT	Lens	Optical Pattern
Standard Models								
H2GMC4NN-SNG	25,250	180	140	IP66	110 - 277V AC	5000K (cool white)	Tempered glass	Circular
H2GMC5NN-SNG	25,250	192	132	IP66	480V AC	5000K (cool white)	Tempered glass	Circular
Variable Dimming Models								
H2GMC4ND-SNG	25,250	180	140	IP66	110 - 277V AC	5000K (cool white)	Tempered glass	Circular
H2GMC5ND-SNG	25,250	192	132	IP66	480V AC	5000K (cool white)	Tempered glass	Circular

All values typical unless otherwise stated, Lumen values are typical (tolerance +/- 10%)



**HBXW3-SSL-316**  
**HBXW3-SSL-304**

- Stainless Steel Bracket



**HBXCAB48**

- 48" long stainless steel safety rope (for use with safety bracket)



**HBXDC**

- 21° slope dust cover **HBXDC45**
- 45° slope dust cover **HBXDC60**
- 60° slope dust cover



**FLX1HBXSS**

- 304 Stainless steel forward throw bracket



**HBXTH347480**

- Top hat with 347-480V AC step down transformer (consult factory when using with hook or loop)



**HBXH**

- Hook



**HBXW2**

- Swivel bracket and cable gland

**HBXW3**

- Swivel bracket



**HBXL**

- Loop




**HBXDUALBRCKT**

- Dual bracket



**HBXCU**

- Ceiling / wall mount



**HBXLENGC**

- Clear tempered glass