



### Pneumatic Tensioning Tool with Plastic Housing

- **MK9P up to 13.5 mm strap width**

The MK9P is constructed with heavy duty parts to ensure optimum performance. It is ideally designed to apply heavy-duty ties that are used in vehicle construction like trucks, busses and railways.

#### Features and Benefits

- Pneumatic tensioning tool
- Glass-fibre-reinforced housing
- For cable ties up to 13.5 mm width
- For consistent tensioning and automatically flush cutting
- Infinitely adjustable tension force
- High application speed
- Holding ring for a balancer
- Option of lower or upper air attachment



MK9P.



MK9P is also available with upper air attachment.

<b>Air Supply</b>	Non oiled / oiled
<b>Air Pressure (min.)</b>	3 Bar
<b>Air Pressure (max.)</b>	6 Bar
<b>Hose Internal Diameter</b>	4.0 mm
<b>L x H x W</b>	approx. 280 x 200 x 55mm
<b>Specifications</b>	CE, GS



TYPE	Strap Width max. (G)	Strap Thickness max.	Weight	Air att. Position	Article-No.
MK9P	13.5	2.5	0.91 kg	Lower air connection	110-09100
	13.5	2.5	0.91 kg	Top air connection	110-09110
Compressed-air hose	-	-	0.35 kg	-	110-30002
Lock cap tensioning knob	-	-	0.011 kg	-	110-07200
Replacement Blade	-	-	0.01 kg	-	110-09111

All dimensions in mm. Subject to technical changes.



Please note! Not all products listed on this page may have this approval. For product specific approvals please refer to the Appendix.