

1-Piece Fixing Ties with Arrowhead, with Wings, releasable RT50RSF



1-Piece Fixing Ties with Arrowhead, with wings, releasable, Article number: 115-07010

- Easy to assemble without the need for a tool
- Cable tie head always situated in defined position
- Arrowhead simply locks into place
- Supporting legs provide a secure and firm fixing in areas where space is limited
- Releasable and therefore reusable
- "Ladder style" types are very flexible

With a diverse range of fixing possibilities are ideal for use in many different industries, including automotive, aerospace and panel building.

RoHS



Catalogue page (February



All catalogue pages

2014)



CAD-Download

▼ Base Data

Anti rotation (Yes / No)	NO
Application Tool	MK20, MK21, MK3PNSP2, MK3SP, EVO7, MK7HT, MK7P, MK6, MK9
Colour	Black (BK)
Fixation Method (FF)	Arrowhead
Fixing Hole Shape	Circular
Identification Plate Position	none
Manufacturer Type	RT50RSF PA66 BK 100
Product Family	1-Piece Fixing Ties with Arrowhead, with wings, releasable
Product Group	1-Piece Fixing Ties with Arrowhead, with Wings, releasable
Releasable Closure (Yes/No)	Yes
Type	RT50RSF.NB3P

▼ Product Dimensions

Bundle Ø max.	50.0 mm
Bundle Ø min.	1.5 mm
Disc Ø	18.5 mm
Height (H)	9.5 mm
Hole Ø	8.2 mm
Hole Ø (FH)	7.8 - 8.2 mm
Hole Ø (FH) min.	7.8 mm
Length (L)	215 mm
Min.Tensile Strength (N)	225 N
Panel Thickness min - max	0.8 - 2.5 mm

▼ Logistic and Packaging**Carton Quantity** 3000 pcs.**EAN / GTIN** 5022660136221**Pack Cont.** 100 pcs.**Quantity of Europallet** 54000 pcs.**Quantity per** pieces**Weight** 1.3 kg**▼ Material and Specifications****ELV compliant Dir. Art. 4 (2)** YES**Flammability** UL94 V2**Material** Polyamide 6.6 (PA66)**Material** PA66**Operating Temperature** -40 °C to +85 °C, (+105 °C, 500 h)**REACH compliant Regu. Art. 33** YES**▼ More Information****ETIM 5.0** EC000046**ETIM 6.0** EC000046