# Safety Data Sheet



Revision Number: 005.1

### 1. PRODUCT AND COMPANY IDENTIFICATION

Product name:

Comp Product type: Anaer Restriction of Use: None Company address: Henkel Corporation One Henkel Way Rocky Hill, Connecticut 06067

LOCTITE 609 RETAINING COMPOUND IDH number: known as Loctite(R) 609 Retaining Compo Anaerobic Adhesive Item number None identified Region: Contact infor Telephone: (8

Item number:60905Region:United StatesContact information:Telephone:(860) 571-5100MEDICAL EMERGENCY Phone:Poison Control Center1-877-671-4608 (toll free) or 1-303-592-1711TRANSPORT EMERGENCY Phone:CHEMTREC1-800-424-9300 (toll free) or 1-703-527-3887Internet:www.henkelna.com

234667

#### 2. HAZARDS IDENTIFICATION

# EMERGENCY OVERVIEW WARNING: CAUSES SKIN IRRITATION. MAY CAUSE AN ALLERGIC SKIN REACTION. CAUSES SERIOUS EYE IRRITATION.

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
EYE IRRITATION	2A
SKIN SENSITIZATION	1

PICTOGRAM(S)	

#### **Precautionary Statements**

Prevention:	Avoid breathing vapors, mist, or spray. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear eye and face protection. Wear protective gloves.
Response:	F ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing.
Storage:	Not prescribed
Disposal:	Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

#### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*	
Polyglycol dimethacrylate	Proprietary	60 - 100	
2-Hydroxyethyl methacrylate	868-77-9	10 - 30	
Ethyl methacrylate homopolymer	Proprietary	1 - 5	
Cumene hydroperoxide	80-15-9	1 - 5	
Saccharin	81-07-2	1 - 5	
Adhesion Promoter	Proprietary	0.1 - 1	
Cumene	98-82-8	0.1 - 1	

\* Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES			
Inhalation:	Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.		
Skin contact:	Immediately flush skin with plenty of water (using soap, if available). Remove contaminated clothing and footwear. Wash clothing before reuse. Get medical attention.		
Eye contact:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.		
Ingestion:	Do not induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention.		
Symptoms:	See Section 11.		
5. FI	5. FIRE FIGHTING MEASURES		
Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide.		
Special firefighting procedures:	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.		
Unusual fire or explosion hazards:	Uncontrolled polymerization may occur at high temperatures resulting in explosions or rupture of storage containers. In case of fire, keep containers cool with water spray.		
Hazardous combustion products:	Oxides of carbon. Oxides of sulfur. Oxides of nitrogen. Irritating organic vapours.		

## 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Do not allow product to enter sewer or waterways.	
Clean-up methods:	Remove all sources of ignition. Evacuate and ventilate spill area; dike spill to prevent entry into water system; wear full protective equipment during clean- up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up as much material as possible. Store in a partly filled, closed container until disposal. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up.	

## 7. HANDLING AND STORAGE

Handling:

Use only with adequate ventilation. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Refer to Section 8.

Storage:

For safe storage, store at or below 38 °C (100.4 °F) Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

#### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Polyglycol dimethacrylate	None	None	None	None
2-Hydroxyethyl methacrylate	None	None	None	3 ppm Ceiling
Ethyl methacrylate homopolymer	None	None	None	None
Cumene hydroperoxide	None	None	1 ppm (6 mg/m3) TWA (SKIN)	None
Saccharin	None	None	None	None
Adhesion Promoter	20 ppm TWA	None	None	None
Cumene	50 ppm TWA	50 ppm (245 mg/m3) PEL (SKIN)	None	None
Engineering controls:		e adequate local exhaust re limits.	ventilation to maintain w	vorker exposure below
Respiratory protection:	Use NIOSH approved respirator if there is potential to exceed exposure limit(s).			
Eye/face protection:	Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Safety showers and eye wash stations should be available.			
Skin protection:	apron c gloves.	Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact. Neoprene gloves. Butyl rubber gloves. Natural rubber gloves. Glove recommendations are based upon permeation study results for similar products.		

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Color: Odor: Odor threshold: pH: Vapor pressure: Boiling point/range: Melting point/ range: Specific gravity: Vapor density: Flash point: Flammable/Explosive limits - lower: Flammable/Explosive limits - upper: Autoignition temperature: Evaporation rate: Solubility in water: Partition coefficient (n-octanol/water): Liquid Green Mild Not available. Not applicable < 5 mm hg (27 °C (80.6 °F)) > 149 °C (> 300.2 °F) Not available. 1.1 Not available. > 93.3 °C (> 199.94 °F) Tagliabue closed cup Not available. Not available. Not available. Not available. Slight Not available.

Product name: LOCTITE 609 RETAINING COMPOUND known as Loctite(R) 609 Retaining Compo Page 3 of 6 VOC content: Viscosity: Decomposition temperature:

0.22 %; 2.46 g/l Not available. Not available.

10. STABILITY AND REACTIVITY		
Stability:	Stable under normal conditions of storage and use.	
Hazardous reactions:	None under normal processing. Polymerization may occur at elevated temperature or in the presence of incompatible materials.	
Hazardous decomposition products:	Oxides of carbon. Oxides of sulfur. Oxides of nitrogen. Irritating organic vapours.	
Incompatible materials:	Strong oxidizing agents.	
Reactivity:	Not available.	
Conditions to avoid:	Elevated temperatures. Heat, flames, sparks and other sources of ignition. Store away from	

Elevated temperatures. Heat, flames, sparks and other sources of ignition. Store away from incompatible materials.

# **11. TOXICOLOGICAL INFORMATION**

Relevant routes of exposure:

Skin, Inhalation, Eyes, Ingestion

#### Potential Health Effects/Symptoms

Inhalation:	Inhalation of vapors or mists of the product may be irritating to the respiratory system.
Skin contact:	Causes skin irritation. May cause allergic skin reaction.
Eye contact:	Causes serious eye irritation.
Ingestion:	May cause gastrointestinal tract irritation if swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects	
Polyglycol dimethacrylate	None	Allergen, Irritant	
2-Hydroxyethyl methacrylate	Oral LD50 (RAT) = 11.2 g/kg Oral LD50 (RAT) = 5,050 mg/kg		
Ethyl methacrylate homopolymer	None	Irritant	
Cumene hydroperoxide	None Allergen, Central nervous system Irritant, Mutagen		
Saccharin	None	No Target Organs	
Adhesion Promoter	Oral LD50 (RABBIT) = 1,200 mg/kg Oral LD50 (RAT) = 1,060 mg/kg Oral LD50 (RAT) = 2,224 mg/kg Dermal LD50 (RABBIT) = 500 mg/kg Inhalation LC50 (RAT, 4 h) = 7.1 mg/l	Corrosive, Irritant, Allergen	
Cumene	Oral LD50 (RAT) = 2.91 g/kg Oral LD50 (RAT) = 1,400 mg/kg Inhalation LC50 (RAT, 4 h) = 8000 ppm	Central nervous system, Irritant, Lung	

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Polyglycol dimethacrylate	No	No	No
2-Hydroxyethyl methacrylate	No	No	No
Ethyl methacrylate homopolymer	No	No	No
Cumene hydroperoxide	No	No	No
Saccharin	No	No	No
Adhesion Promoter	No	No	No
Cumene	Reasonably Anticipated to be a Human Carcinogen.	Group 2B	No

12.	ECOL	OGICAL	INFORMATION
-----	------	--------	-------------

Ecological information:

Not available.

#### **13. DISPOSAL CONSIDERATIONS**

 Information provided is for unused product only.

 Recommended method of disposal:
 Follow all local, state, federal and provincial regulations for disposal.

 Hazardous waste number:
 Not a RCRA hazardous waste.

#### **14. TRANSPORT INFORMATION**

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)	
Proper shipping name:	RQ, Environmentally hazardous substances, liquid, n.o.s.
Hazard class or division:	9
Identification number:	UN 3082
Packing group:	
DOT Hazardous Substance(s):	alpha,alpha-Dimethylbenzylhydroperoxide
International Air Transportation (ICAO/IATA)	
Proper shipping name:	Environmentally hazardous substance, liquid, n.o.s.
Hazard class or division:	9
Identification number:	UN 3082
Packing group:	III
Water Transportation (IMO/IMDG)	
Proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
Hazard class or division:	9
Identification number:	UN 3082
Packing group:	III

## **15. REGULATORY INFORMATION**

**United States Regulatory Information** 

TSCA 8 (b) Inventory Status: TSCA 12 (b) Export Notification:	All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory. None above reporting de minimis
CERCLA/SARA Section 302 EHS: CERCLA/SARA Section 311/312: CERCLA/SARA Section 313:	None above reporting de minimis Immediate Health, Delayed Health This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Cumene hydroperoxide (CAS# 80-15-9). Saccharin (CAS# 81-07-2).
CERCLA Reportable quantity:	Cumene hydroperoxide (CAS# 80-15-9) 10 lbs. (4.54 kg)
California Proposition 65:	This product contains a chemical known in the State of California to cause cancer.
Canada Regulatory Information	
CEPA DSL/NDSL Status:	All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

#### **16. OTHER INFORMATION**

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format. 11

#### Prepared by: Sheila Gines, Regulatory Affairs Specialist

**Issue date:** 07/17/2015

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.