

Revision Number: 006.0 Issue date: 05/14/2014

1. PRODUCT AND COMPANY IDENTIFICATION

Product name:574 Flange Sealant Fast CuringIDH number:223856Product type:Anaerobic SealantItem number:26338Restriction of Use:None identifiedRegion:United States

Company address: Henkel Corporation One Henkel Way

Rocky Hill, Connecticut 06067

WARNING:

Contact information: Telephone: (860) 571-5100 MEDICAL EMERGENCY Ph

MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW
CAUSES SKIN IRRITATION.

MAY CAUSE AN ALLERGIC SKIN REACTION.

CAUSES SERIOUS EYE IRRITATION.

| HAZARD CLASS | HAZARD CATEGORY |
|--------------------|-----------------|
| SKIN IRRITATION | 2 |
| EYE IRRITATION | 2A |
| SKIN SENSITIZATION | 1 |

PICTOGRAM(S)



Precautionary Statements

Prevention: Avoid breathing vapors, mist, or spray. Wash thoroughly after handling. Contaminated work

clothing should not be allowed out of the workplace. Wear eye and face protection. Wear

protective gloves.

Response: IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for

several minutes. Remove contact lenses, if present and easy to remove. Continue rinsing. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical

attention. Take off contaminated clothing.

Storage: Not prescribed

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

| Hazardous Component(s) | CAS Number | Percentage* |
|------------------------|------------|-------------|

| Polyglycol dimethacrylate | Proprietary | 30 - 60 |
|--|-------------|---------|
| Polyglycoldioctanoate | Proprietary | 5 - 10 |
| Decan-1-ol | 112-30-1 | 5 - 10 |
| Ethene, tetrafluoro-, homopolymer | 9002-84-0 | 5 - 10 |
| Silica, amorphous, fumed, crystal-free | 112945-52-5 | 1 - 5 |
| Rheological additive | Unknown | 1 - 5 |
| Cumene hydroperoxide | 80-15-9 | 0.1 - 1 |

^{*} Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation: Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give

artificial respiration. Get medical attention.

Skin contact: Remove contaminated clothing and footwear. Immediately flush skin with

plenty of water (using soap, if available). Get medical attention. Wash clothing

before reuse.

Eye contact: Rinse immediately with plenty of water, also under the eyelids, for at least 15

minutes. Get medical attention.

Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious

person. Get medical attention.

Symptoms: See Section 11.

5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear.

Uncontrolled polymerization may occur at high temperatures resulting in

explosions or rupture of storage containers.

Hazardous combustion products: Oxides of carbon. Irritating organic vapours.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Do not allow product to enter sewer or waterways.

Clean-up methods: Remove all sources of ignition. Evacuate and ventilate spill area; dike spill to

prevent entry into water system; wear full protective equipment during cleanup. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up spilled material and place in a closed container for disposal. Refer to Section 8 "Exposure Controls / Personal

Protection" prior to clean up.

7. HANDLING AND STORAGE

Handling: Use only with adequate ventilation. Prevent contact with eyes, skin and

clothing. Do not breathe vapor and mist. Wash thoroughly after handling.

Refer to Section 8.

Storage: For safe storage, store at or below 38 °C (100.4 °F)

Keep in a cool, well ventilated area away from heat, sparks and open flame.

Keep container tightly closed until ready for use.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

| Hazardous Component(s) | ACGIH TLV | OSHA PEL | AIHA WEEL | OTHER |
|--|--|--|----------------------------------|---|
| Polyglycol dimethacrylate | None | None | None | None |
| Polyglycoldioctanoate | None | None | None | None |
| Decan-1-ol | None | None | None | None |
| Ethene, tetrafluoro-, homopolymer | None | None | None | 10 mg/m3 TWA Total dust. 5 mg/m3 TWA Respirable fraction. |
| Silica, amorphous, fumed, crystal-free | 10 mg/m3 TWA Inhalable dust. 3 mg/m3 TWA Respirable fraction. | 20 MPPCF TWA 0.8 mg/m3 TWA | None | None |
| Rheological additive | 10 mg/m3 TWA Total dust. 3 mg/m3 TWA Respirable fraction. | 15 mg/m3 TWA Total dust. 5 mg/m3 TWA Respirable fraction. | None | None |
| Cumene hydroperoxide | None | None | 1 ppm (6 mg/m3) TWA (SKIN) | None |

Engineering controls: Provide adequate local exhaust ventilation to maintain worker exposure below

exposure limits.

Respiratory protection:Use NIOSH approved respirator if there is potential to exceed exposure

limit(s).

Eyelface protection: Safety goggles or safety glasses with side shields. Full face protection should

be used if the potential for splashing or spraying of product exists. Safety

showers and eye wash stations should be available.

Skin protection:Use chemical resistant, impermeable clothing including gloves and either an

apron or body suit to prevent skin contact. Neoprene gloves. Butyl rubber

gloves. Natural rubber gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Paste, Liquid Color: Orange Odor: Mild

Odor threshold:

pH:

Not available.

Not applicable

Vapor pressure: $< 5 \text{ mm} \text{ hg} (27 \,^{\circ}\text{C} (80.6 \,^{\circ}\text{F}))$ Boiling point/range: $> 149 \,^{\circ}\text{C} (> 300.2 \,^{\circ}\text{F})$ Melting point/ range:Not available.

Specific gravity: 1.1518
Vapor density: Not available.

Flash point: > 93.3 °C (> 199.94 °F) Pensky Martens closed cup

Flammable/Explosive limits - lower: Not available. Flammable/Explosive limits - upper: Not available. Autoignition temperature: Not available. **Evaporation rate:** Not available. Solubility in water: Sliaht Partition coefficient (n-octanol/water): Not available. **VOC** content: 0.6 %; 6.01 g/l Viscosity: Not available. **Decomposition temperature:** Not available.

10. STABILITY AND REACTIVITY

Stable under normal conditions of storage and use.

Hazardous reactions: Will not occur.

Hazardous decomposition

products:

Oxides of carbon. Irritating organic vapours.

Incompatible materials: Strong oxidizing agents. Reducing agents. Acids. Alkalis. Oxygen scavengers.

Reactivity: Not available.

Conditions to avoid: Heat, flames, sparks and other sources of ignition. Store away from incompatible materials.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes

Potential Health Effects/Symptoms

Inhalation: Inhalation of vapors or mists of the product may be irritating to the respiratory system.

Skin contact: Causes skin irritation. May cause allergic skin reaction.

Eye contact: Causes serious eye irritation.

Ingestion: Not expected to be harmful by ingestion.

| Hazardous Component(s) | LD50s and LC50s | Immediate and Delayed Health Effects |
|--|---|--|
| Polyglycol dimethacrylate | None | Allergen, Irritant |
| Polyglycoldioctanoate | None | Irritant |
| Decan-1-ol | Oral LD50 (RAT) = 4,720 mg/kg Dermal LD50 (RABBIT) = 3,560 mg/kg | Irritant |
| Ethene, tetrafluoro-, homopolymer | None | No Target Organs |
| Silica, amorphous, fumed, crystal-free | None | Nuisance dust |
| Rheological additive | None | No Data |
| rumene hydroperoxide None | | Allergen, Central nervous system, Corrosive, Irritant, Mutagen |

| Hazardous Component(s) | NTP Carcinogen | IARC Carcinogen | OSHA Carcinogen (Specifically Regulated) |
|--|----------------|-----------------|--|
| Polyglycol dimethacrylate | No | No | No |
| Polyglycoldioctanoate | No | No | No |
| Decan-1-ol | No | No | No |
| Ethene, tetrafluoro-, homopolymer | No | No | No |
| Silica, amorphous, fumed, crystal-free | No | No | No |
| Rheological additive | No | No | No |
| Cumene hydroperoxide | No | No | No |

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: Not a RCRA hazardous waste.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:
Hazard class or division:
Identification number:
Packing group:
Not regulated
None
None

International Air Transportation (ICAO/IATA)

Proper shipping name:
Hazard class or division:
Identification number:
Packing group:
Not regulated
None
None

Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12 (b) Export Notification: Ethene, tetrafluoro-, homopolymer (CAS# 9002-84-0).

CERCLA/SARA Section 302 EHS:
CERCLA/SARA Section 311/312:
CERCLA/SARA Section 313:

None above reporting de minimis
None above reporting de minimis

CERCLA Reportable quantity: Cumene hydroperoxide (CAS# 80-15-9) 10 lbs. (4.54 kg)

California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This

product contains a chemical known to the State of California to cause birth defects or other

reproductive harm.

Canada Regulatory Information

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: Sheila Gines, Regulatory Affairs Specialist

Issue date: 05/14/2014

IDH number: 223856 Product name: 574 Flange Sealant Fast Curing

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

IDH number: 223856 Product name: 574 Flange Sealant Fast Curing