

Revision Number: 005.0 Issue date: 08/12/2014

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: LOCTITE PC 9626 GROUT known as

Fixmaster Deep Pour Grout

Product type: Epoxy Hardener
Restriction of Use: None identified

Company address: Henkel Corporation One Henkel Way

Rocky Hill, Connecticut 06067

IDH number: 702290

Item number:99545_204000Region:United States

Contact information: Telephone: (860) 571-5100

MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC

1-800-424-9300 (toll free) or 1-703-527-3887 Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER: HARMFUL IF SWALLOWED.

TOXIC IN CONTACT WITH SKIN.

CAUSES SEVERE SKIN BURNS AND EYE DAMAGE.

MAY CAUSE AN ALLERGIC SKIN REACTION.

MAY CAUSE ALLERGY OR ASTHMA SYMPTOMS OR BREATHING

DIFFICULTIES IF INHALED.

HAZARD CLASS	HAZARD CATEGORY
ACUTE TOXICITY ORAL	4
ACUTE TOXICITY DERMAL	3
SKIN CORROSION	1B
SERIOUS EYE DAMAGE	1
RESPIRATORY SENSITIZATION	1
SKIN SENSITIZATION	1









Precautionary Statements

Storage:

Prevention: Do not breathe vapors, mist, or spray. Wash thoroughly after handling. Do not eat, drink or

smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, eye protection, and face protection. In case of inadequate

ventilation wear respiratory protection.

Response: If SWALLOWED: Immediately call poison control or physician if you feel unwell. IF

SWALLOWED: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. IF INHALED: Remove person to fresh air and keep comfortable for

breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to remove. Continue rinsing. Immediately call a poison control center or physician. If skin irritation or rash occurs: Get medical attention. If experiencing respiratory symptoms: Call a poison center or physician. Wash contaminated clothing before reuse.

Store locked up.

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*	
Substituted Piperazine	Proprietary	30 - 60	
Triethylenetetramine	112-24-3	10 - 30	
Substituted Amine	Proprietary	5 - 10	
Diethylenetriamine	111-40-0	1 - 5	
Substituted Piperazine	Proprietary	1 - 5	
Carbon black	1333-86-4	1 - 5	

^{*} Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation: Move to fresh air. If not breathing, give artificial respiration. If breathing is

difficult, give oxygen. Get medical attention.

Skin contact: Immediately flush skin with plenty of water (using soap, if available). Remove

contaminated clothing and footwear. Get medical attention. Wash clothing

before reuse. Thoroughly clean shoes before reuse.

Eye contact: Rinse immediately with plenty of water, also under the eyelids, for at least 15

minutes. Get medical attention.

Ingestion: DO NOT induce vomiting unless directed to do so by medical personnel.

Never give anything by mouth to an unconscious person. Get medical

attention.

Symptoms: See Section 11.

5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear.

Unusual fire or explosion hazards: Burning produces obnoxious and toxic fumes. Personnel in vicinity and

downwind should be evacuated. Use of water may result in the formation of very toxic aqueous solutions. Do not allow run-off from fire fighting to enter drains or water courses. Closed containers may rupture (due to build up of

pressure) when exposed to extreme heat.

Hazardous combustion products: Oxides of carbon. Oxides of nitrogen. Aldehydes. Ammonia. Toxic furnes.

Irritating vapors.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Do not allow product to enter sewer or waterways.

Product name: LOCTITE PC 9626 GROUT known as Fixmaster Deep Pour Grout Page 2 of 7

Clean-up methods: Immediately contact emergency personnel. Remove all sources of ignition.

Evacuate and ventilate spill area; dike spill to prevent entry into water system; wear full protective equipment during clean-up. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape

up spilled material and place in a closed container for disposal.

7. HANDLING AND STORAGE

Handling: Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist.

Wash thoroughly after handling. Use only with adequate ventilation. Keep

container closed. Refer to Section 8.

Storage: Store in original container until ready to use. Keep container tightly closed and

in a cool, well-ventilated place away from incompatible materials. Store away

from heat, sparks, flames, or other sources of ignition.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Substituted Piperazine	None	None	None	None
Triethylenetetramine	None	None	1 ppm (6 mg/m3) TWA (SKIN)	None
Substituted Amine	None	None	None	None
Diethylenetriamine	1 ppm TWA (SKIN)	None	None	None
Substituted Piperazine	None	None	None	None
Carbon black	3 mg/m3 TWA Inhalable fraction.	3.5 mg/m3 PEL	None	None

Engineering controls: Use local ventilation if general ventilation is insufficient to maintain vapor

concentration below established exposure limits.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure

limit(s).

Eye/face protection: Safety goggles or safety glasses with side shields. Full face protection should

be used if the potential for splashing or spraying of product exists. Safety

showers and eye wash stations should be available.

Skin protection: Use chemical resistant, impermeable clothing including gloves and either an

apron or body suit to prevent skin contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:LiquidColor:BlueOdor:AmineOdor threshold:Not available.pH:Not available.

Vapor pressure:

0 mm hg (20 °C (68°F))

Boiling point/range:

224 °C (435.2 °F)

Melting point/ range:

Not available.

Specific gravity: 0.988
Vapor density: 4.2

IDH number: 702290

Flash point: $> 93 \, ^{\circ}\text{C} \ (> 199.4 \, ^{\circ}\text{F}) \ ;$ Estimated

Flammable/Explosive limits - lower: Not available. Flammable/Explosive limits - upper: Not available.

Autoignition temperature:Not available.Evaporation rate:Not available.Solubility in water:SolublePartition coefficient (n-octanol/water):Not available.

VOC content: < 1.0 %; < 10 g/l (value for resin and hardener together) (estimated)

Viscosity: Not available.

Decomposition temperature: Not available.

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions of storage and use.

Hazardous reactions: None under normal processing.

Hazardous decomposition

products:

Oxides of carbon. Oxides of nitrogen. Aldehydes. Ammonia. Toxic fumes. Irritating vapors.

Incompatible materials: Acids. Acrylates. Alcohols. Aldehydes. Ketones. Peroxides. Reactive metals. Strong alkalis.

Strong oxidizing agents. Sodium hypochlorite. This product slowly corrodes copper, aluminum, zinc and galvanized surfaces. Do not mix this product with nitrites or other nitrosating agents

because a carcinogenic nitrosamine may be formed.

Reactivity: Not available.

Conditions to avoid: Keep away from heat, ignition sources and incompatible materials.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

Potential Health Effects/Symptoms

Inhalation: May cause allergic respiratory reaction. These symptoms, which can include chest tightness,

wheezing, cough, shortness of breath or asthma attack, could be immediate or delayed (up to several hours after exposure). Inhalation of vapors or mists of the product may be irritating to

the respiratory system.

Skin contact: Toxic in contact with skin. Causes burns. May cause allergic skin reaction. May cause nausea,

headache and general discomfort if absorbed through skin. Rash. Redness.

Eye contact: Causes serious eye damage. Burns of the eye may cause blindness. Corneal edema may give

appearance of "blue haze" or "fog" around lights. Redness. Tissue damage. Tearing. Pain and

discomfort.

Ingestion: Harmful if swallowed. If ingested, severe burns of the mouth and throat may occur, as well as

perforation of the esophagus and the stomach. May cause an aspiration hazard if swallowed.

Aspirated material can enter the lungs and result in pneumonitis.

Hazardous Component(s) LD50s and LC50s		Immediate and Delayed Health Effects	
Substituted Piperazine	None	Irritant, Corrosive, Allergen	
Triethylenetetramine	None	Allergen, Corrosive, Developmental, Irritant, Mutagen	
Substituted Amine	Oral LD50 (RAT) = 3,000 mg/kg	Irritant, Allergen	
Diethylenetriamine	Oral LD50 (RAT) = 1,080 mg/kg Oral LD50 (RAT) = 2.33 g/kg Oral LD50 (RAT) Approximate 1,140 mg/kg	Allergen, Irritant, Eyes	
Substituted Piperazine	None	Allergen, Central nervous system, Irritant	
Carbon black	Oral LD50 (RAT) = > 8,000 mg/kg	Respiratory, Some evidence of carcinogenicity	

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Substituted Piperazine	No	No	No
Triethylenetetramine	No	No	No
Substituted Amine	No	No	No
Diethylenetriamine	No	No	No
Substituted Piperazine	No	No	No
Carbon black	No	Group 2B	No

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

IDH number: 702290

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: It is the responsibility of the user to determine if an item is hazardous as

defined in the Resource Conservation and Recovery Act (RCRA) at the time of disposal. Product uses, transformations, mixtures, processes, etc., may render the resulting material hazardous, under the criteria of ignitability, corrosivity, reactivity and toxicity characteristics of the Toxicity Characteristics

Leaching Procedure (TCLP) 40 CFR 261.20-24.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Amines, liquid, corrosive, n.o.s. (Aminoethylpiperazine, Triethylenetetramine)

Hazard class or division: 8
Identification number: UN 2735
Packing group: II

International Air Transportation (ICAO/IATA)

Proper shipping name: Amines, liquid, corrosive, n.o.s. (Aminoethylpiperazine, Triethylenetetramine)

Hazard class or division: 8
Identification number: UN 2735

Packing group:

Water Transportation (IMO/IMDG)

Proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S. (Aminoethylpiperazine,

Triethylenetetramine)

Hazard class or division: 8
Identification number: UN 2735
Packing group: II

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS:
CERCLA/SARA Section 311/312:
CERCLA/SARA Section 313:

None above reporting de minimis
Immediate Health, Delayed Health
None above reporting de minimis

California Proposition 65: This product contains a chemical known in the State of California to cause cancer.

Canada Regulatory Information

IDH number: 702290

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: Sheila Gines, Regulatory Affairs Specialist

Issue date: 08/12/2014

Product name: LOCTITE PC 9626 GROUT known as Fixmaster Deep Pour Grout Page 6 of 7

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

IDH number: 702290