

Revision Number: 005.2 Issue date: 11/29/2016

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: Loctite(R) 577 Thread Sealant Medium IDH number: 231119

Strength

Product type:Anaerobic SealantItem number:21456Restriction of Use:None identifiedRegion:United States

Company address:Contact information:Henkel CorporationTelephone: (860) 571-5100

One Henkel Way

MEDICAL EMERGENCY Phone: Poison Control Center
Rocky Hill, Connecticut 06067

1-877-671-4608 (toll free) or 1-303-592-1711
TRANSPORT EMERGENCY Phone: Poison Control Center

TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

WARNING: CAUSES SKIN IRRITATION.

MAY CAUSE AN ALLERGIC SKIN REACTION. CAUSES SERIOUS EYE IRRITATION.

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
EYE IRRITATION	2A
SKIN SENSITIZATION	1

PICTOGRAM(S)



Precautionary Statements

Prevention: Avoid breathing vapors, mist, or spray. Wash affected area thoroughly after handling.

Contaminated work clothing should not be allowed out of the workplace. Wear protective

gloves, eye protection, and face protection.

Response: IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several

minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off

contaminated clothing.

Storage: Not prescribed

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*	
Polyglycol dimethacrylate	25852-47-5	40 - 50	
Polyglycol dioctanoate	18268-70-7	10 - 20	
Lauryl methacrylate	142-90-5	5 - 10	
Ethene, tetrafluoro-, homopolymer	9002-84-0	1 - 5	
Vinyl acetal polymers, butyrals	63148-65-2	1 - 5	
Tetradecyl methacrylate	2549-53-3	1 - 5	
Silica, amorphous, fumed, crystal-free	112945-52-5	1 - 5	
1-Acetyl-2-phenylhydrazine	114-83-0	0.1 - 1	
Hexadecyl methacrylate	2495-27-4	0.1 - 1	
Cumene hydroperoxide	80-15-9	0.1 - 1	

^{*} Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation: Move to fresh air. If not breathing, give artificial respiration. If breathing is

difficult, give oxygen. Get medical attention.

Skin contact: Immediately flush skin with plenty of water (using soap, if available). Remove

contaminated clothing and footwear. Wash clothing before reuse. Get medical

attention.

Eye contact: Rinse immediately with plenty of water, also under the eyelids, for at least 15

minutes. Get medical attention.

Ingestion: DO NOT induce vomiting unless directed to do so by medical personnel.

Never give anything by mouth to an unconscious person. Get medical

attention.

Symptoms: See Section 11.

5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear. In case of fire, keep containers cool with water spray.

Uncontrolled polymerization may occur at high temperatures resulting in

explosions or rupture of storage containers.

Hazardous combustion products: Oxides of carbon. Oxides of nitrogen. Oxides of sulfur. Irritating organic

vapours.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Do not allow product to enter sewer or waterways.

Clean-up methods: Remove all sources of ignition. Evacuate and ventilate spill area; dike spill to

prevent entry into water system; wear full protective equipment during cleanup. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up as much material as possible. Store in a partly filled, closed container until disposal. Refer to Section 8 "Exposure

Controls / Personal Protection" prior to clean up.

7. HANDLING AND STORAGE

Handling: Use only with adequate ventilation. Prevent contact with eyes, skin and

clothing. Do not breathe vapor and mist. Wash thoroughly after handling.

Keep container closed. Refer to Section 8.

For safe storage, store at or below 38 °C (100.4 °F) Storage:

Keep in a cool, well ventilated area away from heat, sparks and open flame.

Keep container tightly closed until ready for use.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Polyglycol dimethacrylate	None	None	None	None
Polyglycol dioctanoate	None	None	None	None
Lauryl methacrylate	None	None	None	50 ppm
Ethene, tetrafluoro-, homopolymer	None	None	None	10 mg/m3 TWA Total dust. 5 mg/m3 TWA Respirable fraction.
Vinyl acetal polymers, butyrals	None	None	None	None
Tetradecyl methacrylate	None	None	None	50 ppm TWA 75 ppm STEL
Silica, amorphous, fumed, crystal-free	10 mg/m3 TWA Inhalable dust. 3 mg/m3 TWA Respirable fraction.	20 MPPCF TWA 0.8 mg/m3 TWA	None	None
1-Acetyl-2-phenylhydrazine	None	None	None	None
Hexadecyl methacrylate	None	None	None	None
Cumene hydroperoxide	None	None	1 ppm (6 mg/m3) TWA (SKIN)	None

Engineering controls: Provide adequate local exhaust ventilation to maintain worker exposure below

exposure limits.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure

limit(s).

Eye/face protection: Safety goggles or safety glasses with side shields. Full face protection should

be used if the potential for splashing or spraying of product exists. Safety

showers and eye wash stations should be available.

Skin protection: Use chemical resistant, impermeable clothing including gloves and either an

apron or body suit to prevent skin contact. Butyl rubber gloves. Natural rubber

aloves. Neoprene gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Paste, Liquid Color: Yellow, dark Odor: Mild Odor threshold: Not available.

pH: 3.0 - 6.0

Vapor pressure: < 5 mm hg (27 °C (80.6 °F)) Boiling point/range: > 149 °C (> 300.2 °F)no method

Melting point/ range: Not available. Specific gravity: 1.15 - 1.2 Vapor density: Not available.

IDH number: 231119

Flash point: > 100 °C (> 212°F) Pensky Martens closed cup Flammable/Explosive limits - lower: Not available. Flammable/Explosive limits - upper: Not available. Autoignition temperature: Not available. Flammability: Not applicable **Evaporation rate:** Not available. Solubility in water: Not available. Partition coefficient (n-octanol/water): Not available. **VOC** content: 0.1 %; 0.99 g/l Viscosity: Not available. **Decomposition temperature:** Not available.

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions of storage and use.

Hazardous reactions: None under normal processing. Polymerization may occur at elevated temperature or in the

presence of incompatible materials.

Hazardous decomposition

products:

IDH number: 231119

Oxides of carbon. Irritating organic vapours. Oxides of nitrogen. Oxides of sulfur.

Incompatible materials: Strong oxidizing agents (peroxides, chlorine, strong acids).

Reactivity: Not available.

Conditions to avoid: Elevated temperatures. Heat, flames, sparks and other sources of ignition. Store away from

incompatible materials.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

Potential Health Effects/Symptoms

Inhalation: Inhalation of vapors or mists of the product may be irritating to the respiratory system.

Skin contact: Causes skin irritation. May cause allergic skin reaction.

Eye contact: Causes serious eye irritation.

Ingestion: May cause gastrointestinal tract irritation if swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects	
Polyglycol dimethacrylate	None	Allergen, Irritant	
Polyglycol dioctanoate	None	Irritant	
Lauryl methacrylate	Oral LD50 (Rat) = > 5.0 g/kg Oral LD50 (Mouse) = > 87,250 mg/kg	Irritant, Allergen	
Ethene, tetrafluoro-, homopolymer	None	No Target Organs	
Vinyl acetal polymers, butyrals	None	Irritant	
Tetradecyl methacrylate	None	Irritant, Allergen	
Silica, amorphous, fumed, crystal-free	None	Nuisance dust	
1-Acetyl-2-phenylhydrazine	Oral LD50 (Mouse) = 270 mg/kg	Allergen, Blood, Kidney, Mutagen, Some evidence of carcinogenicity	
Hexadecyl methacrylate	None	Irritant, Allergen	
Cumene hydroperoxide	Inhalation LC50 (Mouse, 4 h) = 200 mg/l	Allergen, Central nervous system, Corrosive	

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Polyglycol dimethacrylate	No	No	No
Polyglycol dioctanoate	No	No	No
Lauryl methacrylate	No	No	No
Ethene, tetrafluoro-, homopolymer	No	No	No
Vinyl acetal polymers, butyrals	No	No	No
Tetradecyl methacrylate	No	No	No
Silica, amorphous, fumed, crystal-free	No	No	No
1-Acetyl-2-phenylhydrazine	No	No	No
Hexadecyl methacrylate	No	No	No
Cumene hydroperoxide	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number:Not a RCRA hazardous waste.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: RQ, Environmentally hazardous substance, liquid, n.o.s.

Hazard class or division: 9
Identification number: UN 3082
Packing group: III

DOT Hazardous Substance(s): alpha,alpha-Dimethylbenzylhydroperoxide

International Air Transportation (ICAO/IATA)

Proper shipping name: RQ, Environmentally hazardous substance, liquid, n.o.s.

Hazard class or division:

Identification number: UN 3082 Packing group: Ш

Water Transportation (IMO/IMDG)

Proper shipping name: RQ, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Hazard class or division: Identification number: UN 3082 Ш

Packing group:

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12 (b) Export Notification: Ethene, tetrafluoro-, homopolymer (CAS# 9002-84-0).

CERCLA/SARA Section 302 EHS: None above reporting de minimis. CERCLA/SARA Section 311/312: Immediate Health, Delayed Health CERCLA/SARA Section 313: None above reporting de minimis.

CERCLA Reportable quantity: Cumene hydroperoxide (CAS# 80-15-9) 10 lbs. (4.54 kg)

California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This

product contains a chemical known to the State of California to cause birth defects or other

reproductive harm.

Canada Regulatory Information

IDH number: 231119

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: Reviewed SDS. Reissued with new date.

Prepared by: Sheila Gines, Regulatory Affairs Specialist

Issue date: 11/29/2016

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.