


9/5/2013

Linear Fluorescent Lamps

T8 Linear Fluorescent Lamp 32 Watt / 85 CRI / 4100K HIGH LUMEN

Project:	
Catalog#:	
Approved by:	



Ordering Information								
Howard Catalog Number (Ordering Code)	F32T8/841/HL/ECO							
UPC Code	01949							
Description	T8 Low Mercury Linear Fluorescent							
Package Quantity	25							
Physical Characteristics								
Base	Medium Bipin							
Bulb Type	T8 (8/8 inch)							
Bulb Description	Tubular Fluorescent Lamp							
Nominal Length (in)	48							
Base face to base face (Amax) (in)	47.22							
Base face to end of opposite base pin	47.40/47.78							
(Bmin/Bmax) (in)								
End of base pin to end of the opposite pin	47.67/47.78							
end (Cmin/Cmax) (in)								
Operating Characteristics								
Nominal Wattage	32							
Approximate Initial Lumen (Im)	3100							
Approximate Mean Lumen (lm)	2950							
Average Rated Life (hours)	24000							
Color Temperature (K)	4100							
Color Rendering Index (CRI)	85							



Power	1.0-									\top	_						
	0.8						-	\vdash			\vdash						
	0.6						\dashv	\vdash		+	-					_	
Relative	0.4		1				\dashv	┞		+	+					\dashv	
lati	0.2	4	\mathbb{A}		Λ		+	ackslash		\Box	Ļ					_	
Re	0.0	۸_	/ ५	_	/ \	_	_/_	1	_/_	Ψ		V	~~	_~	ム		
	40	00	45	0	50	0	5	50	6	300)	65	50	70	0	750	0
Wavelength / nm																	

Note: Rated lamp life is 24,000 hours based on 3 hours per start and 30,000 hours based on 12 hours per start. Lamp life will be affected when using occupancy sensors, dimmers, or dimming systems. These products are Low-Mercury fluorescent lamps and pass the Federal TCLP for hazardous waste. Disposal regulations may very; check local and state regulations. Specifications subject to change.

Specifications subject to change without notice.