

Kellems® Wire Management Products
PolyTuff® I Non-Metallic Liquidtight Conduit
Liquidtight Conduit

HUBBELL



Features

- No jagged metal edges
- Rigid PVC core bonded to flexible PVC jacket
- Non-metallic construction ends metal fatigue and separation problems

Ordering Information

| Description | Device Color | UPC | Catalog Number |
|-----------------------------------------------|--------------|--------------|----------------|
| Non-Metallic, PolyTuff® I Conduit, Gray | Gray | 783585333687 | G1200 |



Listings

CSA Certified
Meets requirements of NEC
UL Listed, UL Standard 1660

Online Resources

[eCatalog](#)

Specifications

| | |
|---------------------------|------------------------------------|
| Material | Co-extruded rigid and flexible PVC |
| Trade Size | 2 Inch |
| Bend Radius Inches (mm) | 10.00" (254.0) |
| Conduit ID/OD Inches (mm) | 2.03"/2.36" (51.6/59.9) |

Performance

Electrical

Voltage Rating 600V Maximum

Environmental

Operating Temperature Wet Env. 0°F to +140°F (-18°C to +60°C)
Operating Temperature Oil Env. 0°F to +158°F (-18°C to +70°C)
Operating Temperature Dry Env. 0°F to +140°F (-18°C to +60°C)

Dimensions in Inches (mm)

Hubbell Wiring Device-Kellems • Hubbell Incorporated (Delaware) • 40 Waterview Drive • Shelton, CT 06484

Phone (800) 288-6000 • Fax (800) 255-1031 • Specifications subject to change without notice.

