



# Locking Plugs, Connectors and Receptacles

## Locking Devices

Description	Catalog Numbers	Connector Receptacle Plug	
2P 3W 15A 125V Connector	<b>L515C</b>		
2P 3W Brown Duplex Receptacle	<b>L515DR</b>		
2P 3W Ivory Duplex Receptacle	<b>L515DRI</b>		
2P 3W 15A 125V Plug	<b>L515P</b>		
2P 3W 15A 125V Receptacle	<b>L515R</b>		
2P 3W 20A 125V Connector	<b>L520C</b>		
2P 3W 20A 125V Plug	<b>L520P</b>		
2P 3W 20A 125V Receptacle	<b>L520R</b>		
2P 3W 30A 125V Connector	<b>L530C</b>		
2P 3W 30A 125V Plug	<b>L530P</b>		
2P 3W 30A 125V Receptacle	<b>L530R</b>		
2P 3W 20A 250V Connector	<b>L620C</b>		
2P 3W 20A 250V Plug	<b>L620P</b>		
2P 3W 20A 250V Receptacle	<b>L620R</b>		
2P 3W 30A 250V Connector	<b>L630C</b>		
2P 3W 30A 250V Plug	<b>L630P</b>		
2P 3W 30A 250V Receptacle	<b>L630R</b>		
2P 3W 15A 277V AC Connector	<b>L715C</b>		
2P 3W 15A 277V AC Plug	<b>L715P</b>		
2P 3W 15A 277V AC Receptacle	<b>L715R</b>		
2P 3W 20A 277V AC Connector	<b>L720C</b>		
2P 3W 20A 277V AC Plug	<b>L720P</b>		
2P 3W 20A 277V AC Receptacle	<b>L720R</b>		
2P 3W 30A 277V AC Connector	<b>L730C</b>		
2P 3W 30A 277V AC Plug	<b>L730P</b>		
2P 3W 30A 277V AC Receptacle	<b>L730R</b>		
3P 4W 20A 125/250V AC Connector	<b>L1420C</b>		
3P 4W 20A 125/250V Plug	<b>L1420P</b>		
3P 4W 20A 125/250V AC Receptacle	<b>L1420R</b>		
3P 4W 30A 125/250V AC Connector	<b>L1430C</b>		
3P 4W 30A 125/250V AC Plug	<b>L1430P</b>		
3P 4W 30A 125/250V AC Receptacle	<b>L1430R</b>		
3P 4W 20A 3Ø250V AC Connector	<b>L1520C</b>		
3P 4W 20A 3Ø250V AC Plug	<b>L1520P</b>		
3P 4W 20A 3Ø250V AC Receptacle	<b>L1520R</b>		
3P 4W 30A 3Ø250V AC Connector	<b>L1530C</b>		
3P 4W 30A 3Ø250V AC Plug	<b>L1530P</b>		
3P 4W 30A 3Ø250V AC Receptacle	<b>L1530R</b>		
3P 4W 20A 3Ø480V AC Connector	<b>L1620C</b>		
3P 4W 20A 3Ø480V AC Plug	<b>L1620P</b>		
3P 4W 20A 3Ø480V AC Receptacle	<b>L1620R</b>		
3P 4W 30A 3Ø480V AC Connector	<b>L1630C</b>		
3P 4W 30A 3Ø480V AC Plug	<b>L1630P</b>		
3P 4W 30A 3Ø480V AC Receptacle	<b>L1630R</b>		



Select Spec™ locking devices provide a safe disconnect solution between an equipment load and a power source. These devices incorporate a locking interface that is engaged and disengaged simply by rotating the device assuring a safe and reliable electrical connection. Locking devices are used on a wide range of industrial, MRO & OEM, and construction applications for providing a secure electrical connection. Uses include plant floor equipment wiring, ceiling power drops, extension cords and portable equipment. The product line includes plugs, connectors and receptacles in 15, 20 and 30 amperages and common voltage ratings.



**L730P**



**L730C**



**L730R**

