

HEAVY-DUTY AIR CIRCULATORS - 115V PEDESTAL, WALL, I-BEAM & CEILING MOUNT FANS Oscillating

5 Year Warranty - Ultra Quiet

FEATURES

- Energy Efficient - Lowest Watts Per CFM
- Ultra Quiet Die Cast Aluminum Airfoil Propeller
- Excellent for Churches, Schools, Industrial and Commercial Applications
- Includes Cord and Plug
- Wall and I-Beam Mounts Able To Be Installed By One Individual

- Meets OSHA Standards & UL / CUL Listed
- 3 Speed Motor
- 1/5 HP (18" & 20") and 1/3 HP (24" & 30"), 115V, 1 Phase, Totally Enclosed, Ball Bearing Motor
- 26" Base (18" & 20"); 32" Base (24" & 30")
- Patented Modular Motor End Dome for easy maintenance
- UPS Shippable
- All Stocked



Adjustable Pedestal



PERFORMANCE 115V

Prop Dia.	CFM			RPM			Motor Number	F.L. Amps
	High	Med.	Low	High	Med.	Low		
18"	2600	2113	1805	1125	915	780	967J (Osc.)	1.41
20"	3100	2060	1657	1120	745	600	967J (Osc.)	1.65
24"	5387	4356	3125	1070	850	628	967 (Osc.)	2.5
30"	7996	5859	4063	1045	789	561	967 (Osc.)	2.9

Performance Ratings are conducted in accordance with AMCA Standard 230-99.

UNIT PACKS Motor, Specified Mounting, Propeller & Guard Shipped In A Single Carton

OSCILLATING MODELS - 967 MOTOR

Prop Dia.	Fan Style	EDP Number	Catalog No. 115V	HP	Ship Wt.	List Price
18"	Pedestal Fan	20894	UP18BN-S	1/5	71	\$740
	Wall Mount	20903	UP18WN-S8	1/5	51	\$680
	I-Beam Mount	20908	UP18IN-S	1/5	54	\$738
	Ceiling Mount	N/A	N/A	---	---	---
20"	Pedestal Fan	20898	UP20BN-S	1/5	72	\$790
	Wall Mount	20904	UP20WN-S8	1/5	52	\$730
	I-Beam Mount	20909	UP20IN-S	1/5	55	\$780
	Ceiling Mount	N/A	N/A	---	---	---
24"	Pedestal Fan	20885	UP24BN-S	1/3	89	\$1176
	Wall Mount	37129	UP24WN-S8	1/3	60	\$1092
	I-Beam Mount	37147	UP24IN-S	1/3	63	\$1153
	Ceiling Mount	N/A	N/A	---	---	---
30"	Pedestal Fan	20890	UP30BN-S	1/3	95	\$1236
	Wall Mount	37135	UP30WN-S8	1/3	64	\$1152
	I-Beam Mount	37148	UP30IN-S	1/3	67	\$1215
	Ceiling Mount	N/A	N/A	---	---	---



Wall Mount



Ceiling Mount

A safety cable kit is included in all overhead mounted air circulators to prevent the fan from falling if accidentally struck or mounting fails. Single safety cable kits consist of 12 feet of 1/16" diameter cable, 2 cable clamps and instructions.



I-Beam Mount

MOTOR TILT ADJUSTMENTS

TYPE	TILT UP OR DOWN (IN DEGREES)			
	OSCILLATING		NON-OSCILLATING	
	UP	DOWN	UP	DOWN
FLOOR	20°	10°	20°	10°
WALL	20°	10°	20°	15°
I-BEAM	20°	20°	20°	20°
CEILING	N/A	N/A	N/A	N/A

0° = Horizontal Plane

NOTES:

Oscillating motor not to be used upside down.
See page 6 for optional accessories.

