

Product availability : Stock - Normally stocked in distribution facility



Main

| | |
|------------------------------|-----------------------------|
| Range | Multi 9 |
| Product or component type | Undervoltage release |
| Device short name | MN |
| [Uc] control circuit voltage | 48 V AC 50/60 Hz 48 V DC |
| Control type | Standard |
| 9 mm pitches | 2 |

Complementary

| | |
|-------------------------|--|
| Range compatibility | Multi 9: Multi 9 C60 C60BP Multi 9: Multi 9 C60 C60BPR Multi 9: Multi 9 C60 C60SP Multi 9: Multi 9 GFP GFP Multi 9: Multi 9 C60H-DC C60H-DC |
| Local signalling | Action indicator |
| Mounting mode | Fixed |
| Mounting support | DIN rail |
| Height | 3.25 in (82.5 mm) |
| Width | 0.71 in (18 mm) |
| Depth | 2.68 in (68 mm) |
| Product weight | 0.15 lb(US) (0.066 kg) |
| Connections - terminals | Clamp terminal bottom 1 cable(s) 0 in ² (2.5 mm ²) rigid (AWG 14) Clamp terminal bottom 2 cable(s) 0 in ² (1.5 mm ²) rigid (AWG 16) |
| Wire stripping length | 0.35 in (9 mm) bottom |
| Tightening torque | 8.85 lbf.in (1 N.m) bottom |

Environment

| | |
|-----------|----------------|
| Standards | EN/IEC 60947-1 |
|-----------|----------------|

EN 60947-2

| | |
|---------------------------------------|----------------------------|
| Product certifications | UR PCT UL CSA |
| Pollution degree | 3 |
| Ambient air temperature for operation | -13...122 °F (-25...50 °C) |
| Ambient air temperature for storage | -40...185 °F (-40...85 °C) |

Ordering and shipping details

| | |
|-----------------------|----------------------------------|
| Category | 00948 - M9 GEN 2 CB UL1077 / IEC |
| Discount Schedule | DE2 |
| GTIN | 00785901761334 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 0.14999999999999999 |
| Returnability | Y |
| Country of origin | BE |