

Product data sheet

Characteristics

QOU230

QOU Miniature Circuit Breaker, 30A, 2P,
120/240V, 10kA

Product availability : Stock - Normally stocked in distribution facility



Main

Product or component type	Miniature circuit-breaker
Range of product	QOU
Circuit breaker type	Standard
Circuit breaker application	HACR and Switching Duty rated

Complementary

Line Rated Current	30 A
Poles description	2P
Breaking capacity	10 kA at: 120/240 V AC 5 kA at: 48 V DC
Electrical connection	Slotted box lugs, line side Slotted box lugs, load side
System Voltage	120/240 V AC 48 V DC
Mounting mode	Unit mount
AWG gauge	AWG 14...AWG 2 (aluminium/copper)
Height	4.05 in
Depth	2.95 in
Width	1.5 in

Environment

Product certifications	UL listed IEC CSA
------------------------	-------------------------

Ordering and shipping details

Category	00900 - QOU BREAKERS & SWITCH
----------	-------------------------------

Discount Schedule	DE2
GTIN	00785901418719
Nbr. of units in pkg.	24
Package weight(Lbs)	0.7600000000000001
Returnability	Y
Country of origin	MX

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1323 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------