

# XB4BA941

red flush reset pushbutton Ø22 for 30...130 mm  
actuation distance

Product availability : Stock - Normally stocked in distribution facility



## Main

Range of product	Harmony XB4
Product or component type	Complete manual overload reset push-button
Device short name	XB4
Bezel material	Chromium plated metal
Fixing collar material	Zamak
Mounting diameter	0.87 in (22 mm)
Operator profile	Red flush unmarked
Activating distance	1.18...5.12 in (30...130 mm)

## Complementary

Product weight	0.13 lb(US) (0.058 kg)
Resistance to high pressure washer	1015.26 psi (7000000 Pa) at 131 °F (55 °C), distance: 0.1 m
Shape of signaling unit head	Round
Operating travel	0.55 in (14 mm)
Mechanical durability	5000000 cycles
Compatibility code	XB4

## Environment

Protective treatment	TH
Ambient air temperature for storage	-40...158 °F (-40...70 °C)
Ambient air temperature for operation	-40...158 °F (-40...70 °C)
Electrical shock protection class	Class I conforming to IEC 60536
IP degree of protection	IP66 conforming to IEC 60529
NEMA degree of protection	NEMA 13 NEMA 4X
IK degree of protection	IK03 conforming to IEC 50102
Standards	EN/IEC 60947-5-1

EN/IEC 60947-5-4  
JIS C 4520  
EN/IEC 60947-5-5  
CSA C22.2 No 14  
UL 508  
EN/IEC 60947-1

---

Product certifications	GL DNV LROS (Lloyds register of shipping) BV CSA UL listed RINA
------------------------	---

---

### Ordering and shipping details

---

Category	22468 - PUSHBUTTONS,22MM(METAL) NEW
Discount Schedule	CS2
GTIN	00785901371182
Nbr. of units in pkg.	1
Package weight(Lbs)	0.14999999999999999
Returnability	Y
Country of origin	FR

---

### Contractual warranty

---

Warranty period	18 months
-----------------	-----------

---