





WSPS20LED3K 20 Watt LED SlimPak











Project Informa Job Name	pject Information Name	
Fixture Type	20 Watt LED Die Cast SlimPak	
Catalog Number	WSPS20LED3K	
Annroyed by		

SPECIFICATIONS:

Lumens: 2125 **Watts:** 19.82

Lumens/Watt: 107.20

CRI: 83.2 **CCT:** 2929

Lifespan: 200,000+ hrs.¹

Construction:

Designed for commercial and industrial applications, providing cooler operating temperatures, brighter light and longer LED life. Apertures for field or factory installed photocontrol. Hinged at bottom to prevent leakage.

Installations

Labor saving features including bubble level and removable hinged face frame.

Zero Glare:

The fixture design directs more light down and forward without wasting lumens and offensive light.

Thermal Management:

Atlas SlimPak Pro fixtures are designed as a complete system to optimize LED life and light output. The Patent Pending thermal stacking heat removal technology extracts heat from within the housing moving it away from LEDs and components. The lower temperatures result in long LED life (200,000+ hrs) and component life and also allows for higher light output.

Listings:

Luminaire is certified to UL/cUL Standards for Wet Locations IDA Listed

DesignLights Consortium qualified luminaire, eligible for rebates from DLC member utilities. DLC Product ID: P0UYUSJ3

AC Input:

120/208/240/277 V

Driver

Constant current, Class 2, 120-277 VAC, 50-60 Hz High Efficiency – min. 85% Off-State Power: 0 Watts 0-10 V Dimming

LEDs

3000K CCT

Testing:

Atlas LED luminaires have been tested by an independent laboratory in accordance with IESNA LM-79 & LM-80.

Warranty: Five-year limited warranty

Photo Control:


For factory installed 120V button photo control add suffix PC to part number. Atlas uses only premium LED compatible photocontrols.





Patent Pending

DIMENSIONS:



Rebates and Incentives are available in many areas. Contact an Atlas Representative for more information.





PHOTOMETRIC

