

PART NUMBER	UNIT OF ISSUE	ITEMS PER UNIT OF ISSUE	UPC	NSN	PRODUCT NAME	ITEM EXPANDED DESCRIPTION
60510024536	Case	5	00051119558074		3M(TM) Cloth Belt 970DZ, 37 in x 60 in P120, 5 per case	Premium Cubitron(TM) abrasive grain open coat, non-loading belt on Y weight heavy, strong cloth backing with anti-static property. Resin bonded for heat resistance. Use for intermediate and finish
61500039419	Case	10	00048011089164		Scotch-Brite(TM) Surface Conditioning Belt Maroon/Maroon, 2 in x 60 in A MED, 10 per case	Non-woven and reinforced backing with good flexibility. Use for cleaning, finishing, blending and deburring applications. Abrasive mineral medium grade aluminum oxide. MOS 6500 SFPM.
60430036347	Case	25	00051144814435		3M(TM) Cloth Belt 777F, 4 in x 132 in P120, 25 per case	Cubitron(TM) abrasive grain and aluminum oxide mineral coated on YF weight heavy polyester cloth backing. Resin bonded for heat resistance. Includes grinding aid for cooler grinding and optimum
60510024528	Case	5	00051119558067		3M(TM) Cloth Belt 970DZ, 37 in x 60 in P100, 5 per case	Premium Cubitron(TM) abrasive grain open coat, non-loading belt on Y weight heavy, strong cloth backing with anti-static property. Resin bonded for heat resistance. Use for intermediate and finish
60430036289	Case	50	00051144767380		3M(TM) Cloth Belt 777F, 2 in x 48 in 36, 50 per case	Cubitron(TM) abrasive grain and aluminum oxide mineral coated on YF weight heavy polyester cloth backing. Resin bonded for heat resistance. Includes grinding aid for cooler grinding and optimum
60430036271	Case	50	00051144776634		3M(TM) Cloth Belt 777F, 2 in x 60 in 36, 50 per case	Cubitron(TM) abrasive grain and aluminum oxide mineral coated on YF weight heavy polyester cloth backing. Resin bonded for heat resistance. Includes grinding aid for cooler grinding and optimum
60510024510	Case	3	00051119558050		3M(TM) Cloth Belt 970DZ, 37 in x 60 in 80, 3 per case	Premium Cubitron(TM) abrasive grain open coat, non-loading belt on Y weight heavy, strong cloth backing with anti-static property. Resin bonded for heat resistance. Use for intermediate and finish
61500103314	Case	10	00048011175171		Scotch-Brite(TM) Surface Conditioning Belt Blue/Blue, 1 in x 18 in A VFN, 10 per case	Non-woven and reinforced backing with good flexibility. Use for cleaning, finishing, blending and deburring applications. Abrasive mineral very fine grade aluminum oxide. MOS 6500 SFPM.
60430036263	Case	50	00051144765324		3M(TM) Cloth Belt 777F, 2 1/2 in x 60 in 36, 50 per case	Cubitron(TM) abrasive grain and aluminum oxide mineral coated on YF weight heavy polyester cloth backing. Resin bonded for heat resistance. Includes grinding aid for cooler grinding and optimum
60510024502	Case	5	00051119558043		3M(TM) Regal(TM) Xodust(TM) Plus Paper Belt, 970DZ, 50 in x 103 in, P150 Grade	Regal(TM) Xodust(TM) Plus Paper. P150 Grade
61500039310	Case	10	00048011089065		Scotch-Brite(TM) Surface Conditioning Belt Maroon/Maroon, 3 in x 21 in A MED, 10 per case	Non-woven and reinforced backing with good flexibility. Use for cleaning, finishing, blending and deburring applications. Abrasive mineral medium grade aluminum oxide. MOS 6500 SFPM.
61500103306	Case	20	00048011175164		Scotch-Brite(TM) Surface Conditioning Belt, SC-BS, Gray/Gray, 1/2 in x 24 in, SFN Grade	Non-Woven, Provides More Consistent, Appealing Finish In Decorative Finishing. Resists Loading And Reduces Heat Build-Up. S Mineral, SFN Grade
60430036248	Case	50	00051144765317		3M(TM) Cloth Belt 777F, 2 in x 72 in 36, 50 per case	Cubitron(TM) abrasive grain and aluminum oxide mineral coated on YF weight heavy polyester cloth backing. Resin bonded for heat resistance. Includes grinding aid for cooler grinding and optimum
60430049159	Case	25	00051144853786		3M(TM) Cloth Belt 977F, 3 in x 132 in 80, 25 per case	Premium Cubitron(TM) abrasive grain mineral on YF weight heavy polyester cloth backing. Resin bonded for heat resistance. Includes grinding aid for cooler grinding. Can be run wet or dry. Use for
60510024494	Case	5	00051119558036		3M(TM) Cloth Belt 970DZ, 50 in x 103 in P120, 5 per case	Premium Cubitron(TM) abrasive grain open coat, non-loading belt on Y weight heavy, strong cloth backing with anti-static property. Resin bonded for heat resistance. Use for intermediate and finish
61500103298	Case	20	00048011175157		Scotch-Brite(TM) Surface Conditioning Belt Maroon/Maroon, 1/2 in x 12 in A MED, 20 per case	Non-woven and reinforced backing with good flexibility. Use for cleaning, finishing, blending and deburring applications. Abrasive mineral medium grade aluminum oxide. MOS 6500 SFPM.
61500039302	Case	10	00048011089058		Scotch-Brite(TM) Surface Conditioning Belt, SC-BS, Maroon/Maroon, 2 in x 34 in, MED Grade	Non-Woven, Provides More Consistent, Appealing Finish In Decorative Finishing. Resists Loading And Reduces Heat Build-Up. A Mineral, MED Grade
60430043038	Case	50	00051144853779		3M(TM) Cloth Belt 777F, 2 in x 60 in P120, 50 per case	Cubitron(TM) abrasive grain and aluminum oxide mineral coated on YF weight heavy polyester cloth backing. Resin bonded for heat resistance. Includes grinding aid for cooler grinding and optimum
60430036230	Case	50	00051144775132		3M(TM) Regalite(TM) Polycut(TM) Resin Bond Cloth Belt, 777F, 3 in x 120 in, 36 Grade	Regalite(TM) Polycut(TM) Resin Bond Cloth. 36 Grade, YF Weight, FILM-LOK Splice
61500039252	Case	10	00048011089003		Scotch-Brite(TM) Surface Conditioning Belt, SC-BS, Maroon/Maroon, 4 in x 36 in, MED Grade	Non-Woven, Provides More Consistent, Appealing Finish In Decorative Finishing. Resists Loading And Reduces Heat Build-Up. A Mineral, MED Grade
60430036214	Case	50	00051144142644		3M(TM) Regalite(TM) Polycut(TM) Resin Bond Cloth Belt, 777F, 2 in x 132 in, 36 Grade	Regalite(TM) Polycut(TM) Resin Bond Cloth. 36 Grade, YF Weight, FILM-LOK Splice
60510024460	Case	5	00051119558005		3M(TM) Cloth Belt 970DZ, 36 in x 75 in P150, 5 per case	Premium Cubitron(TM) abrasive grain open coat, non-loading belt on Y weight heavy, strong cloth backing with anti-static property. Resin bonded for heat resistance. Use for intermediate and finish
61500039237	Case	10	00048011088983		Scotch-Brite(TM) Surface Conditioning Belt Maroon/Maroon, 1 in x 30 in A MED, 10 per case	Non-woven and reinforced backing with good flexibility. Use for cleaning, finishing, blending and deburring applications. Abrasive mineral medium grade aluminum oxide. MOS 6500 SFPM.
60430036206	Case	25	00051144765331		3M(TM) Cloth Belt 777F, 3 in x 132 in 36, 25 per case	Cubitron(TM) abrasive grain and aluminum oxide mineral coated on YF weight heavy polyester cloth backing. Resin bonded for heat resistance. Includes grinding aid for cooler grinding and optimum
61500039187	Case	5	00048011088938		Scotch-Brite(TM) Surface Conditioning Belt Gray/Gray, 3 in x 132 in S SFN, 5 per case	Non-woven and reinforced backing with good flexibility. Use for cleaning, finishing, blending and deburring applications. Abrasive mineral super fine grade silicon carbide. MOS 6500 SFPM.
60510024452	Case	5	00051119557992		3M(TM) Cloth Belt 970DZ, 36 in x 75 in P120, 5 per case	Premium Cubitron(TM) abrasive grain open coat, non-loading belt on Y weight heavy, strong cloth backing with anti-static property. Resin bonded for heat resistance. Use for intermediate and finish
60430036198	Case	50	00051144765348		3M(TM) Regalite(TM) Polycut(TM) Resin Bond Cloth Belt, 777F, 4 in x 132 in, 36 Grade	Regalite(TM) Polycut(TM) Resin Bond Cloth. 36 Grade, YF Weight, FILM-LOK Splice
61500039146	Case	10	00048011088891		Scotch-Brite(TM) Surface Conditioning Belt, SC-BS, Brown/Brown, 2 in x 18 15/16 in, CRS Grade	Non-Woven, Provides More Consistent, Appealing Finish In Decorative Finishing. Resists Loading And Reduces Heat Build-Up. A Mineral, CRS Grade
60510024445	Case	5	00051119557985		3M(TM) Cloth Belt 970DZ, 36 in x 75 in P100, 5 per case	Premium Cubitron(TM) abrasive grain open coat, non-loading belt on Y weight heavy, strong cloth backing with anti-static property. Resin bonded for heat resistance. Use for intermediate and finish
61500039120	Case	10	00048011088877		Scotch-Brite(TM) Surface Conditioning Belt Brown/Brown, 1 in x 30 in A CRS, 10 per case	Non-woven and reinforced backing with good flexibility. Use for cleaning, finishing, blending and deburring applications. Abrasive mineral coarse grade aluminum oxide. MOS 6500 SFPM.