

PART NUMBER	UNIT OF ISSUE	ITEMS PER UNIT OF ISSUE	UPC	NSN	PRODUCT NAME	ITEM EXPANDED DESCRIPTION
61500125705	Case	20	00048011196886		Scotch-Brite(TM) Surface Conditioning Belt Blue/Blue, 1/2 in x 12 in A VFN, 20 per case	Non-woven and reinforced backing with good flexibility. Use for cleaning, finishing, blending and deburring applications. Abrasive mineral very fine grade aluminum oxide. MOS 6500 SFPM.
61500072857	Case	10	00048011005850		Scotch-Brite(TM) Surface Conditioning Belt Maroon/Maroon, 4 in x 24 in A MED, 10 per case	Non-woven and reinforced backing with good flexibility. Use for cleaning, finishing, blending and deburring applications. Abrasive mineral medium grade aluminum oxide. MOS 6500 SFPM.
61500073020	Case	5	00048011139449		Scotch-Brite(TM) Surface Conditioning LS Belt Blue/Blue, 2 in x 132 in A VFN, 5 per case	Non-woven and firm with stretch resistant backing for high belt tensions. Use for cleaning, finishing, blending and deburring applications. Abrasive mineral very fine grade aluminum oxide. MOS 6500
61500067691	Case	1	00048011145372		Scotch-Brite(TM) Surface Conditioning LS Belt Maroon/Maroon, 37 in x 60 in A MED, 1 per case	Non-woven and firm with stretch resistant backing for high belt tensions. Use for cleaning, finishing, blending and deburring applications. Abrasive mineral medium grade aluminum oxide. MOS 6500
61500108065	Case	1	00048011178776		Scotch-Brite(TM) Surface Conditioning LS Belt Blue/Blue, 37 in x 60 in A VFN, 1 per case	Non-woven and firm with stretch resistant backing for high belt tensions. Use for cleaning, finishing, blending and deburring applications. Abrasive mineral very fine grade aluminum oxide. MOS 6500
61500073145	Case	5	00048011139517		Scotch-Brite(TM) Surface Conditioning LS Belt Maroon/Maroon, 4 in x 132 in A MED, 5 per case	Non-woven and firm with stretch resistant backing for high belt tensions. Use for cleaning, finishing, blending and deburring applications. Abrasive mineral medium grade aluminum oxide. MOS 6500
61500067667	Case	5	00048011145341		Scotch-Brite(TM) Surface Conditioning LS Belt Maroon/Maroon, 6 in x 48 in A MED, 5 per case	Non-woven and firm with stretch resistant backing for high belt tensions. Use for cleaning, finishing, blending and deburring applications. Abrasive mineral medium grade aluminum oxide. MOS 6500
60980018802	Case	5	00051144828982		3M(TM) Belt Pack 524S, 1/2 in x 24 in, 5 per case	Contains 2 ea of 60YF, 80YF and 120YF 3M(TM) Coated Abrasive Belt 777F, and 1 ea of AVFN, AMED and ACRS Scotch-Brite(TM) Surface Conditioning Belt 1/2 in x 24 in.
60420009007	Case	200	00051144267231		3M(TM) Cloth Belt 241E, 1/2 in x 24 in 60 XE wt, 200 per case	Aluminum oxide belt constructed on XE weight durable rayon cloth backing. Resin bonded for heat resistance.
60410002483	Case	50	00051144802449		3M(TM) Cloth Belt 200D, 9 in x 7 15/32 in P150 J wt, 50 per case	Aluminum oxide open coat, non-loading belt constructed on J weight light, flexible cloth backing. Resin bonded for heat resistance.
60410001873	Case	20	00051144773299		3M(TM) Cloth Belt 200D, 9 in x 20 in 80 J wt, 20 per case	Aluminum oxide open coat, non-loading belt constructed on J weight light, flexible cloth backing. Resin bonded for heat resistance.
60410001857	Case	50	00051144773275		3M(TM) Cloth Belt 200D, 9 in x 10 39/64 in 80 J wt, 50 per case	Aluminum oxide open coat, non-loading belt constructed on J weight light, flexible cloth backing. Resin bonded for heat resistance.
60420008934	Case	200	00051144770397		3M(TM) Cloth Belt 241E, 3/4 in x 20 1/2 in 60 XE wt, 200 per case	Aluminum oxide belt constructed on XE weight durable rayon cloth backing. Resin bonded for heat resistance.
60420008900	Case	200	00051144323999		3M(TM) Cloth Belt 241E, 1/2 in x 24 in 240 XE wt, 200 per case	Aluminum oxide belt constructed on XE weight durable rayon cloth backing. Resin bonded for heat resistance.
60410001808	Case	20	00051144773220		3M(TM) Cloth Belt 200D, 9 in x 13 3/4 in P100 J wt, 20 per case	Aluminum oxide open coat, non-loading belt constructed on J weight light, flexible cloth backing. Resin bonded for heat resistance.
60410001790	Case	50	00051144773213		3M(TM) Cloth Belt 200D, 9 in x 10 39/64 in P100 J wt, 50 per case	Aluminum oxide open coat, non-loading belt constructed on J weight light, flexible cloth backing. Resin bonded for heat resistance.
60510025871	Case	5	00051144832262		3M(TM) Paper Belt 362UZ, 50 in x 103 in P120, 5 per case	An aluminum oxide open coat, non-loading paper belt constructed on a F weight, extra heavy paper backing. Features an anti-static property. Grade: P120. Primary market: woodworking.
60420008777	Case	200	00051144814824		3M(TM) Cloth Belt 707E, 1/2 in x 24 in 80, 200 per case	Cubitron(TM) abrasive grain mineral coated on JE weight flexible rayon cloth backing. Resin bonded for heat resistance. Includes grinding aid for cooler grinding.
60510025830	Case	5	00051144828197		3M(TM) Paper Belt 362UZ, 52 in x 75 in P150, 5 per case	An aluminum oxide open coat, non-loading paper belt constructed on a F weight, extra heavy paper backing. Features an anti-static property. Grade: P150. Primary market: woodworking.
60510025095	Case	2	00051144816552		3M(TM) Cloth Belt 361F, 37 in x 75 in 80, 2 per case	Aluminum oxide open coat mineral on YF weight heavy polyester cloth backing. Resin bonded for heat resistance. Can be run wet or dry. Use for dry grinding and finishing wood, plastic, leather and
60430048144	Case	50	00051144839094		3M(TM) Cloth Belt 361F, 2 1/2 in x 72 in P120, 50 per case	Aluminum oxide open coat mineral on YF weight heavy polyester cloth backing. Resin bonded for heat resistance. Can be run wet or dry. Use for dry grinding and finishing wood, plastic, leather and
60430044945	Case	20	00051144836185		3M(TM) Cloth Belt 361F, 6 in x 120 in P120, 20 per case	Aluminum oxide open coat mineral on YF weight heavy polyester cloth backing. Resin bonded for heat resistance. Can be run wet or dry. Use for dry grinding and finishing wood, plastic, leather and
60510018561	Case	5	00051144825189		3M(TM) Three-M-ite(TM) Resin Bond Cloth Open Coat Belt, 270D, 50 in x 103 in, 180 Grade	Aluminum oxide open coat, non-loading mineral on Y weight heavy, strong cloth backing. Resin bonded for heat resistance. Use for intermediate wood sanding, off-hand grinding of aluminum
60510017563	Case	3	00051144813667		3M(TM) Cloth Belt 270D, 36 in x 103 in 80, 3 per case	Aluminum oxide open coat, non-loading mineral on Y weight heavy, strong cloth backing. Resin bonded for heat resistance. Use for intermediate wood sanding, off-hand grinding of aluminum
60510017225	Case	5	00051144810901		3M(TM) Cloth Belt 270D, 50 in x 103 in 150, 5 per case	Aluminum oxide open coat, non-loading mineral on Y weight heavy, strong cloth backing. Resin bonded for heat resistance. Use for intermediate wood sanding, off-hand grinding of aluminum
60510026259	Case	5	00051144800377		3M(TM) Cloth Belt 361F, 37 in x 75 in P150, 5 per case	Aluminum oxide belt on XF weight, water resistant polyester cloth backing. Resin bonded for heat resistance. Can be run wet or dry.
60510026200	Case	5	00051144149056		3M(TM) Cloth Belt 361F, 37 in x 60 in P100, 5 per case	Aluminum oxide open coat mineral on YF weight heavy polyester cloth backing. Resin bonded for heat resistance. Can be run wet or dry. Use for dry grinding and finishing wood, plastic, leather and
60510014198	Case	5	00051144803477		3M(TM) Cloth Belt 270D, 43 in x 75 in 100, 5 per case	Aluminum oxide open coat, non-loading mineral on Y weight heavy, strong cloth backing. Resin bonded for heat resistance. Use for intermediate wood sanding, off-hand grinding of aluminum
60430043129	Case	25	00051144853861		3M(TM) Cloth Belt 977F, 4 in x 132 in 50, 25 per case	Premium Cubitron(TM) abrasive grain mineral on YF weight heavy polyester cloth backing. Resin bonded for heat resistance. Includes grinding aid for cooler grinding. Can be run wet or dry. Use for
60510013364	Case	5	00051144144501		3M(TM) Cloth Belt 270D, 36 in x 75 in 150, 5 per case	Aluminum oxide open coat, non-loading mineral on Y weight heavy, strong cloth backing. Resin bonded for heat resistance. Use for intermediate wood sanding, off-hand grinding of aluminum