



# Repulpable Flying Splice Tape

## 906B (Blue) • 906W (White)

Technical Data

March 2014

**Product Description** 3M™ Repulpable Tape 906 is a light-weight tissue coated on both sides with a high tack, high shear strength, repulpable adhesive and is on a repulpable easy-release paper liner.

Construction	Adhesive	Liner	Std. Roll Length
	High tack, repulpable	Silicone-coated, semi-bleached kraft paper	33 m (36 yds)

### Typical Physical Properties and Performance Characteristics

**Note: The following technical information and data should be considered representative or typical only and should not be used for specification purposes.**

Repulpability:	Tape - Completely* Liner - Completely*
Tape Thickness:	3.0 mils (.075 mm) without liner
Bonding Strength:	Delaminates most papers
Heat Resistance:	Excellent to 400°F (204°C) web temperature

\*Repulpability judged according to TAPPI UM-213, Procedure A.

### Features

- All components of the adhesive and backing meet the requirements of indirect food additive regulations as described under 21 CFR 176.170 (Components of paper and paperboard in contact with aqueous and fatty food) and 21 CFR 176.180 (Components of paper and paperboard in contact with dry foods).
- Packing in sealed plastic bags helps protect constant moisture content of unused tape.
- Water solubility and alkali dispersibility are excellent and eliminate danger of contaminating the paper mill broke with non-repulpable material. Poor quality paper and plugged Fourdrinier screens can often be caused by non-repulpable rubber-based splicing media.
- Improved adhesive formulation for high adhesion – even to treated papers and strong splices to help save money.
- Totally repulpable construction so no need to remove splice from waste and prevents broke contamination caused by non-repulpable splice material to help save labor and increase value of waste paper.
- Tissue reinforced for smoother surface contact, improves splice strength to wider range of papers to help increase splice success ratio.
- Not recommended for finished roll splices or where oozing and bleeding may occur.

# 3M™ Repulpable Flying Splice Tape

906B (Blue) • 906W (White)

---

**Application Techniques** For optimum results, firm even rub down pressure must be applied to the taped area to create the best possible adhesion between the tape and paper surface. A plastic squeegee or similar tool can help achieve the proper uniform pressure.

---

**Application Ideas**

- Flying splice at Off Machine Coater.
- Splicing tape on Automatic Splicing Equipment.

---

**Major Industries**

- Paper mills.
- Web printers, bag makers, etc.
- Paper converters.

---

**Storage** Store in a clean, dry place at 70°F (21°C), and 50% relative humidity in the sealed plastic bags until ready for use.

---

**Shelf Life** For best results, use within 18 months of date of manufacture.

---

**Product Use** All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

---

**Warranty and Limited Remedy** Unless stated otherwise in 3M's product literature, packaging inserts or product packaging for individual products, 3M warrants that each 3M product meets the applicable specifications at the time 3M ships the product. Individual products may have additional or different warranties as stated on product literature, package inserts or product packages. 3M MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's application. If the 3M product is defective within the warranty period, your exclusive remedy and 3M's and seller's sole obligation will be, at 3M's option, to replace the product or refund the purchase price.

---

**Limitation of Liability** Except where prohibited by law, 3M and seller will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.



This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001:2000 standards.



**Industrial Business  
Industrial Adhesives and Tapes Division**

3M Center, Building 225-3S-06  
St. Paul, MN 55144-1000  
800-362-3550 • 877-369-2923 (fax)  
www.3M.com/industrial



Recycled Paper  
40% pre-consumer  
10% post-consumer

3M is a trademark of 3M Company.  
Printed in U.S.A.  
©3M 2014 (3/14)