

Chipping Hammers

“A” Series

Industrial Duty

Renowned for its valve life and handle durability, this classic tool is widely used throughout industry and construction. It is ideal for light demolition work, bridge decking, concrete surface preparation, metal removal, form stripping, and many other applications. It is available in a 1, 2, 3 or 4 in. piston stroke with your choice of .580 hex or .680 round shank. Uses oval collar accessories.

- Grooved barrel, lock spring retainer
- Swan neck handle
- Outside trigger
- Time tested valve durability
- Replaceable piston
- Long nozzle for extra life



3A2SA
*Units ending in 'A' include a retainer as standard. Those ending in 'S' do not.

“W” Series

Heavy Duty

Same tough specifications as the “A” series units, but with a heavy duty front end featuring a threaded barrel and rubber buffered retainer for increased steel and retainer life. Uses round collared accessories.



W3A2
Screw on retainers are standard on all 'W' units.

Model	Weight less Chisel		Length		Piston Stroke		Bore		Blows per Minute	Chisel Retainer in.	Hose Connector Pipe Tap in.	Size Hose Recomm. mm	CFM	
	lb.	kg	in.	mm	in.	mm	in.	mm						
'A' Series Industrial Duty Chippers														
With .580" Hex Nozzle — uses Hex Shank Oval Collar Chisels														
1A1S	12 ³ / ₄	5.78	13 ¹ / ₂	343	1	25	1 ¹ / ₈	28	2500	None	³ / ₈	¹ / ₂	13	28
1A1SA	14 ³ / ₄	6.69	15 ¹ / ₂	394	1	25	1 ¹ / ₈	28	2500	Plain	³ / ₈	¹ / ₂	13	28
2A1S	13 ¹ / ₈	5.95	14	356	2	51	1 ¹ / ₈	28	2300	None	³ / ₈	¹ / ₂	13	28
2A1SA	15 ¹ / ₈	6.86	16	406	2	51	1 ¹ / ₈	28	2300	Plain	³ / ₈	¹ / ₂	13	28
3A1S	14 ⁵ / ₈	6.63	15 ⁷ / ₈	403	3	76	1 ¹ / ₈	28	1725	None	³ / ₈	¹ / ₂	13	29
3A1SA	16 ⁵ / ₈	7.54	17 ⁷ / ₈	454	3	76	1 ¹ / ₈	28	1725	Plain	³ / ₈	¹ / ₂	13	29
4A1S	15 ¹ / ₂	7.03	16 ⁷ / ₈	429	4	102	1 ¹ / ₈	28	1480	None	³ / ₈	¹ / ₂	13	29
4A1SA	17 ¹ / ₂	7.94	18 ⁷ / ₈	480	4	102	1 ¹ / ₈	28	1480	Plain	³ / ₈	¹ / ₂	13	29
With .680" Round Nozzle — uses Round Shank Oval Collar Chisels														
1A2S	13 ³ / ₄	5.78	13 ¹ / ₂	343	1	25	1 ¹ / ₈	28	2500	None	³ / ₈	¹ / ₂	13	28
1A2SA	14 ³ / ₄	6.69	15 ¹ / ₂	394	1	25	1 ¹ / ₈	28	2500	Plain	³ / ₈	¹ / ₂	13	28
2A2S	13 ¹ / ₈	5.95	14	356	2	51	1 ¹ / ₈	28	2300	None	³ / ₈	¹ / ₂	13	28
2A2SA	15 ¹ / ₈	6.86	16	406	2	51	1 ¹ / ₈	28	2300	Plain	³ / ₈	¹ / ₂	13	28
3A2S	14 ⁵ / ₈	6.63	15 ⁷ / ₈	403	3	76	1 ¹ / ₈	28	1725	None	³ / ₈	¹ / ₂	13	29
3A2SA	16 ⁵ / ₈	7.54	17 ⁷ / ₈	454	3	76	1 ¹ / ₈	28	1725	Plain	³ / ₈	¹ / ₂	13	29
4A2S	15 ¹ / ₂	7.03	16 ⁷ / ₈	429	4	102	1 ¹ / ₈	28	1480	None	³ / ₈	¹ / ₂	13	29
4A2SA	17 ¹ / ₂	7.94	18 ⁷ / ₈	480	4	102	1 ¹ / ₈	28	1480	Plain	³ / ₈	¹ / ₂	13	29
'W' Series Heavy Duty Chippers														
With .580" Hex Nozzle — to use Hex Shank Round Collared Accessories														
W1A1	14 ³ / ₄	6.69	15 ⁷ / ₈	403	1	25	1 ¹ / ₈	28	2500	N/A	³ / ₈	¹ / ₂	13	28
W2A1	15 ¹ / ₂	7.03	16 ³ / ₈	416	2	51	1 ¹ / ₈	28	2300	N/A	³ / ₈	¹ / ₂	13	28
W3A1	16 ⁵ / ₈	7.54	18 ¹ / ₄	464	3	76	1 ¹ / ₈	28	1725	N/A	³ / ₈	¹ / ₂	13	29
W4A1	17 ¹ / ₂	7.94	19 ¹ / ₄	489	4	102	1 ¹ / ₈	28	1480	N/A	³ / ₈	¹ / ₂	13	29
With .680" Round Nozzle — to use Round Shank Round Collared Accessories														
W1A2	14 ³ / ₄	6.69	15 ⁷ / ₈	403	1	25	1 ¹ / ₈	28	2500	N/A	³ / ₈	¹ / ₂	13	28
W2A2	15 ¹ / ₂	7.03	16 ³ / ₈	416	2	51	1 ¹ / ₈	28	2300	N/A	³ / ₈	¹ / ₂	13	28
W3A2	16 ⁵ / ₈	7.54	18 ¹ / ₄	464	3	76	1 ¹ / ₈	28	1725	N/A	³ / ₈	¹ / ₂	13	29
W4A2	17 ¹ / ₂	7.94	19 ¹ / ₄	489	4	102	1 ¹ / ₈	28	1480	N/A	³ / ₈	¹ / ₂	13	29

Performance figures are at 90 psi (620 kPa) air pressure.
For hose lengths exceeding 50', use larger dia. hose.