

# Spring Balancers

## Cable

### BIDS Series

#### Features

- Safety device prevents dropping of load due to spring breakage
- Anti-friction cable guide
- Adjustable stroke limiting device
- Upper rotary suspension
- Safety hook
- Auxiliary safety suspension




#### Manuals:



BIDS



BIDS-14

Model	SWL 		
	lbs (kg)	ft (m)	lbs (kg)
<b>BIDS SERIES</b>			
BIDS-7	8.8 – 15.4 (4.0 – 7.0)	6.5 (2.0)	5.0 (2.26)
BIDS-10	15.4 – 22.0 (7.0 – 10.0)	6.5 (2.0)	5.5 (2.49)
BIDS-14	22.0 – 30.9 (10.0 – 14.0)	6.5 (2.0)	5.5 (2.49)
BIDS-18	30.9 – 39.7 (14.0 – 18.0)	6.5 (2.0)	6.5 (2.95)
BIDS-22	39.7 – 48.5 (18.0 – 22.0)	6.5 (2.0)	6.5 (2.95)
BIDS-26	48.5 – 55.1 (22.0 – 25.0)	6.5 (2.0)	6.5 (2.95)

### BHD Series

#### Features

- Safety device prevents dropping of load due to spring breakage
- Anti-friction cable guide
- Adjustable stroke limiting device
- Upper suspension with rotary hook
- Precision guided cable winding prevents jams
- Manual locking device for instant clamping or release
- Worm screw capacity adjustment

#### Manuals:






BHD

#### Accessories:

Floor-controlled locking device: BIL-7343



BHD-25

Model	SWL 		
	lbs (kg)	ft (m)	lbs (kg)
<b>BHD SERIES</b>			
BHD-15	22.0 – 33.1 (10.0 – 15.0)	6.5 (2.0)	22.7 (10.3)
BHD-20	33.1 – 44.1 (15.0 – 20.0)	6.5 (2.0)	23.4 (10.6)
BHD-25	44.1 – 55.1 (20.0 – 25.0)	6.5 (2.0)	24.7 (11.2)
BHD-30	55.1 – 66.1 (25.0 – 30.0)	6.5 (2.0)	25.4 (11.5)
BHD-35	66.1 – 77.2 (30.0 – 35.0)	6.5 (2.0)	26.0 (11.8)
BHD-45	77.2 – 99.2 (35.0 – 45.0)	6.5 (2.0)	27.3 (12.4)
BHD-55	99.2 – 121.3 (45.0 – 55.0)	6.5 (2.0)	27.6 (12.5)
BHD-65	121.3 – 143.3 (55.0 – 65.0)	6.5 (2.0)	30.0 (13.6)