


1139-150

- Made of hard plastic, non-magnetic and non-conductive, which can effectively prevent harm to the surface of workpieces from scratching by caliper
- Resolution: .0005"/0.01mm
- Buttons: on/off, zero, inch/mm
- Battery CR2032, automatic power off
- Supplied in fitted storage case


Order No.	EDP No.	Range	Accuracy		
1139-150	280024	0-6"/0-150mm	±.004"		





1311-6

- Shockproof dial indicator
- Made of stainless steel
- Supplied in fitted storage case



Dial indicator graduation .001"

Order No.	EDP No.	Range	Accuracy	L	а	b	С	d	D
1311-4	280462	0-4"	±.0012"	6.496"	.709"	.512"	.512"	1.181"	1.260" DIA
1311-6	816028	0-6"	±.0015"	9.173"	.827"	.650"	.630"	1.575"	1.535" DIA
1311-8	816030	0-8"	±.002"	11.339"	.945"	.748"	.630"	1.969"	1.535" DIA
1311-12	816032	0-12"	±.002"	15.354"	.945"	.768"	.669"	2.520"	1.535" DIA

Dial indicator graduation 0.01mm

Order No.	EDP No.	Range	Accuracy	L	а	b	С	d	D
1311-150A	816034	0-150mm	±0.03mm	233mm	21mm	16.5mm	16mm	40mm	Ø39mm
1311-200A	816036	0-200mm	±0.03mm	288mm	24mm	19mm	16mm	50mm	Ø39mm
1311-300A	816038	0-300mm	±0.04mm	390mm	24mm	19.5mm	17mm	64mm	Ø39mm