

Aisle Marking Tape

PVC FILM TAPE

INTERTAPE POLYMER GROUP®

TECHNICAL DATA SHEET

DESCRIPTION

Vinyl safety aisle marking tapes are designed specifically with high visibility or immediate visual impact in mind. Their bright solid colors and/or striped pattern are perfect where lane marking, hazard identification, and coding is required.

Soft polyvinylchloride (PVC) base film provides for durability, puncture, tear and scratch resistance. Specially blended rubber adhesive makes these tapes adhere quickly to surfaces while conforming well even on irregular surfaces. Tapes adhere firmly while removing cleanly off most surfaces. Color throughout the film ensures consistent visibility during tape use.

PRODUCT APPLICATION

For lane marking and hazard identification.

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard test. The data should not be considered as specifications.

Backing	PVC Film
Adhesive	Synthetic Rubber
Adhesion to Steel (oz/in of width)	30 (8.3 N/25mm)
Tensile Strength (lbs/in of width)	18 lbs/in (80 N/25mm)
Elongation (% at break)	160
Total Thickness (mils)	6.0 (0.152mm)



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA
Customer Service: 800.IPG.8273 | 800.474.8273
Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 2/11

