

Raised Panel / Control Panel Materials

www.BradyID.com

Benchtop Thermal Transfer Materials



Raised Panel / Control Panel Material A cost-saving alternative to engraved legend plates

Brady's Raised Panel Material are foam-backed polyester labels with an aggressive, permanent adhesive. Thicker and more durable than a normal label, Raised Panel material is a cost-effective alternative to engraved legend plates and are ideal to identify industrial control panels, signal lights and other indoor components, as well as outdoor electrical boxes, instrument panels and more.

Using one of Brady's printers means you can create your labels in real time right in your facility - a more practical and customizable option than traditional legend plates.

Printer Compatibility

All raised panel / control panel parts shown on the following pages are compatible with the following printers unless otherwise noted.



**Bradyprinter™
PR Plus Printers**

See Page 114



Brady IP™ Printer

See Page 110

Understanding THT Label Part Numbers


Most label part numbers can be broken down in the following manner by the label's components.

Example: **THT-5-423-10**

<p>Technology: Thermal Transfer</p>	<p>Quantity: Multiply by 1,000 10 x 1,000 = 10,000</p>
<p>Die Cut: #5, 1.000" x 0.500"</p>	<p>Material Number: B-423, Gloss White Polyester</p>

3" Core Rectangular Raised Panel Material: B-593 Foam Backed Polyester Material Color: Various Finish: Gloss

Glossy, foam-backed polyester with permanent adhesive, coined a "raised panel" material. Ideal for external push-buttons, switches, and internal connection points. Can be printed with alphanumerics for use as rating and serial plates. Available in a variety of colors.



Performance Attributes:

Diagram	Catalog #	Material	Color	Label Width A Inch (mm)	Label Height B Inch (mm)	Vert. Repeat D Inch (mm)	Web Width E Inch (mm)	Labels Per Row	Labels Per Pkg	Rec. Ribbon
Fig. 62	THTEP-171-593-.5	Polyester	White	1.060 (27.0)	0.490 (12.5)	0.625 (15.9)	1.260 (32.0)	1	500	R6006
Fig. 62	THTEP171-593-.25	Polyester	White	1.060 (27.0)	0.490 (12.5)	0.625 (15.9)	1.260 (32.0)	1	250	R6006
Fig. 62	THTEP-172-593-.5	Polyester	White	1.770 (45.0)	0.590 (15.0)	0.725 (18.5)	1.970 (50.0)	1	500	R6000
Fig. 62	THTEP172-593-.25	Polyester	White	1.770 (45.0)	0.590 (15.0)	0.725 (18.5)	1.970 (50.0)	1	250	R6000
Fig. 62	THTEP-173-593-.5	Polyester	White	2.000 (50.8)	1.000 (25.4)	1.125 (28.5)	2.200 (55.9)	1	500	R6000
Fig. 62	THTEP173-593-.25	Polyester	White	2.000 (50.8)	1.000 (25.4)	1.125 (28.5)	2.200 (55.9)	1	250	R6000
Fig. 62	THTEP-175-593-.5	Polyester	White	3.000 (76.2)	0.750 (19.1)	0.875 (22.2)	3.200 (81.3)	1	500	R6002
Fig. 62	THTEP175-593-.25	Polyester	White	3.000 (76.2)	0.750 (19.1)	0.875 (22.2)	3.200 (81.3)	1	250	R6002
Fig. 62	THTEP-176-593-.5	Polyester	White	3.000 (76.2)	1.000 (25.4)	1.125 (28.5)	3.200 (81.3)	1	500	R6002
Fig. 62	THTEP176-593-.25	Polyester	White	3.000 (76.2)	1.000 (25.4)	1.125 (28.5)	3.200 (81.3)	1	250	R6002
Fig. 62	THTEP-177-593-.5	Polyester	White	3.000 (76.2)	2.500 (63.5)	2.625 (67.0)	3.200 (81.3)	1	500	R6002
Fig. 62	THTEP177-593-.25	Polyester	White	3.000 (76.2)	2.500 (63.5)	2.625 (67.0)	3.200 (81.3)	1	250	R6002
Fig. 62	THTEP-178-593-.5	Polyester	White	3.000 (76.2)	3.500 (88.9)	3.625 (92.0)	3.200 (81.3)	1	500	R6002
Fig. 62	THTEP178-593-.25	Polyester	White	3.000 (76.2)	3.500 (88.9)	3.625 (92.0)	3.200 (81.3)	1	250	R6002
Fig. 62	THTEP-174-593-.5YL	Polyester	White	4.000 (101.6)	1.000 (25.4)	1.125 (28.5)	4.200 (106.7)	1	500	R6007
Fig. 62	THTEP174-593-.25YL	Polyester	White	4.000 (101.6)	1.000 (25.4)	1.125 (28.5)	4.200 (106.7)	1	250	R6007
Fig. 62	THTEP-171-593-.5YL	Polyester	Yellow	1.060 (27.0)	0.490 (12.5)	0.625 (15.9)	1.260 (32.0)	1	500	R6006
Fig. 62	THTEP171-593-.25YL	Polyester	Yellow	1.060 (27.0)	0.490 (12.5)	0.625 (15.9)	1.260 (32.0)	1	250	R6006
Fig. 62	THTEP-172-593-.5YL	Polyester	Yellow	1.770 (45.0)	0.590 (15.0)	0.725 (18.5)	1.970 (50.0)	1	500	R6000
Fig. 62	THTEP172-593-.25YL	Polyester	Yellow	1.770 (45.0)	0.590 (15.0)	0.725 (18.5)	1.970 (50.0)	1	250	R6000
Fig. 62	THTEP-173-593-.5YL	Polyester	Yellow	2.000 (50.8)	1.000 (25.4)	1.125 (28.5)	2.200 (55.9)	1	500	R6000
Fig. 62	THTEP173-593-.25YL	Polyester	Yellow	2.000 (50.8)	1.000 (25.4)	1.125 (28.5)	2.200 (55.9)	1	250	R6000
Fig. 62	THTEP-175-593-.5YL	Polyester	Yellow	3.000 (76.2)	0.750 (19.1)	0.875 (22.2)	3.200 (81.3)	1	500	R6002
Fig. 62	THTEP175-593-.25YL	Polyester	Yellow	3.000 (76.2)	0.750 (19.1)	0.875 (22.2)	3.200 (81.3)	1	250	R6002

Brady B-593 Rectangular Raised Polyester Labels continue on following page.

View the Material Brands & Attributes Guide on page 4.
Benchtop Printer Ribbons on page 184.
Full Material Properties on page 187.