



Kit Name: **DEVCON® Plastic Steel® Putty (A)**  
Stock No.: 10110  
Manufacturer Name: ITW Polymers Adhesives, North America  
Address: 30 Endicott Street  
Danvers, MA 01923

Component list	
Component B	PLASTIC STEEL PUTTY (A) RESIN
Component A	Putty Hardener
Kit SDS Revision Date	08/10/2015

### SECTION 1 : PRODUCT AND COMPANY IDENTIFICATION

Product Name: **PLASTIC STEEL PUTTY (A) RESIN**  
Synonyms: None.  
Product Use/Restriction: Not applicable.  
Manufacturer Name: ITW  
Address: 30 Endicott Street  
Danvers, MA 01923  
General Phone Number: (978) 777-1100  
Emergency Phone Number: (800) 424-9300  
CHEMTREC: For emergencies in the US, call CHEMTREC: 800-424-9300

HMIS	
Health Hazard	2*
Fire Hazard	1
Reactivity	1
Personal Protection	X

\* Chronic Health Effects

### SECTION 2 : COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS#	Ingredient Percent
Iron	7439-89-6	53.4 - 59.1 by weight
Titanium	7440-32-6	3.4 - 3.7 by weight
Bisphenol A diglycidyl ether resin	25068-38-6	22.9 - 25.3 by weight
Organophillic clay	71011-26-2	2 - 2.3 by weight
Silicon	7440-21-3	10.9 - 12.1 by weight
Aluminum flake	7429-90-5	1.3 - 1.5 by weight

### SECTION 3 : HAZARDS IDENTIFICATION

Route of Exposure: Eyes. Skin. Inhalation. Ingestion.  
Potential Health Effects:  
Eye: Can cause moderate irritation, burning sensation, tearing, redness, and swelling. Overexposure may cause lacrimation, conjunctivitis, corneal damage and permanent injury.  
Skin: Can cause skin irritation; itching, redness, rashes, hives, burning, and swelling. Allergic reactions are possible. May cause skin sensitization, an allergic reaction, which becomes evident on reexposure to this material.  
Inhalation: Respiratory tract irritant. High concentration may cause dizziness, headache, and anesthetic effects.  
Ingestion: Causes irritation, a burning sensation of the mouth, throat and gastrointestinal tract and abdominal pain.  
Chronic Health Effects: Prolonged skin contact may lead to burning associated with severe reddening, swelling, and possible tissue destruction.  
Signs/Symptoms: Overexposure can cause headaches, dizziness, nausea, and vomiting.  
Target Organs: Eyes. Skin. Respiratory system. Digestive system.  
Aggravation of Pre-Existing Conditions: Individuals with pre-existing skin disorders, asthma, allergies or known sensitization may be more susceptible to the effects of this product.

### SECTION 4 : FIRST AID MEASURES

<b>Eye Contact:</b>	Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of the eyes by separating the eyelids with fingers. Get immediate medical attention.
<b>Skin Contact:</b>	Immediately wash skin with plenty of soap and water for 15 to 20 minutes, while removing contaminated clothing and shoes. Get medical attention if irritation develops or persists.
<b>Inhalation:</b>	If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.
<b>Ingestion:</b>	If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

## SECTION 5 : FIRE FIGHTING MEASURES

<b>Flash Point:</b>	>400°F (204.4°C)
<b>Flash Point Method:</b>	Pensky-Martens Closed Cup
<b>Auto Ignition Temperature:</b>	Not determined.
<b>Lower Flammable/Explosive Limit:</b>	Not determined.
<b>Upper Flammable/Explosive Limit:</b>	Not determined.
<b>Fire Fighting Instructions:</b>	Evacuate area of unprotected personnel. Use cold water spray to cool fire exposed containers to minimize risk of rupture. Do not enter confined fire space without full protective gear. If possible, contain fire run-off water.
<b>Extinguishing Media:</b>	Use carbon dioxide (CO2) or dry chemical when fighting fires involving this material.
<b>Unsuitable Media:</b>	Water or foam may cause frothing.
<b>Protective Equipment:</b>	As in any fire, wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH (approved or equivalent) and full protective gear.
<b>Unusual Fire Hazards:</b>	Sealed containers at elevated temperatures may rupture explosively and spread fire due to polymerization. Heating above 300 deg F in the presence of air may cause slow oxidative decomposition and above 500 deg F may cause polymerization.

## SECTION 6 : ACCIDENTAL RELEASE MEASURES

<b>Personnel Precautions:</b>	Evacuate area and keep unnecessary and unprotected personnel from entering the spill area.
<b>Environmental Precautions:</b>	Avoid runoff into storm sewers, ditches, and waterways.
<b>Spill Cleanup Measures:</b>	Absorb spill with inert material (e.g., dry sand or earth), then place in a chemical waste container. Provide ventilation. Clean up spills immediately observing precautions in the protective equipment section. After removal, flush spill area with soap and water to remove trace residue. Avoid personal contact and breathing vapors or mists. Ventilate area. Use proper personal protective equipment as listed in Section 8.
<b>Other Precautions:</b>	Pump or shovel to storage/salvage vessels.

## SECTION 7 : HANDLING and STORAGE

<b>Handling:</b>	Use with adequate ventilation. Avoid breathing vapor, aerosol or mist.
<b>Storage:</b>	Store in a cool, dry, well ventilated area away from sources of heat and incompatible materials. Keep container tightly closed when not in use.
<b>Special Handling Procedures:</b>	Provide appropriate ventilation/respiratory protection against decomposition products (see Section 10) during welding/flame cutting operations and to protect against dust during sanding/grinding of cured product.
<b>Hygiene Practices:</b>	Wash thoroughly after handling.

## SECTION 8 : EXPOSURE CONTROLS, PERSONAL PROTECTION - EXPOSURE GUIDELINES

<b>Engineering Controls:</b>	Use appropriate engineering control such as process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance of the personal protective equipment.
<b>Eye/Face Protection:</b>	Wear appropriate protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye and face protection regulation, or the European standard EN 166.
<b>Skin Protection Description:</b>	Wear appropriate protective gloves and other protective apparel to prevent skin contact. Consult manufacturer's data for permeability data.
<b>Respiratory Protection:</b>	A NIOSH approved air-purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.
<b>Other Protective:</b>	Facilities storing or utilizing this material should be equipped with an eyewash and a deluge shower safety station.

**Silicon :**

Guideline OSHA: PEL-TWA: 15 mg/m<sup>3</sup> Total particulate/dust (T)  
PEL-TWA: 5 mg/m<sup>3</sup> Respirable fraction (R)

**Aluminum flake :**

Guideline ACGIH: TLV-TWA: 1 mg/m<sup>3</sup> Respirable fraction (R)  
TLV-TWA: 1 mg/m<sup>3</sup> Respirable fraction (R)  
TLV-TWA: 1 mg/m<sup>3</sup> (R)

Guideline OSHA: PEL-TWA: 15 mg/m<sup>3</sup> Total particulate/dust (T)  
PEL-TWA: 5 mg/m<sup>3</sup> Respirable fraction (R)

Notes : Only established PEL and TLV values for the ingredients are listed.

**SECTION 9 : PHYSICAL and CHEMICAL PROPERTIES**

Physical State Appearance:	Paste.
Color:	Dark Gray
Odor:	Slight. odor.
Boiling Point:	>500°F (260°C)
Melting Point:	Not determined.
Specific Gravity:	2.8
Solubility:	negligible.
Vapor Density:	>1 (air = 1)
Vapor Pressure:	0.03 mmHg @171°F
Percent Volatile:	0
Evaporation Rate:	<<1 (butyl acetate = 1)
pH:	Neutral.
Molecular Formula:	Mixture
Molecular Weight:	Mixture
Flash Point:	>400°F (204.4°C)
Flash Point Method:	Pensky-Martens Closed Cup
Auto Ignition Temperature:	Not determined.
VOC Content:	0 g/L
Percent Solids by Weight	100

**SECTION 10 : STABILITY and REACTIVITY**

Chemical Stability:	Stable under normal temperatures and pressures.
Hazardous Polymerization:	Not reported.
Conditions to Avoid:	Extreme heat, sparks, and open flame. Incompatible materials, oxidizers and oxidizing conditions. Heating resin above 300 F in the presence of air may cause slow oxidative decomposition.
Incompatible Materials:	Strong Lewis or mineral acids, strong oxidizing agents, strong mineral and organic bases (especially primary and secondary aliphatic amines).

**SECTION 11 : TOXICOLOGICAL INFORMATION****Iron :**

Ingestion: Oral - Rat LD50 - Lethal dose, 50 percent kill: 30 gm/kg [Nutritional and Gross Metabolic - Weight loss or decreased weight gain]  
Oral - Rat LD50 - Lethal dose, 50 percent kill: 750 mg/kg [Blood - Changes in serum composition (e.g., TP, bilirubin, cholesterol) Biochemical - Enzyme inhibition, induction, or change in blood or tissue levels - Transaminases] (RTECS)

**Bisphenol A diglycidyl ether resin :**

Eye: Administration into the eye - Rabbit Standard Draize test: 100 mg [Mild]  
Administration into the eye - Rabbit Standard Draize test: 20 mg/24H [Moderate]  
Administration into the eye - Rabbit Standard Draize test: 5 mg/24H [Severe] (RTECS)

Skin: Administration onto the skin - Rabbit LD50 - Lethal dose, 50 percent kill: >20 mL/kg [Details of toxic effects not reported other than lethal dose value]  
Administration onto the skin - Rat LD50 - Lethal dose, 50 percent kill: >1200 mg/kg [Details of toxic effects not reported other than lethal dose value] (RTECS)

Ingestion: Oral - Rat LD50 - Lethal dose, 50 percent kill: 10700 uL/kg [Details of toxic effects not reported other than lethal dose value]  
Oral - Rat LD50 - Lethal dose, 50 percent kill: 13600 mg/kg [Behavioral - Somnolence (general depressed activity) Lungs, Thorax, or Respiration - Dyspnea Nutritional and Gross Metabolic - Weight loss or decreased weight gain]  
Oral - Rat LD50 - Lethal dose, 50 percent kill: 13.6 gm/kg [Details of toxic effects not reported other than lethal dose value]  
Oral - Rat LD50 - Lethal dose, 50 percent kill: 11.4 gm/kg [Details of toxic effects not reported other than lethal dose value]  
Oral - Rat LD50 - Lethal dose, 50 percent kill: 30 gm/kg [Behavioral - Somnolence (general depressed activity) Lungs, Thorax, or Respiration - Dyspnea Nutritional and Gross Metabolic - Weight loss or decreased weight gain]  
Oral - Rat LD50 - Lethal dose, 50 percent kill: 30 gm/kg [Details of toxic effects not reported other than lethal dose value]

Oral - Rat LD50 - Lethal dose, 50 percent kill: >1 gm/kg [Details of toxic effects not reported other than lethal dose value]  
Oral - Rat LD50 - Lethal dose, 50 percent kill: 11400 mg/kg [Behavioral - Somnolence (general depressed activity) Lungs, Thorax, or Respiration - Dyspnea Nutritional and Gross Metabolic (RTECS)]

**Silicon :**

Eye: Administration into the eye - Rabbit Standard Draize test: 3 mg [Mild] (RTECS)

Ingestion: Oral - Rat LD50 - Lethal dose, 50 percent kill: 3160 mg/kg [Details of toxic effects not reported other than lethal dose value] (RTECS)

**SECTION 12 : ECOLOGICAL INFORMATION**

Ecotoxicity: No ecotoxicity data was found for the product.

Environmental Fate: No environmental information found for this product.

**SECTION 13 : DISPOSAL CONSIDERATIONS**

Waste Disposal: Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classifications of hazardous waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and/or state and local guidelines.

RCRA Number: Not determined.

**SECTION 14 : TRANSPORT INFORMATION**

DOT Shipping Name: Non regulated.

DOT UN Number: Not applicable.

DOT Hazard Class: Not applicable.

DOT Packing Group: Not applicable.

**SECTION 15 : REGULATORY INFORMATION**

**Iron :**

TSCA Inventory Status: Listed

Canada DSL: Listed

**Titanium :**

TSCA Inventory Status: Listed

Canada DSL: Listed

**Bisphenol A diglycidyl ether resin :**

TSCA Inventory Status: Listed

Canada DSL: Listed

**Organophillic clay :**

TSCA Inventory Status: Listed

Canada DSL: Listed

**Silicon :**

TSCA Inventory Status: Listed

Canada DSL: Listed

**Aluminum flake :**

TSCA Inventory Status: Listed

Section 313: EPCRA - 40 CFR Part 372 - (SARA Title III) Section 313 Listed Chemical.

Canada DSL: Listed

Canadian Regulations: WHMIS Hazard Class(es): D2B  
All components of this product are on the Canadian Domestic Substances List.

WHMIS Pictograms:



**SECTION 16 : ADDITIONAL INFORMATION**

**HMIS Ratings:**

HMIS Health Hazard: 2\*

HMIS Fire Hazard: 1

HMIS Reactivity: 1  
 HMIS Personal Protection: X  
 SDS Revision Date: May 19, 2015  
 MSDS Revision Notes: GHS Update  
 SDS Format: According to ANSI Z400.1-2004  
 MSDS Author: Actio Corporation

**Disclaimer:** The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. ITW Polymers Adhesives, NA, MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the ITW Polymers Adhesives, NA product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a ITW Polymers Adhesives, NA product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the ITW Polymers Adhesives, NA product to determine whether it is fit for a particular purpose and suitable for user's method of use or application. ITW Polymers Adhesives, NA provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, ITW Polymers Adhesives, NA makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from ITW Polymers Adhesives, NA

Copyright© 1996-2015 Actio Corporation. All Rights Reserved.

## SECTION 1 : PRODUCT AND COMPANY IDENTIFICATION

**Product Name:** Putty Hardener  
**Manufacturer Name:** ITW  
**Address:** 30 Endicott Street  
 Danvers, MA 01923  
**General Phone Number:** (978) 777-1100  
**Emergency Phone Number:** (800) 424-9300  
**CHEMTREC:** For emergencies in the US, call CHEMTREC: 800-424-9300

HMIS	
Health Hazard	2*
Fire Hazard	1
Reactivity	0
Personal Protection	X

\* Chronic Health Effects

## SECTION 2 : COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS#	Ingredient Percent
Titanium dioxide	13463-67-7	34.8 - 38.5 by weight
Aliphatic Amines	No Data	23 - 25.4 by weight
Amorphous silica	7631-86-9	2.3 - 2.5 by weight
Benzyl alcohol	100-51-6	11.5 - 12.7 by weight
Triethylenetetramine	112-24-3	11.5 - 12.7 by weight
Synthetic amorphous silica	112945-52-5	10 - 11 by weight
Aluminum trihydrate	21645-51-2	1.7 - 1.9 by weight

## SECTION 3 : HAZARDS IDENTIFICATION

**Route of Exposure:** Eyes. Skin. Inhalation. Ingestion.  
**Potential Health Effects:**  
**Eye:** Can cause moderate irritation, burning sensation, tearing, redness, and swelling. Overexposure may cause lacrimation, conjunctivitis, corneal damage and permanent injury.  
**Skin:** Can cause skin irritation; itching, redness, rashes, hives, burning, and swelling. Allergic reactions are possible. May cause skin sensitization, an allergic reaction, which becomes evident on reexposure to this material.  
**Inhalation:** Respiratory tract irritant. High concentration may cause dizziness, headache, and anesthetic effects.  
**Ingestion:** Causes irritation, a burning sensation of the mouth, throat and gastrointestinal tract and abdominal pain.  
**Chronic Health Effects:** Prolonged skin contact causes burns. Repeated or prolonged inhalation may cause toxic effects.  
**Signs/Symptoms:** Overexposure can cause headaches, dizziness, nausea, and vomiting.  
**Target Organs:** Eyes. Skin. Respiratory system. Digestive system. Central nervous system.  
**Aggravation of Pre-Existing:** Individuals with pre-existing skin disorders, asthma, allergies or known sensitization may be more

**SECTION 4 : FIRST AID MEASURES**

**Eye Contact:** Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of the eyes by separating the eyelids with fingers. Get immediate medical attention.

**Skin Contact:** Immediately wash skin with plenty of soap and water for 15 to 20 minutes, while removing contaminated clothing and shoes. Get medical attention if irritation develops or persists.

**Inhalation:** If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.

**Ingestion:** If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

**SECTION 5 : FIRE FIGHTING MEASURES**

**Flash Point:** >200°F (93.3°C)

**Flash Point Method:** Tag closed cup. (TCC)

**Auto Ignition Temperature:** Not determined.

**Lower Flammable/Explosive Limit:** Not determined.

**Upper Flammable/Explosive Limit:** Not determined.

**Fire Fighting Instructions:** Evacuate area of unprotected personnel. Use cold water spray to cool fire exposed containers to minimize risk of rupture. Do not enter confined fire space without full protective gear. If possible, contain fire run-off water.

**Extinguishing Media:** Use carbon dioxide (CO2) or dry chemical when fighting fires involving this material.

**Unsuitable Media:** Water or foam may cause frothing.

**Protective Equipment:** As in any fire, wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH (approved or equivalent) and full protective gear.

**SECTION 6 : ACCIDENTAL RELEASE MEASURES**

**Personnel Precautions:** Evacuate area and keep unnecessary and unprotected personnel from entering the spill area.

**Environmental Precautions:** Avoid runoff into storm sewers, ditches, and waterways.

**Spill Cleanup Measures:** Absorb spill with inert material (e.g., dry sand or earth), then place in a chemical waste container. Provide ventilation. Clean up spills immediately observing precautions in the protective equipment section. After removal, flush spill area with soap and water to remove trace residue.

**Other Precautions:** Pump or shovel to storage/salvage vessels.

**SECTION 7 : HANDLING and STORAGE**

**Handling:** Use with adequate ventilation. Avoid breathing vapor, aerosol or mist. Avoid contact with eyes and skin. Do not reuse containers without proper cleaning or reconditioning.

**Storage:** Store in a cool, dry, well ventilated area away from sources of heat and incompatible materials. Keep container tightly closed when not in use. Do not store in reactive metal containers. Keep away from acids, oxidizers.

**Special Handling Procedures:** Provide appropriate ventilation/respiratory protection against decomposition products (see Section 10) during welding/flame cutting operations and to protect against dust during sanding/grinding of cured product.

**Hygiene Practices:** Wash thoroughly after handling.

**SECTION 8 : EXPOSURE CONTROLS, PERSONAL PROTECTION - EXPOSURE GUIDELINES**

**Engineering Controls:** Use appropriate engineering control such as process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance of the personal protective equipment.

**Eye/Face Protection:** Wear appropriate protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye and face protection regulation, or the European standard EN 166.

**Skin Protection Description:** Chemical-resistant gloves and chemical goggles, face-shield and synthetic apron or coveralls should be used to prevent contact with eyes, skin or clothing.

**Respiratory Protection:** A NIOSH approved air-purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

**Other Protective:** Facilities storing or utilizing this material should be equipped with an eyewash and a deluge shower safety station.

## EXPOSURE GUIDELINES

### Titanium dioxide :

Guideline ACGIH: TLV-TWA: 10 mg/m<sup>3</sup>

Notes : Only established PEL and TLV values for the ingredients are listed.

## SECTION 9 : PHYSICAL and CHEMICAL PROPERTIES

Physical State Appearance:	Paste.
Color:	White
Odor:	Mild ammonia like
Boiling Point:	>450°F (232.2°C)
Melting Point:	Not determined.
Specific Gravity:	0.98
Solubility:	slightly soluble.
Vapor Density:	>1
Vapor Pressure:	<10 mmHg @70°F
Percent Volatile:	0
Evaporation Rate:	<1
pH:	8
Molecular Formula:	Mixture
Molecular Weight:	Mixture
Flash Point:	>200°F (93.3°C)
Flash Point Method:	Tag closed cup. (TCC)
Auto Ignition Temperature:	Not determined.
VOC Content:	0
Percent Solids by Weight	100

## SECTION 10 : STABILITY and REACTIVITY

Chemical Stability:	Stable under normal temperatures and pressures.
Hazardous Polymerization:	Not reported.
Conditions to Avoid:	Extreme heat, sparks, and open flame. Incompatible materials, oxidizers and oxidizing conditions. Product may slowly corrode copper, aluminum, zinc and galvanized surfaces.
Incompatible Materials:	Oxidizers, acids, and chlorinated organic compounds. Reactive metals (e.g. sodium, calcium, zinc). Sodium/calcium hypochlorite. Nitrous acid/ oxide, nitrites. Peroxides. Materials reactive with hydroxyl compounds.

## SECTION 11 : TOXICOLOGICAL INFORMATION

### Titanium dioxide :

**Chronic Effects:** Normal application procedures for this product pose minimal hazard as to the release of respirable titanium dioxide dust, but grinding or sanding dried films of this product may yield some respirable titanium dioxide. Although IARC has classified titanium dioxide as possible carcinogenic to human (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products which titanium dioxide is bound to other materials". OSHA does not regulate titanium dioxide as a carcinogen. However, under 29CFR 1910.1200 the SDS must convey the fact that titanium dioxide is a potential carcinogen to rats.

**Carcinogenicity:** Animal evidence shows that high concentrations of pigment-grade (powdered) and ultrafine titanium dioxide dust caused respiratory tract cancer in rats exposed by inhalation.

### Amorphous silica :

**Eye:** Administration into the eye - Rabbit Standard Draize test: 25 mg/24H [Mild] (RTECS)

### Benzyl alcohol :

**Skin:** Administration onto the skin - Rabbit LD50 - Lethal dose, 50 percent kill: 2000 mg/kg [Details of toxic effects not reported other than lethal dose value] (RTECS)

**Inhalation:** Inhalation - Rat LC50 - Lethal concentration, 50 percent kill: >500 mg/m<sup>3</sup> [Behavioral - Somnolence (general depressed activity) Behavioral - Ataxia Lungs, Thorax, or Respiration - Respiratory depression] (RTECS)

**Ingestion:** Oral - Rat LD50 - Lethal dose, 50 percent kill: 1230 mg/kg [Behavioral - Somnolence (general depressed activity) Behavioral - Excitement Behavioral - Coma]  
Oral - Rat LD50 - Lethal dose, 50 percent kill: 1660 mg/kg [Behavioral - Somnolence (general depressed activity) Behavioral - Ataxia Lungs, Thorax, or Respiration - Respiratory depression]  
Oral - Rat LD50 - Lethal dose, 50 percent kill: 1.5 mL/kg [Details of toxic effects not reported other than lethal dose value] (RTECS)

### Triethylenetetramine :

**Eye:** Administration into the eye - Rabbit Standard Draize test: 49 mg [Severe]  
Administration into the eye - Rabbit Standard Draize test: 20 mg/24H [Moderate] (RTECS)

**Skin:** Administration onto the skin - Rabbit LD50 - Lethal dose, 50 percent kill: 805 mg/kg [Details of toxic effects not reported other than lethal dose value] (RTECS)

**Ingestion:** Oral - Rat LD50 - Lethal dose, 50 percent kill: 2500 mg/kg [Details of toxic effects not reported other than lethal dose value] (RTECS)

**Synthetic amorphous silica :**

**Ingestion:** Oral - Rat LD50 - Lethal dose, 50 percent kill: 3160 mg/kg [Details of toxic effects not reported other than lethal dose value] (RTECS)

**SECTION 12 : ECOLOGICAL INFORMATION**

**Ecotoxicity:** No ecotoxicity data was found for the product.

**Environmental Fate:** No environmental information found for this product.

**SECTION 13 : DISPOSAL CONSIDERATIONS**

**Waste Disposal:** Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classifications of hazardous waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and/or state and local guidelines.

**SECTION 14 : TRANSPORT INFORMATION**

**DOT Shipping Name:** Non regulated.

**DOT UN Number:** Non regulated.

**SECTION 15 : REGULATORY INFORMATION**

**Titanium dioxide :**

**TSCA Inventory Status:** Listed

**Canada DSL:** Listed

**Amorphous silica :**

**TSCA Inventory Status:** Listed

**Canada DSL:** Listed

**Benzyl alcohol :**

**TSCA Inventory Status:** Listed

**Canada DSL:** Listed

**Triethylenetetramine :**

**TSCA Inventory Status:** Listed

**Canada DSL:** Listed

**Synthetic amorphous silica :**

**Canada DSL:** Listed

**Aluminum trihydrate :**

**TSCA Inventory Status:** Listed

**Canada DSL:** Listed

**Canadian Regulations:** WHMIS Hazard Class(es): D2B

**WHMIS Pictograms:**



**SECTION 16 : ADDITIONAL INFORMATION**

**HMIS Ratings:**

**HMIS Health Hazard:** 2\*

**HMIS Fire Hazard:** 1

**HMIS Reactivity:** 0

**HMIS Personal Protection:** X

**SDS Creation Date:** June 06, 2014

**SDS Revision Date:** July 25, 2015

**MSDS Revision Notes:** GHS Update

**SDS Format:** According to ANSI Z400.1-2004

**MSDS Author:** Actio Corporation



**Disclaimer:**

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. ITW Polymers Adhesives, NA, MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the ITW Polymers Adhesives, NA product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a ITW Polymers Adhesives, NA product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the ITW Polymers Adhesives, NA product to determine whether it is fit for a particular purpose and suitable for user's method of use or application. ITW Polymers Adhesives, NA provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, ITW Polymers Adhesives, NA makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from ITW Polymers Adhesives, NA

Copyright© 1996-2015 Actio Corporation. All Rights Reserved.