

ITW Permatex
 10 Columbus Blvd.
 Hartford, CT 06106 USA
 Telephone: 1-87-Permatex
 (877) 376-2839
 Emergency: 800-255-3924 (ChemTel)
 International Emergency: +01-813-248-0585

Material Safety Data Sheet

1. PRODUCT IDENTIFICATION

Product Name: 6MA POWERBEAD SENSOR SAFE BLUE RTV SILICONE 7.25 OZ AE
Item No: 81860
Product Type: Elastomeric rubber (pressurized)

2. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Weight%	ACGIH; TLV-TWA	OSHA PEL
POLY (DIMETHYLSILOXANE), HYDROXY TERMINATED 70131-67-8	30-50	Not listed	Not listed
LIMESTONE 1317-65-3	20-40	Not listed	15 mg/m ³
CALCIUM CARBONATE 471-34-1	15-40	10 mg/m ³	Not listed
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT 64742-47-8	<5	Not listed	Not listed
VINYL OXIMINOSILANE 2224-33-1	<5	Not listed	Not listed
STEARIC ACID 57-11-4	<2	Not listed	Not listed
2-BUTANONE OXIME 96-29-7	0.5-2.0	Not listed	Not listed
NITROGEN 7727-37-9	0.5-2.0	Not listed	Not listed

3. HAZARDS IDENTIFICATION

Toxicity: May cause eye and skin irritation. When this product is exposed to moisture, butanone oxime may be formed. May be harmful if swallowed. May irritate lips, gums, tongue, mouth, nose and throat.
Primary Routes of Entry: Eye and skin contact, ingestion, inhalation
Signs and Symptoms of Exposure: Butanone oxime produced during curing is toxic and irritates eyes, nose and throat. Overexposure to the silane may cause coma and respiratory failure.
Aggravated Medical Condition: Preexisting eye, skin and respiratory disorders may be aggravated by overexposure to this product.

4. FIRST AID MEASURES

Ingestion: Rinse mouth. If swallowed, DO NOT induce vomiting. Keep individual calm. Obtain medical attention.
Inhalation: Move to fresh air in case of accidental inhalation of vapours. Obtain medical attention.
Skin Contact: Wipe off material with paper towel or cloth. Wash off with soap and water. If skin irritation persists, call a physician.
Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

5. FIRE FIGHTING MEASURES

Flash Point °F(C°): >200°F TCC
Recommended Extinguishing Media: Carbon Dioxide, Dry Chemicals, Foam.
Special Fire-Fighting Procedures: ***Warning: This container is pressurized with nitrogen. Do not remove rubber plug. Keep containers cool. Use equipment or shielding required to protect against bursting or venting of containers.
Hazardous Products of Combustion: Oxides of nitrogen, Methyl ethyl ketone, possibly methyl ethyl ketoxime, Silica fume, Oxides of carbon, Formaldehyde
Unusual Fire/Explosion Hazards: Contents under pressure. Heated cans may burst.
Lower Explosive Limit: Not determined

5. FIRE FIGHTING MEASURES

Upper Explosive Limit: Not determined

6. ACCIDENTAL RELEASE MEASURES

Spill Procedures: Wipe or scrape up spill material. Maintain good ventilation for large spills. Place scrap material in a well-ventilated area and allow to cure to rubber. Clean up spills thoroughly as residue is slippery.

7. HANDLING AND STORAGE

Storage: Store away from heat, sparks or open flame. Do not store at temperatures above 100°F (38°C). Exposure to high temperatures may cause container to burst.

Handling: Avoid contact with skin and eyes. Do not wear contact lenses. Do not inhale vapors. Do not take internally. Wash hands before eating and smoking.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes: Safety glasses.

Skin: Neoprene or nitrile gloves recommended.

Ventilation: General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product.

Respiratory Protection: An approved organic vapor respirator should be worn when exposures are expected to exceed the applicable limits.

Comments: When heated to temperatures above 300 degrees F. in the presence of air, this product can form formaldehyde vapors. Formaldehyde is a potential cancer hazard and a known skin and respiratory sensitizer. Safe handling conditions may be maintained by keeping vapor concentrations below the OSHA permissible limit for formaldehyde

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Blue paste

Odor: Mild

Boiling Point: Not applicable, polymeric material

pH: Does not apply

Solubility in Water: Polymerized

Specific Gravity: 1.43

VOC(Wt.%): <4%

Vapor Pressure: <5 mm Hg @ 80°F

Vapor Density (Air=1): 3.0

Evaporation Rate: Not Determined

10. STABILITY AND REACTIVITY

Chemical Stability: Stable at normal conditions

Hazardous Polymerization: Will not occur

Incompatibilities: Polymerized by contact with moisture., Strong oxidizers, Acids, Iron

Conditions to Avoid: Keep away from heat, sparks and open flame. Exposure to moisture.

Hazardous Products of Combustion: Oxides of nitrogen, Methyl ethyl ketone, possibly methyl ethyl ketoxime, Silica fume, Oxides of carbon, Formaldehyde

11. TOXICOLOGICAL INFORMATION

See Section 3

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended Method of Disposal: Disposal should be made in accordance with federal, state and local regulations.

US EPA Waste Number: NH - Not a RCRA Hazardous Waste Material

14. TRANSPORTATION INFORMATION

DOT (49CFR 172)
U.S. Department of Transportation - DOT - 49 CFR (Ground)

DOT Shipping Name: Aerosols, Limited Quantity

Hazard Class: Class 2.2

Product Name: 6MA POWERBEAD SENSOR SAFE BLUE
RTV SILICONE 7.25 OZ AE

Item No. 81860

14. TRANSPORTATION INFORMATION

UN/ID Number: UN 1950

IATA (Air)

Proper Shipping Name: Consumer Commodity (Not more than 1 liter)

Class or Division: Class 9

UN/ID Number: ID 8000

IMDG (Vessel)

Proper Shipping Name: Aerosols, Limited Quantity

Hazard Class: Class 2.2

UN Number: UN 1950

Marine Pollutant: None

15. REGULATORY INFORMATION

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical.

NONE

California Proposition 65: No California Prop 65 chemicals are known to be present at or above the No Significant Risk Level

TSCA Inventory Status: All components of this product are listed (or exempt) on the EPA TSCA inventory.

16. OTHER INFORMATION

Estimated NFPA Rating: HEALTH 1, FLAMMABILITY 1, REACTIVITY 0.

Estimated HMIS Classification: HEALTH 1, FLAMMABILITY 1, PHYSICAL HAZARD 0

(NFPA is a registered trademark of the National Fire Protection Association)

HMIS is a registered trademark of the National Paint and Coatings Association

Prepared By: Denise Boyd, Manager-Environmental, Health & Safety
Company: ITW Permatex 10 Columbus Blvd. Hartford, CT USA 06106
Telephone No.: 1-87-Permatex (877) 376-2839

Revision Date: February 02, 2012
Revision Number: 2