

All Parts Packaged in One UPS Shippable Carton

FEATURES

- 2 Mounting Options
- Guard Meets OSHA Standards
- 115V, 60 Hz, 1/3 HP, 1 Phase, 3 Speed, Totally Enclosed Ball Bearing Motors
- Galvanized Steel Propeller
- 15 Foot Three Conductor Cord and Plug
- 3 Year Warranty
- UL/ CUL Listed
- All Stocked

OSCILLATING PERFORMANCE 115V

Prop Dia.	CFM			RPM			Motor Number	F. L. Amps
	High	Med	Low	High	Med	Low		
24"	5548	4699	4062	1110	958	856	0-3B	3.2
30"	7794	5943	5143	1091	871	759	0-3B	3.2

Performance Ratings are conducted in accordance with AMCA Standard 230-99.

115V MODELS : OSCILLATING - UNIT PACKS

Prop Dia.	Fan Style	EDP Number	Catalog Number	HP	Ship Wt.	List Price
24"	Adjustable Floor	71567	I-24-OAP (3-SP)	1/3	86	\$608
	Wall Mount*	71565	I-24-OIW (3-SP)	1/3	57	\$553
30"	Adjustable Floor	71568	I-30-OAP (3-SP)	1/3	95	\$638
	Wall Mount*	71566	I-30-OIW (3-SP)	1/3	61	\$595

Wall Mount is supplied with the required Safety Cable Kit. *Used with EDP# 37772 Mounting Bracket. Unit Pack - Motor, Specified Style Mounting, Propeller & Guard shipped in a single carton.

MOTOR TILT ADJUSTMENTS

TYPE	TILT (IN DEGREES)	
	OSCILLATING	
	UP	DOWN
FLOOR	20°	20°
WALL	0°	20°

0° = Horizontal Plane



Adjustable Floor



Oscillating Wall Mount

A safety cable kit is included in all overhead mounted air circulators to prevent the fan from falling if accidentally struck or mounting fails. Single safety cable kits consist of 12 feet of 1/16" diameter cable, 2 cable clamps and instructions.



OSCILLATING ASSEMBLED FAN HEADS

OSCILLATING ASSEMBLED FAN HEADS †

Prop Dia.	Fan Style	EDP Number	Catalog Number	HP	Ship Wt.	List Price
24"	Head Assembly	71610	24-IAC-MGBO (3-SP)	1/3	46	\$497
30"	Head Assembly	38422	30-IAC-MGBO (3-SP)	1/3	56	\$530

†Motor, Guard, and Propeller Pre-Assembled
Note: Oscillating fan heads are NOT to be used in upside down position.
30" Head Assembly is UPS OverSize 2.

See page 9 for Mounting Components.



Industrial Head Assembly

