

Wrenches

SHORT BOX WRENCHES - 12 POINT - SATIN FINISH

- Satin finish provides corrosion resistance and a slip resistant grip.
- 12 point box end allows for fine indexing, helping to improve speed and access. Fits 4, 6 and 12 point fasteners.
- Box ends incorporate the TorquePlus[™] system.
- Proto[®] TorquePlus[™] wrenches are ideal for use on stubborn or damaged fasteners, and also on fasteners made from soft materials.
- The TorquePlus™ design is a high performance drive configuration which allows for quick and easy wrench engagement to the fastener flats, not the corners.
- The TorquePlus™ configuration employs a radiuscorner design, shifting contact area and stress away from the fastener corners and distributing contact stresses over a large area of the box end, minimizing slippage.
- The TorquePlus[™] internal design minimizes fastener rounding, helps to extend fastener life, and allows the user to more easily turn worn, rounded, or rusted fasteners.





Product	O in.						Weight		
ID No.	<u> </u>	С	D	C1	D1	L	lbs.	ASME Spec.	AS Spec.
J1120	5/16" x 3/8"	33/64"	17/64"	37/64"	19/64"	4-1/4"	0.07 lbs.	ASME B107.100	AS954E S3.8.1
J1122	3/8" x 7/16"	37/64"	19/64"	43/64"	21/64"	4-5/8"	0.09 lbs.	ASME B107.100	AS954E S3.8.1
J1125	7/16" x 1/2"	43/64"	21/64"	49/64"	11/32"	5"	0.10 lbs.	ASME B107.100	AS954E S3.8.1
J1126	1/2" x 9/16"	43/64"	11/32"	55/64"	23/64"	5-3/8"	0.12 lbs.	ASME B107.100	AS954E S3.8.1
J1131	5/8" x 3/4"	1-27/32"	13/32"	1-3/32"	15/32"	6-1/8"	0.25 lbs.	ASME B107.100	AS954E S3.8.1



