FACOM® INSULATED RATCHETS

- Sockets and accessories secured by spring -ball.
- 2 Color warning handle insulation color changes from orange to yellow if Insulation integrity compromised.
- For manual use.
- Insulated to 1000V AC or 1500 DC.

.	n :	Overall		
Product #	Drive Size (in)	Length (in)	Weight (lbs)	
FT-R.151AVSE	1/4	4-7/8	0.28	
FT-J.151AVSE	3/8	7	0.53	
FT-S.151AVSE	1/2	10-3/8	1.24	





SPUD HANDLE RATCHET

- > Tapered handle for aligning bolt holes.
- Spring loaded pellet in male drive plug.
- Black oxide finish.



				Uverali	
Product #	Drive Size (in)	Finish	Style	Length (in)	Weight (lbs)
J5449-14BL	1/2	Black Oxide	Pear Head	14	2.03

ASME B107.500

SCAFFOLDING RATCHET

- > The scaffold ratchet is designed for working with scaffolding and other construction applications.
- Socket retained with through hole and pin for safety.
- > Hammer tip reduces vibration and protects fasteners against distortion.
- ▶ Hole in ratchet handle to be used with tether strap.



Product #	Drive Size (in)	Finish	Style	Length (in)	Weight (lbs)
J5449SC	1/2	Full Polish	Scaffolding	10	2.01

SPINNER RATCHET

- Made from alloy steel.
- Heat-treated for strength and durability.
- > Fits on the drive end of the ratchet for quickly running down the fastener before final tightening with the ratchet.

Product #	Drive Size (in)	Finish	Overall Length (in)	Weight (lbs)
J5251	3/8	Full Polish	1-1/2	0.56



