

## CLASSIC PEAR HEAD RATCHETS (CONT'D)

### MALE/FEMALE

- ▶ An extra safety factor is provided through the use of a spring-loaded pellet in each male drive plug that snaps into a hole in the drive end of the socket and acts as a retaining pin. The socket stays locked on until the pellet is depressed and the socket is removed.



Product #	Drive Size (in)	Finish	Style	Overall Length (in)	Weight (lbs)	Repair Kit Part #
<b>J5849</b>	1	Satin	Pear Head	26	13.02	J5849RK

🇺🇸 ASME B107.500

### STUBBY



Product #	Drive Size (in)	Finish	Style	Overall Length (in)	Weight (lbs)	Repair Kit Part #
<b>J5248S</b>	3/8	Full Polish	Pear Head	5	0.28	J6064RK

🇺🇸 ASME B107.500

### FEMALE DRIVE



Product #	Drive Size (in)	Finish	Style	Overall Length (in)	Weight (lbs)	Repair Kit Part #
<b>J5249FW</b>	3/8	Full Polish	Pear Head	7	0.56	J5249WRK
<b>J5450FW</b>	1/2	Full Polish	Pear Head	16	1.82	J5450FWRK
<b>J5649FW</b>	3/4	Satin	Pear Head	20	5.62	J5649FWRK

🇺🇸 ASME B107.500

## PEAR HEAD RATCHET REPAIR KITS

Product #	Drive Size (in)	Ratchet	Weight (lbs)
<b>J4749XLRK</b>	1/4	J4749XL	0.04
<b>J4749XLHSRK</b>	1/4	J4749XLHS	0.06
<b>J4749RK</b>	1/4	J4749	0.04
<b>J4749HSRK</b>	1/4	J4749HS	0.04
<b>J4749XLQRRK</b>	1/4	J4749XLQR	0.13
<b>J5249XLRK</b>	3/8	J5249XL	0.13
<b>J5249FWRK</b>	3/8	J5249FW	0.13
<b>J5249HSRK</b>	3/8	J5249HS	0.15
<b>J5249XLHSRK</b>	3/8	J5249XLHS	0.15
<b>J5249XLQRRK</b>	3/8	J5249XLQR	0.15
<b>J5449RK</b>	1/2	J5449	0.38
<b>J5449UTRK</b>	1/2	J5449UT	0.38
<b>J5449XLRK</b>	1/2	J5449XL	0.23
<b>J5449-14RK</b>	1/2	J5449-14BL	0.37
<b>J5449XLQRRK</b>	1/2	J5449XLQR	0.25
<b>J5450FWRK</b>	1/2	J5450FW	0.26
<b>J5649FWRK</b>	3/4	J5649FW	1.00
<b>J5649RK</b>	3/4	J5649	1.00

🇺🇸

