

# Wrenches



## FACOM® VSE ADJUSTABLE WRENCHES

- Finger stops help keep hands safe.
- 2 color warning handle insulation - color changes from orange to yellow if insulation integrity is compromised.
- Graduated head, 15° angle.
- Burnished finish.
- Thumbwheel rotates counterclockwise.



Product ID No.	Size	Length	Weight lbs.
<b>FM-113.8TAVSE</b>	8"	8-15/32"	0.83 lbs.
<b>FA-113.10TAVSE</b>	10"	10-7/16"	1.37 lbs.
<b>FA-113.12TAVSE</b>	12"	12-19/32"	1.93 lbs.
<b>FA-113.15TAVSE</b>	15"	15-9/16"	3.12 lbs.

## PROTOBLACK™ ADJUSTABLE WRENCHES - CLIK-STOP®

- Non-reflective ProtoBlack™ finish for use where non-plated products are required.
- Extra wide jaw capacity.
- Square jaw opening provides greater strength and better fit.
- Clik-Stop® locking design holds the moving jaw of an adjustable wrench in place when the wrench is in use.



Product ID No.	Max. Opening	L	Weight lbs.	ASME Spec.
<b>J704SL</b>	1/2"	4"	0.14 lbs.	ASME B107.8
<b>J706SL</b>	5/16"	6"	0.28 lbs.	ASME B107.8
<b>J708SL</b>	1-1/8"	8"	0.57 lbs.	ASME B107.8
<b>J710SL</b>	1-15/16"	10"	1.06 lbs.	ASME B107.8
<b>J712SL</b>	1-1/2"	12"	1.50 lbs.	ASME B107.8
<b>J715SL</b>	1-11/16"	15"	3.07 lbs.	ASME B107.8
<b>J718SL</b>	2-1/16"	18"	5.60 lbs.	ASME B107.8

## FACOM® MONKEY WRENCHES

- Satin finish provides corrosion resistance and a slip resistant grip.
- Sturdy, wide-opening tools for heavy-duty work on farms and building sites.
- Fixed jaw/handle and worm gear made from hardened steel.
- Smooth jaw faces help prevent marring of fastener surfaces.



Product ID No.	Max. Opening	Length	Jaw Depth	Jaw Thickness	Weight lbs.
<b>FA-105.230</b>	2-3/8"	9-1/16"	1-25/32"	25/32"	1.15 lbs.
<b>FA-105.280</b>	2-3/4"	11-1/32"	1-11/32"	21/32"	1.79 lbs.
<b>FA-105.375</b>	3-1/8"	14-23/32"	1-25/32"	7/8"	3.36 lbs.