

Project:	
Fixture Type:	
Location:	
Contact/Phone:	

COMPACT FLUORESCENT STEP/NIGHT LIGHT

7W or 9W COMPACT FLUORESCENT LAMP

ICPL813

PRODUCT DESCRIPTION

ICPL Housing is designed for use in insulated or non-insulated areas.

PRODUCT SPECIFICATIONS

Lamp One 7W or 9W twin tube CFL lamp.

Socket Horizontal mounted in housing.

Ballast 120V normal power factor magnetic • UL listed/CSA certified.


Trims Available in white baked enamel on steel • Fastens to housing with two torsion springs.


Labels UL listed for damp locations and IP ● Union made
■ UL Listed/CSA certified.

Testing All reports are based on published industry procedures; field performance may differ from laboratory performance.

Product specifications subject to change without notice.

DIMENSIONS





8 3/4" X 3 3/4" WALL CUTOUT

INSTALLATION

Real Nail 3 Bar Hangers Telescoping, Patented (US Patent D552,969) Real Nail® 3 system permits quick placement of housing anywhere within 24" O.C. joists or suspended ceilings • Integral T-bar notch and clip secures housing in suspended ceiling grid – no accessory clips required • 24" expansion stop allows quick placement of fixture in standard grid spacing • Bars scored in two locations for fast, clean breaking, allowing housing installation in tight applications • Bars captive to mounting frame • Edgemounted for extra strength • Captive bugle-headed ring shank nail for quick one-step installation and easy removal with claw hammer for fixture relocation • Quick-Loc slot and oversized locking set screw lock fixture in position • Bar hanger foot contoured to align to bottom of construction joist • Alternate mounting holes included.

Junction Box Pre-wired junction compartment provided with (3) $\frac{1}{2}$ knockouts with pryout slots and ground wire • 90° C supply connection.

Housing 22-gauge white painted steel • $8\frac{1}{2}$ L x $3\frac{1}{2}$ H x $3\frac{1}{2}$ D.

PRODUCT CODES

Catalog Number	Input Voltage	Lamp Rating (max.)	
ICPL813	120V	7W or 9W Twin Tube CFL	



COMPACT FLUORESCENT STEP/NIGHT LIGHT

7W or 9W COMPACT FLUORESCENT LAMP

ICPL813

ORDERING INFORMATION: Housing and trim each ordered separately.

Example: ICPL813	Example: 840- 1	WH			
Housing		Trim/Descrip	ption		
ICPL813		104-WH	Diffuse Glass Lens, White Trim	7W or 9W twin tube CFL lamp	
		840-WH	Angled Louvers, White Trim	7W or 9W twin tube CFL lamp	
	Trim Finish: WH - White.				

