

6" IC REMODEL HOUSING

INCANDESCENT LAMPS

V6ICRW

TRIMS/LAMPS

| | Cat. No. | Description | Max. Lamp Rating |
|----------------|--|--|---|
| | V3024W-WH V3024B-WH | Conical White Baffle Conical Black Baffle | 50W PAR30, 75W PAR30L, 65W BR30 |
| | V3025W-WH V3025B-WH | Straight White Baffle Straight Black Baffle | 50W PAR30, 50W PAR30L, 75W PAR38 |
| Air-Loc | V3034W-WH◆◆ V3034B-WH◆◆ V3034TW-WH◆◆ V3034TB-WH◆◆ | Full White Baffle Full Black Baffle Full White Baffle with Torsion Springs Full Black Baffle with Torsion Springs | 40W A19 (white only), 75W PAR30, 75W PAR30L, 65W BR30, 90W BR40, 75W PAR38 (black max.) 90W PAR38 (white only) |
| | V3027C-WH | Clear Cone | 50W PAR30, 75W PAR30L, 65W BR30 |
| Air-Loc | V3037W-WH◆◆ V3037TW-WH◆◆ | Full White Cone Full White Cone with Torsion Springs | 40W A19, 75W PAR30, 75W PAR30L, 65W BR30, 75W BR40, 90W PAR38 |
| | V3029-WH | White Eyeball | 65W BR30, 75W PAR30L |
| Air-Loc | V3040N-PW◆ | Stippled Opal Lens Shower with Reflector | 34W A19, 35W PAR30 |
| Air-Loc | V3041-PW◆ | Drop Opal Lens Shower with Reflector | 40W A19 |
| | V3050-WH | Open Frame | 65W BR30 |

Trim Size: 7 $\frac{3}{4}$ " O.D. (except Cat. Nos. V3034, V3037 - 7 $\frac{5}{8}$ " O.D., Cat. Nos. V3040N, V3041, V3050 - 8" O.D.).

Trim Finish: PW - Plastic White (Polycarbonate material shower trim), WH - White.

Note: In Canada when insulation is present, Type IC fixtures must be used.

◆ UL/cUL Listed for use in wet location.

◆◆ UL/cUL Listed for use in wet location with outdoor rated lamp.

Air-Loc Vulite IC housings meet IECC Energy Code requirements per ASTM E283.
Air-Loc® rated trims are pre-gasketed for minimum air leakage with IC housings.