

Single-Phase Encapsulated

General Purpose

.050 - 1 KVA, 130°C Insulation Class; 1.5 - 25 KVA, 180°C Insulation Class

KVA	Catalog Number	Fig.	Height A (in.)	Width B (in.)	Depth C (in.)	Wiring Diagram	Est. Ship Wgt. (lbs.)
120 X 240 V – 120/240 V 60 Hz • Taps None							
.500	411-0051-120	2	10.19	5.06	4.59	S240A	15
1	411-0071-120	2	10.19	5.06	4.59		19
2	411-0091-120	3	12.50	6.69	5.34		41
3	411-0101-120	3	14.56	7.56	7.15		68
5	411-0111-120	3	14.56	7.56	7.15		93
7.5	411-0131-120	4	16.12	13.50	8.55		130
10	411-0151-120	4	16.12	13.50	8.55		155
15	411-0161-120	4	21.12	16.50	10.06		255
25	411-0181-120	4	21.12	16.50	10.06		291
208 V – 120/240 V 60 Hz • Taps None							
.500	411-0051-208	2	10.19	5.06	4.59	S208A	15
1	411-0071-208	2	10.19	5.06	4.59		19
2	411-0091-208	3	12.50	6.69	5.34		41
3	411-0101-208	3	14.56	7.56	7.15		68
5	411-0111-208	3	14.56	7.56	7.15		93
7.5	411-0131-208	4	16.12	13.50	8.55		130
10	411-0151-208	4	16.12	13.50	8.55		155
15	411-0161-208	4	21.12	16.50	10.06		255
25	411-0181-208	4	21.12	16.50	10.06		291
240 X 480 V – 120/240 V 60 Hz • Taps None							
.050	411-0001-000	2	8.03	3.31	3.08	S480A	6
.100	411-0021-000	2	8.03	3.31	3.08		6
.150	411-0031-000	2	8.03	3.31	3.08		6
.250	411-0041-000	2	8.03	3.31	3.08		7
.500	411-0051-000	2	10.19	5.06	4.59		15
.750	411-0061-000	2	10.19	5.06	4.59		18
1	411-0071-000	2	10.19	5.06	4.59		19
1.5	411-0081-000	3	12.50	6.69	5.34		33
2	411-0091-000	3	12.50	6.69	5.34		41
3	411-0101-000	3	14.56	7.56	7.15		68
5	411-0111-000	3	14.56	7.56	7.15		93
7.5	411-0131-000	4	16.12	13.50	8.55		130
10	411-0151-000	4	16.12	13.50	8.55		155
15	411-0161-000	4	21.12	16.50	10.06		255
25	411-0181-000	4	21.12	16.50	10.06		291
240 x 480 V – 120/240 V 60 Hz • Taps: 2 – 2.5% FCAN + 2 – 2.5% FCBN							
3	411-0104-300	3	14.56	7.56	7.15	S480B	68
5	411-0114-300	3	14.56	7.56	7.15		93
7.5	411-0134-300	4	16.12	13.50	8.55		130
10	411-0154-300	4	16.12	13.50	8.55		155
15	411-0164-300	4	21.12	16.50	10.06		255
25	411-0184-300	4	21.12	16.50	10.06		291

Note: Housing dimensions subject to change without notice. Consult website or factory where dimensions are critical.



2

Single-Phase Encapsulated

General Purpose

.050 - 1 KVA, 130°C Insulation Class; 1.5 - 25 KVA, 180°C Insulation Class

KVA	Catalog Number	Fig.	Height A (in.)	Width B (in.)	Depth C (in.)	Wiring Diagram	Est. Ship Wgt. (lbs.)
277 V – 120/240 V 60 Hz • Taps: 2 – 2.5% FCBN							
.250	411-0041-277	2	8.03	3.31	3.08	S277A	6
.500	411-0051-277	2	10.19	5.06	4.59		15
1	411-0071-277	2	10.19	5.06	4.59		19
2	411-0091-277	3	12.50	6.69	5.34		41
3	411-0101-277	3	14.56	7.56	7.15		68
5	411-0111-277	3	14.56	7.56	7.15		93
7.5	411-0131-277	4	16.12	13.50	8.55		130
10	411-0151-277	4	16.12	13.50	8.55		155
15	411-0161-277	4	21.12	16.50	10.06		255
25	411-0181-277	4	21.12	16.50	10.06		291
600 V – 120/240 V 60 Hz • Taps: .050 - 1 KVA None, 1.5 – 25 KVA 4 – 2.5% FCBN							
.050	411-0006-000	2	8.03	3.31	3.08	S600A	6
.100	411-0026-000	2	8.03	3.31	3.08		6
.150	411-0036-000	2	8.03	3.31	3.08		6
.250	411-0046-000	2	8.03	3.31	3.08		7
.500	411-0056-000	2	10.19	5.06	4.59		15
.750	411-0066-000	2	10.19	5.06	4.59		18
1	411-0077-000	2	10.19	5.06	4.59		19
1.5	411-0087-000	3	12.50	6.69	5.34		33
2	411-0097-000	3	12.50	6.69	5.34		41
3	411-0107-000	3	14.56	7.56	7.15		68
5	411-0117-000	3	14.56	7.56	7.15	93	
7.5	411-0137-000	4	16.12	13.50	8.55	130	
10	411-0157-000	4	16.12	13.50	8.55	155	
15	411-0167-000	4	21.12	16.50	10.06	255	
25	411-0187-000	4	21.12	16.50	10.06	291	



International

1 KVA, 130°C Insulation Class; 2.0 - 25 KVA, 180°C Insulation Class

KVA	Catalog Number	Fig.	Height A (in.)	Width B (in.)	Depth C (in.)	Wiring Diagram	Est. Ship Wgt. (lbs.)
190/200/208/220 x 380/400/416/440 V – 120/240 V 50/60 Hz Electrostatic Shielded							
1	511-0078-055	2	10.19	5.06	4.59	S440A	22
2	511-0098-055	3	12.50	6.69	5.34		44
3	511-0108-055	3	14.56	7.56	7.15		61
5	511-0118-055	3	14.56	7.56	7.15		96
7.5	511-0138-055	4	16.12	13.50	8.55		130
10	511-0158-055	4	16.12	13.50	8.55		155
15	511-0168-055	4	21.12	16.50	10.06		255
25	511-0188-055	4	21.12	16.50	10.06		291

Note: Housing dimensions subject to change without notice. Consult website or factory where dimensions are critical.

