


■ KHSST Hand • Machine Screw and Fractional Sizes • Bottoming Chamfer



● first choice  
○ alternate choice

uncoated	D1 size	L	L3	D	number of flutes	pitch diameter limit
K26003	#2 - 56	1.75	0.38	0.141	2	H4
K26009	#4 - 32	1.94	0.56	0.141	3	H2
K26018	#4 - 40	1.94	0.56	0.141	3	H3
K26044	#6 - 32	2.00	0.69	0.141	3	H11
K26036	#6 - 32	2.00	0.69	0.141	3	H5
K26032	#6 - 32	2.00	0.69	0.141	3	H3
K26040	#6 - 32	2.00	0.69	0.141	3	H7
K27302	#6 - 48	2.00	0.69	0.141	3	H2
K27306	#8 - 24	2.13	0.75	0.168	4	H3
K27319	#8 - 32	2.13	0.75	0.168	4	H11
K27316	#8 - 32	2.13	0.75	0.168	4	H7
K27313	#8 - 32	2.13	0.75	0.168	4	H5
K27309	#8 - 32	2.13	0.75	0.168	4	H3
K27323	#8 - 40	2.13	0.75	0.168	4	H2
K27338	#10 - 24	2.38	0.94	0.190	4	H11
K27331	#10 - 24	2.38	0.94	0.190	4	H5
K27327	#10 - 24	2.38	0.94	0.190	4	H3
K27335	#10 - 24	2.38	0.94	0.190	4	H7
K27342	#10 - 28	2.38	0.94	0.190	4	H3
K26046	#10 - 30	2.38	0.88	0.190	4	H3
K26058	#10 - 32	2.38	0.88	0.190	4	H11
K26055	#10 - 32	2.38	0.88	0.190	4	H7
K26051	#10 - 32	2.38	0.88	0.190	4	H5
K26062	#10 - 36	2.38	0.88	0.190	4	H2
K26065	#10 - 40	2.38	0.88	0.190	4	H2
K26069	0.210 - 36	2.50	0.94	0.220	4	H3
K27610	#12 - 24	2.38	0.94	0.220	4	H11
K27614	#12 - 28	2.38	0.94	0.220	4	H11
K26078	#12 - 32	2.38	0.94	0.220	4	H3
K26082	#12 - 36	2.38	0.94	0.220	4	H2
K26085	#14 - 14	2.50	0.94	0.255	4	H3
K26088	#14 - 24	2.50	0.94	0.255	4	H3
K26096	1/4 - 20	2.50	1.00	0.255	4	H11
K26094	1/4 - 20	2.50	1.00	0.255	4	H7
K26099	1/4 - 24	2.50	1.00	0.255	4	H3
K26103	1/4 - 27	2.50	1.00	0.255	4	H3
K26114	1/4 - 28	2.50	1.00	0.255	4	H11
K26111	1/4 - 28	2.50	1.00	0.255	4	H7
K26107	1/4 - 28	2.50	1.00	0.255	4	H5
K26125	1/4 - 32	2.50	1.00	0.255	4	H5



(continued)