


**■ KHSST Spiral Point • Machine Screw and Fractional Sizes • Plug Chamfer**



● first choice  
○ alternate choice

uncoated	D1 size	L	L3	D	number of flutes	pitch diameter limit
K26005	#2 - 56	1.75	0.38	0.141	2	H5
K26004	#2 - 56	1.75	0.38	0.141	2	H4
K26000	#2 - 56	1.75	0.38	0.141	2	H3
K26020	#4 - 40	1.94	0.56	0.141	2	H7
K26019	#4 - 40	1.94	0.56	0.141	2	H3
K26029	#5 - 40	1.94	0.63	0.141	2	H5
K27295	#6 - 32	2.00	0.69	0.141	2	H11
K26037	#6 - 32	2.00	0.69	0.141	2	H5
K27299	#6 - 40	2.00	0.69	0.141	2	H3
K27303	#6 - 48	2.00	0.69	0.141	2	H2
K27320	#8 - 32	2.13	0.75	0.168	2	H11
K27314	#8 - 32	2.13	0.75	0.168	2	H5
K27339	#10 - 24	2.38	0.94	0.194	2	H11
K27332	#10 - 24	2.38	0.94	0.194	2	H5
K27328	#10 - 24	2.38	0.94	0.194	2	H3
K26059	#10 - 32	2.38	0.94	0.194	2	H11
K26052	#10 - 32	2.38	0.94	0.194	2	H5
K26048	#10 - 32	2.38	0.94	0.194	2	H4
K26047	#10 - 32	2.38	0.94	0.194	2	H3
K26066	#10 - 40	2.38	0.94	0.194	2	H2
K26095	1/4 - 20	2.50	1.00	0.255	2	H7
K26091	1/4 - 20	2.50	1.00	0.255	2	H3
K26112	1/4 - 28	2.50	1.00	0.255	2	H7
K26108	1/4 - 28	2.50	1.00	0.255	2	H5
K26104	1/4 - 28	2.50	1.00	0.255	2	H3
K26122	1/4 - 32	2.50	1.00	0.255	2	H3
K26140	5/16 - 18	2.72	1.13	0.318	2	H3
K26159	5/16 - 24	2.72	1.13	0.318	2	H11
K26153	5/16 - 24	2.72	1.13	0.318	2	H5
K26149	5/16 - 24	2.72	1.13	0.318	2	H3
K26169	5/16 - 32	2.72	1.13	0.318	2	H3
K26177	3/8 - 16	2.94	1.25	0.381	2	H3
K26176	3/8 - 16	2.94	1.25	0.381	3	H3
K26202	3/8 - 24	2.94	1.25	0.381	3	H11
K26195	3/8 - 24	2.94	1.25	0.381	3	H5
K26225	7/16 - 14	3.16	1.44	0.323	3	H11
K26262	1/2 - 13	3.38	1.66	0.429	3	H3
K26283	1/2 - 20	3.38	1.66	0.429	3	H11
K26277	1/2 - 20	3.38	1.66	0.429	3	H3
K28490	9/16 - 12	3.59	1.66	0.542	3	H3



(continued)