



## FITTINGS GE SERIES



1/2", 3/4" and 1" Bodies  
Class I, Div. 1 & 2, Groups B, C & D  
Class I, Zone 1, Groups IIB, IIA  
1-1/4", 1-1/2", and 2" Bodies  
Class I, Div. 1 & 2, Group D  
Class I, Zone 1, Group IIA  
Class II, Div. 1 & 2, Groups E, F, G  
Class III  
For GEJ Series CSA applications for  
Class I Group C, seal conduit within 18  
inches  
Type 4 & 4X

 LISTED E 10514

 LR11716

### Applicable Third Party Standards

UL Standards: 886 and 1203

CSA Standard: C22.2 No. 30

Fed Spec: W-C-586D

Mil Spec: F-28675

## FEATURES-SPECIFICATIONS

### Features

GE conduit outlet boxes have:

- GEM, GEC and GES have water shedding cover – suitable for wet locations when mounted in upright position
- External cover threads on body protecting conductors from damage during pulling
- No pinching of conductors during cover installation
- Ten different hub arrangements
- Taper threaded hubs to provide ground continuity
- Smooth integral hub bushing to protect conductor insulation when pulling
- Internally threaded cover openings for additional wiring room
- Covers furnished with boxes
- Weather-resistant finish
- Green ground screw standard in all boxes

### Materials

#### Aluminum

- **BODY** Copper-free aluminum (less than 1/10 of 1%)
- **FINISH** Electrostatically applied powder coating
- **COVER** (Aluminum) Copper-free aluminum (less than 1/10 of 1%). Electrostatically applied powder coating

#### Iron

- **BODY** Duraloy iron alloy
- **FINISH** Tri-coat finish of electrozinc, chromate sealant, and electrostatically applied powder coating
- **COVER** (Aluminum) Copper-free aluminum (less than 1/10 of 1%). Electrostatically applied powder coating

### Size Ranges

- Hub – 1/2" to 2"
- Cover opening – 2-1/16" to 4-7/8" diameter



## ALUMINUM AND IRON OUTLET BODIES



**GEC  
T Type**



**GES  
X Type**



**GEJ  
LB Type**

### T TYPE OUTLET BODY\*

| CATALOG NUMBER |              | HUB SIZE | DIMENSIONS    |              |               |              |              |              | COVER OPENINGS | VOLUME CU. IN. |
|----------------|--------------|----------|---------------|--------------|---------------|--------------|--------------|--------------|----------------|----------------|
| KILLARK ALUM.  | DURALOY IRON |          | A             | B            | C             | D            | E            | F            |                |                |
| GEMT-1         | —            | 1/2"     | 2-13/16" (56) | 3" (76)      | 2-1/16" (52)  | 2-5/16 (59)  | 11/16" (17)  | 13/16" (21)  | 2-1/16" (52)   | 8              |
| GEMT-2         | —            | 3/4"     | 2-13/16" (56) | 3" (76)      | 2-1/16" (52)  | 2-5/16 (59)  | 11/16" (17)  | 13/16" (21)  | 2-1/16" (52)   | 8              |
| GECTT-1        | GECTT-1M     | 1/2"     | 3-11/16" (93) | 3-5/8" (92)  | 2-11/16" (68) | 2-3/4" (70)  | 1" (25)      | 13/16" (21)  | 2-11/16" (68)  | 19             |
| GECTT-2        | GECTT-2M     | 3/4"     | 3-11/16" (93) | 3-5/8" (92)  | 2-11/16" (68) | 2-3/4" (70)  | 1" (25)      | 13/16" (21)  | 2-11/16" (68)  | 19             |
| GECTT-3        | GECTT-3M     | 1"       | 3-11/16" (93) | 3-5/8" (92)  | 2-11/16" (68) | 2-3/4" (70)  | 1" (25)      | 13/16" (21)  | 2-11/16" (68)  | 19             |
| GESTT-3        | GESTT-3M     | 1"       | 5-1/16" (129) | 4-1/8" (105) | 3-9/16" (90)  | 3-7/16" (87) | 1-1/16" (27) | 1-1/8" (29)  | 3-9/16" (90)   | 42             |
| GESTT-4        | GESTT-4M     | 1-1/4"   | 5-1/16" (129) | 4-1/8" (105) | 3-9/16" (90)  | 3-7/16" (87) | 1-1/16" (27) | 1-1/8" (29)  | 3-9/16" (90)   | 42             |
| GEJTT-5        | GEJTT-5M     | 1-1/2"   | 6-1/4" (159)  | 4-3/8" (111) | 4-7/8" (124)  | 3-9/16" (90) | 1-3/16" (30) | 1-3/16" (30) | 4-7/8" (124)   | 75             |
| GEJTT-6        | GEJTT-6M     | 2"       | 6-1/4" (159)  | 4-3/8" (111) | 4-7/8" (124)  | 3-9/16" (90) | 1-1/2" (38)  | 1-3/16" (30) | 4-7/8" (124)   | 75             |

### X TYPE OUTLET BODY\*


|         |          |        |               |              |               |              |              |              |               |    |
|---------|----------|--------|---------------|--------------|---------------|--------------|--------------|--------------|---------------|----|
| GEMX-1  | —        | 1/2"   | 2-13/16" (56) | 3" (76)      | 2-1/16" (52)  | 2-5/16 (59)  | 11/16" (17)  | 13/16" (21)  | 2-1/16" (52)  | 8  |
| GEMX-2  | —        | 3/4"   | 2-13/16" (56) | 3" (76)      | 2-1/16" (52)  | 2-5/16 (59)  | 11/16" (17)  | 13/16" (21)  | 2-1/16" (52)  | 8  |
| GECXT-1 | GECXT-1M | 1/2"   | 3-11/16" (93) | 3-5/8" (92)  | 2-11/16" (68) | 2-3/4" (70)  | 1" (25)      | 13/16" (21)  | 2-11/16" (68) | 19 |
| GECXT-2 | GECXT-2M | 3/4"   | 3-11/16" (93) | 3-5/8" (92)  | 2-11/16" (68) | 2-3/4" (70)  | 1" (25)      | 13/16" (21)  | 2-11/16" (68) | 19 |
| GECXT-3 | GECXT-3M | 1"     | 3-11/16" (93) | 3-5/8" (92)  | 2-11/16" (68) | 2-3/4" (70)  | 1" (25)      | 13/16" (21)  | 2-11/16" (68) | 19 |
| GESXT-3 | GESXT-3M | 1"     | 5-1/16" (129) | 4-1/8" (105) | 3-9/16" (90)  | 3-7/16" (87) | 1-1/16" (27) | 1-1/8" (29)  | 3-9/16" (90)  | 42 |
| GESXT-4 | GESXT-4M | 1-1/4" | 5-1/16" (129) | 4-1/8" (105) | 3-9/16" (90)  | 3-7/16" (87) | 1-1/16" (27) | 1-1/8" (29)  | 3-9/16" (90)  | 42 |
| GEJXT-5 | GEJXT-5M | 1-1/2" | 6-1/4" (159)  | 4-3/8" (111) | 4-7/8" (124)  | 3-9/16" (90) | 1-1/2" (38)  | 1-3/16" (30) | 4-7/8" (124)  | 75 |
| GEJXT-6 | GEJXT-6M | 2"     | 6-1/4" (159)  | 4-3/8" (111) | 4-7/8" (124)  | 3-9/16" (90) | 1-1/2" (38)  | 1-3/16" (30) | 4-7/8" (124)  | 75 |

### LB TYPE OUTLET BODY\*


|          |           |        |               |              |               |              |              |              |               |    |
|----------|-----------|--------|---------------|--------------|---------------|--------------|--------------|--------------|---------------|----|
| GEMLB-1  | —         | 1/2"   | 2-13/16" (56) | 3" (76)      | 2-1/16" (52)  | 2-5/16 (59)  | 11/16" (17)  | 13/16" (21)  | 2-1/16" (52)  | 8  |
| GEMLB-2  | —         | 3/4"   | 2-13/16" (56) | 3" (76)      | 2-1/16" (52)  | 2-5/16 (59)  | 11/16" (17)  | 13/16" (21)  | 2-1/16" (52)  | 8  |
| GECLBT-1 | GECLBT-1M | 1/2"   | 3-11/16" (93) | 3-5/8" (92)  | 2-11/16" (68) | 2-3/4" (70)  | 1" (25)      | 13/16" (21)  | 2-11/16" (68) | 19 |
| GECLBT-2 | GECLBT-2M | 3/4"   | 3-11/16" (93) | 3-5/8" (92)  | 2-11/16" (68) | 2-3/4" (70)  | 1" (25)      | 13/16" (21)  | 2-11/16" (68) | 19 |
| GECLBT-3 | GECLBT-3M | 1"     | 3-11/16" (93) | 3-5/8" (92)  | 2-11/16" (68) | 2-3/4" (70)  | 1" (25)      | 13/16" (21)  | 2-11/16" (68) | 19 |
| GESLBT-3 | GESLBT-3M | 1"     | 5-1/16" (129) | 4-1/8" (105) | 3-9/16" (90)  | 3-7/16" (87) | 1-1/16" (27) | 1-1/8" (29)  | 3-9/16" (90)  | 42 |
| GESLBT-4 | GESLBT-4M | 1-1/4" | 5-1/16" (129) | 4-1/8" (105) | 3-9/16" (90)  | 3-7/16" (87) | 1-1/16" (27) | 1-1/8" (29)  | 3-9/16" (90)  | 42 |
| GEJLBT-5 | GEJLBT-5M | 1-1/2" | 6-1/4" (159)  | 4-3/8" (111) | 4-7/8" (124)  | 3-9/16" (90) | 1-1/2" (38)  | 1-3/16" (30) | 4-7/8" (124)  | 75 |
| GEJLBT-6 | GEJLBT-6M | 2"     | 6-1/4" (159)  | 4-3/8" (111) | 4-7/8" (124)  | 3-9/16" (90) | 1-1/2" (38)  | 1-3/16" (30) | 4-7/8" (124)  | 75 |

\* For GROUP B applications, contact factory.


### DIMENSIONS



**T Type**



**X Type**



**LB Type**