

Hammers

Brass Sledge Hammers-Fiberglass Rubber Grip Handle

 Used in non-sparking environments or to avoid damage to struck objects 	7HBRFRH14
Head forged from brass for softer, non-damaging blow	
Head is pinned to handle as well as epoxied to prevent head coming off	
• A set to be all the set to be all the term of a set of a feat set of the set of the set of the set of	

- Comfortable, thick rubber grip handle for increased protection from shock and vibration
- Handle includes both overstrike protection and large sweep at base to prevent loss of grip
- This product must be maintained in accordance with Australian standard AS 3797:1991

Cat. No.	Head Weight	Overall Length	Weight
7HBRFRH04	4.0 lbs. (1.81 kg)	16" (406.4 mm)	4.9 lbs. (2.22 kg)
7HBRFRH07	7.0 lbs. (3.18 kg)	32" (812.8 mm)	9.9 lbs. (4.49 kg)
7HBRFRH10	10 lbs. (4.54 kg)	36" (914.4 mm)	12.2 lbs. (5.53 kg)
7HBRFRH14	14.0 lbs. (6.35 kg)	36" (914.4 mm)	16.8 lbs. (7.62 kg)

Chipping Hammer - Rubber Grip

- Used for chipping off slag and spatter around welds
- Also used as geologists' or miners' tool
- Head forged from chrome alloy steel and hardened and tempered for maximum toughness
- Ground and sharpened vertical chisel and diamond point
- Excellent balance with hardened ends that do no flatten when chipping
- Precision heat treated to best suit product application



Cat. No.	Head Length	Overall Length	Weight
5WHRG	6-11/16" (169.9 mm)	10-15/64" (260.0 mm)	1.1 lbs. (0.50 kg)

Safety Punches & Tyre (Tire) Levers

Wire Rope Punches

- Used to safely drive out pins and keys in machinery
- Long, two-handed rubber handle to lessen shocks from blows
- Head attached with wire rope to reduce shock
- Urethane ring around head to reduce likelihood of chipping
- Heat-treated punch, so it will not shatter

Cat. No.	Diameter	Shaft Length	Weight
7WRP13	1/2" (12.7 mm)	4-3/4" (120.7 mm)	3.0 lbs. (1.36 kg)
7WRP16	5/8" (15.9 mm)	4-3/4" (120.7 mm)	3.2 lbs. (1.45 kg)
7WRP19	3/4" (19.1 mm)	4-3/4" (120.7 mm)	3.6 lbs. (1.63 kg)
7WRP22	7/8" (22.2 mm)	4-3/4" (120.7 mm)	4.4 lbs. (2.00 kg)
7WRP25	1" (25.4 mm)	4-3/4" (120.7 mm)	4.6 lbs. (2.09 kg)
7WRP32	1-1/4" (31.8 mm)	4-3/4" (120.7 mm)	5.3 lbs. (2.40 kg)

See page 310 for additional information on warnings.





309