

Cushion-Grip Nut Drivers

Magnetic Tip Nut Drivers – Hollow Shafts*

Additional Feature:

- Exclusive hollow shaft* design with Rare Earth magnetic tip features unobstructed pass-through, even on long bolts.

| Cat. No. | Color Code | Hex Size | Shaft Length | Overall Length | Weight (lbs.) |
|------------|------------|----------|--------------|------------------|---------------|
| 610-1/4M | red | 1/4" | 3" (76 mm) | 1-1/2" (89 mm) | .10 |
| 610-5/16M | yellow | 5/16" | 3" (76 mm) | 1-1/2" (89 mm) | .10 |
| 610-3/8M | blue | 3/8" | 3" (76 mm) | 1-1/2" (89 mm) | .10 |
| 630-3/16M* | black | 3/16" | 3" (76 mm) | 6-3/4" (171 mm) | .20 |
| 630-1/4M | red | 1/4" | 3" (76 mm) | 6-3/4" (171 mm) | .20 |
| 630-5/16M | yellow | 5/16" | 3" (76 mm) | 6-3/4" (171 mm) | .20 |
| 630-11/32M | green | 11/32" | 3" (76 mm) | 6-3/4" (171 mm) | .20 |
| 630-3/8M | blue | 3/8" | 3" (76 mm) | 6-3/4" (171 mm) | .20 |
| 630-7/16M | brown | 7/16" | 3" (76 mm) | 7-5/16" (186 mm) | .25 |
| 630-1/2M | red | 1/2" | 3" (76 mm) | 7-5/16" (186 mm) | .25 |
| 646-3/16M* | black | 3/16" | 6" (152 mm) | 9-3/4" (248 mm) | .25 |




630-3/8M

| Cat. No. | Color Code | Hex Size | Shaft Length | Overall Length | Weight (lbs.) |
|------------|------------|----------|--------------|-------------------|---------------|
| 646-1/4M | red | 1/4" | 6" (152 mm) | 9-3/4" (248 mm) | .25 |
| 646-5/16M | yellow | 5/16" | 6" (152 mm) | 9-3/4" (248 mm) | .25 |
| 646-11/32M | green | 11/32" | 6" (152 mm) | 9-3/4" (248 mm) | .25 |
| 646-3/8M | blue | 3/8" | 6" (152 mm) | 9-3/4" (248mm) | .30 |
| 646-7/16M | brown | 7/16" | 6" (152 mm) | 10-5/16" (262 mm) | .35 |
| 646-1/2M | red | 1/2" | 6" (152 mm) | 10-5/16" (262 mm) | .35 |
| 618-1/4M | red | 1/4" | 18" (457 mm) | 21-3/4" (552 mm) | .50 |
| 618-5/16M | yellow | 5/16" | 18" (457 mm) | 21-3/4" (552 mm) | .50 |

*3/16" magnetic nut driver does not have a hollow shaft.

Drive-A-Matic Cushion-Grip Nut Driver



632

Additional Features:

- Automatically fits 15 different nut and screw sizes.
- Hex head adjusts to the proper size as you turn it.
- Will drive or loosen hex nuts from 1/4" (6.4 mm) to 7/16" (11.1 mm), hex-head screws from No. 6 to 1/4" (6.4 mm), and socket-head cap screws from No. 8 to 5/16" (7.9 mm).

| Cat. No. | Overall Length | Weight (lbs.) |
|----------|----------------------------------------------------|---------------|
| 632 | 7" (178 mm) when open, 6-3/4" (171 mm) when closed | .35 |

Coated Hollow-Shaft Nut Drivers



640-1/2

Additional Features:

- Entire shaft plastic coated for circuit protection only. NOT INSULATED.
- Special plastic coating resists cutting, cracking and chipping.
- Thin coating permits use in confined areas.

| Cat. No. | Color Code | Hex Size | Shaft Length | Overall Length | Weight (lbs.) |
|----------|------------|----------|--------------|------------------|---------------|
| 640-3/16 | black | 3/16" | 3" (76 mm) | 6-3/4" (171 mm) | .25 |
| 640-1/4 | red | 1/4" | 3" (76 mm) | 6-3/4" (171 mm) | .25 |
| 640-5/16 | yellow | 5/16" | 3" (76 mm) | 6-3/4" (171 mm) | .25 |
| 640-3/8 | blue | 3/8" | 3" (76 mm) | 6-3/4" (171 mm) | .25 |
| 640-7/16 | brown | 7/16" | 3" (76 mm) | 7-5/16" (186 mm) | .30 |
| 640-1/2 | red | 1/2" | 3" (76 mm) | 7-5/16" (186 mm) | .25 |
| 640-9/16 | orange | 9/16" | 4" (102 mm) | 9-3/8" (238 mm) | .40 |
| 640-5/8 | yellow | 5/8" | 4" (102 mm) | 9-3/8" (238 mm) | .40 |

⚠ WARNING: NOT insulated. Coating is intended for protection of circuits only.



All dimensions are in inches and (millimeters).

⚠ WARNING: Always wear approved eye protection.

⚠ WARNING: NOT insulated. Will NOT protect against electrical shock.

