# **Tapping Tools and Awls**

#### **Cushion-Grip Triple Taps and 6-in-1 Tap Tool**

- Quickly forms new threads, re-forms burred threads, and cleans out plaster obstructions.
- Each tap size rethreads to next larger size if threads are stripped.

| Cat. No. | Tap Sizes  | Overall Length | Weight (lbs.) |
|----------|--|----------------|---------------|
| 623-20   | Triple Tap 10-24, 12-24, 1/4-20                    | 7-3/4"         | .25           |
| 623-24   | Triple Tap 6-32, 8-32, 10-24                       | 7-3/4"         | .25           |
| 626      | 6-in-1 Tap 6-32, 8-32, 10-32, 10-24, 12-24, 1/4-20 | 7-3/4"         | .25           |



626

| Replacement Taps |                      |                             |
|------------------|----------------------|-----------------------------|
| 628-20           | 10-24, 12-24, 1/4-20 | replacement for 623-20, 626 |
| 626-24           | 6-32, 8-32, 10-24    | replacement for 623-24      |
| 626-32           | 6-32, 8-32, 10-32    | replacement for 623-32, 626 |

### **6-in-1 Tapping Tool**



627-20

- Quickly forms new threads, re-forms burred threads, and cleans out plaster obstructions.
- Each tap size rethreads to next larger size if threads are stripped.
- Two high-carbon steel taps are secured in reversible holder.

| Cat. No. | Tap Sizes                               | Overall Length  | Weight (lbs.) |
|----------|---|-----------------|---------------|
| 627-20   | 6-32, 8-32, 10-32, 10-24, 12-24, 1/4-20 | 7-5/8" (194 mm) | 0.35          |

| Replace | ment Taps            |  |
|---------|----------------------|--|
| 626-32  | 10-32, 8-32, 6-32    |  |
| 628-20  | 10-24, 12-24, 1/4-20 |  |

## **Triple Taps**



625-24

- Quickly forms new threads, re-forms burred threads, and cleans out plaster obstructions.
- Each tap size rethreads to next larger size if threads are stripped.

| Cat. No.              | Tap Sizes                        | Color Code | Overall Length  | Weight (lbs.) |  |
|-----------------------|----------------------------------|------------|-----------------|---------------|--|
| 625-24                | 6-32, 8-32, 10-24                | blue       | 7-1/8" (181 mm) | 0.20          |  |
| 625-32                | 6-32, 8-32, 10-32                | orange     | 7-1/8" (181 mm) | 0.20          |  |
| Replacement Taps      |                                  |            |                 |               |  |
| Replace               | ment Taps                        |            |                 |               |  |
| <b>Replace</b> 626-24 | ment Taps<br>for Cat. No. 625-24 |            |                 |               |  |

# **Cushion-Grip Scratch Awl**



- Professional, heavy-duty, hard-pointed awl.
- Scribes metal, starts screw holes, performs a variety of piercing and punching jobs.
- Rigid, chrome-plated, heat-treated, tempered-steel shank has full reinforcing bolster at handle for extra strength and for handle impact reinforcement.
- Internal flanges provide solid shank anchor.
- Cushion-Grip handle allows for greater comfort.

| Cat. No. | Blade Length   | Overall Length  | Weight (lbs.) |
|----------|----------------|-----------------|---------------|
| 650      | 3-1/2" (89 mm) | 7-7/8" (200 mm) | .25           |

AWARNING: Do NOT hammer on tool

#### **Steel Scratch Awl**



66385

- One-piece forged-steel blade and bolstered shank.
- Heat treated for long life.
- Well-balanced for top efficiency during use.
- Black finish for rust resistance.

| Cat. No. | Blade Length   | Overall Length | Weight (lbs.) |
|----------|----------------|----------------|---------------|
| 66385    | 3-1/2" (89 mm) | 7" (178 mm)    | .30           |

All dimensions are in inches and (millimeters).

**AWARNING:** Always wear approved eye protection.

**AWARNING:** NOT insulated. Will NOT protect against electrical shock.

**AWARNING:** Never use on or near live electrical circuits.

