Fish Tapes

Features:

Polypropylene case and handle offer the maximum in impact resistance.

Round inner ring design provides a smooth, surface for winding and rewinding.

Laser etched markings in 1' increments* allow you to more accurately measure the depth of conduit runs and determine the amount of tape left to pay out.



*except nylon & spiral steel



- Unique sloped handle

optimizes hand position for quick hand-over-hand rewinds.

Raised fingergrips

transfer 100% of the winding power from your hand and fingers.

Available in steel, fiberglass and nylon with a wide variety of tips.

Fiberglass Fish Tapes

Additional Features:

- Designed for flexibility and easy navigation through conduit runs.
- Non-conductive, fiberglass fish tape slides easily over existing wires and through multiple bends.
- Durable 7" leader helps push through crowded conduit.
- The lightweight and strong fiberglass composite tape resists harsh elements and is strength rated up to 500 pulling pounds.
- Repair kit (Cat. No. 56115) available to replace tips.
- Replacement metal eyelets (Cat. No. 56116) and spiral steel leaders (Cat. No. 56120) available.





1' permanent laser etched descending increments.





0	+LEIN
	EST. 18
	10010

Cat. No.	Tape Size	Reel Diameter	Weight	
56009	50' L x 3/16" W (7" leader) (15 m L x 4.8 mm W)	13" (330 mm)	2.8 lbs. (1.27 kg)	
56010	100' L x 3/16" W (7" leader) (30 m L x 4.8 mm W)	13" (330 mm)	3.5 lbs. (1.59 kg)	
56014	200' L x 3/16" W (7" leader) (60 m L x 4.8 mm W)	17" (432 mm)	6.2 lbs. (2.81 kg)	
Replacement Parts				
56115	fiberglass fish tape repair kit		2.18 lbs. (0.1 kg)	
56116	replacement eyelets		.06 lbs. (0.03 kg)	
56120	replacement flexible leaders		.11 lbs. (0.05 kg)	



56115

All dimensions are in inches and (millimeters) unless otherwise specified.

AWARNING: Always wear approved eye protection.

AWARNING: Never remove screws while fish tape is coiled inside reel.

AWARNING: NEVER use on or near live electrical circuits.

AWARNING: Use a safe work position to avoid loss of balance.



Fish Tapes

1/8" Wide Steel Fish Tapes

Additional Features:

- High strength spring steel fish tapes are stiff for long runs and are great for heavy duty wire pulls.
- Full grip style handle gives you a firm, steady grip as you pull tape from the case.
- Stainless Steel fish tape (Cat. Nos. 56007, 56008) is corrosion resistant and extends the life of the tool.



1' permanent laser etched descending increments.



Cat. No.	Tape Size	Reel Diameter	Weight	
Stainless Steel for corrosion resistance				
56007	125' L x 1/8" W x .062" H (38 m L x 3 mm W x 1.5 mm H)	13" (330 mm)	4.7 lbs. (2.13 kg)	
56008	240' L x 1/8" W x .062" H (73 m L x 3 mm W x 1.5 mm H)	13" (330 mm)	7.5 lbs. (3.40 kg)	
Flat Steel				
56000	25' L x 1/8" W x .045" H (7 m L x 3 mm W x 1.1 mm H)	7" (178 mm)	1.0 lbs. (0.45 kg)	
56001	50' L x 1/8" W x .045" H (15 m L x 3 mm W x 1.1 mm H)	7" (178 mm)	1.3 lbs. (0.59 kg)	
56002	65' L x 1/8" W x .062" H (19 m L x 3 mm W x 1.5 mm H)	9" (229 mm)	2.6 lbs. (1.18 kg)	
56003	125' L x 1/8" W x .062" H (38 m L x 3 mm W x 1.5 mm H)	13" (330 mm)	4.7 lbs. (2.13 kg)	
56004	240' L x 1/8" W x .062" H (73 m L x 3 mm W x 1.5 mm H)	13" (330 mm)	7.5 lbs. (3.40 kg)	
Replacement Tapes				
56065	65' L x 1/8" W x .062" H (19 m L x 3 mm W x 1.5 mm H)	-	1.7 lbs. (0.77 kg)	
56125	125' L x 1/8" W x .062" H (38 m L x 3 mm W x 1.5 mm H)	_	3.3 lbs. (1.50 kg)	
56240	240' L x 1/8" W x .062" H (73 m L x 3 mm W x 1.5 mm H)	_	6.1 lbs. (2.77 kg)	

1/4" Wide Steel Fish Tapes

Additional Features:

Cat. No.

56005

56006

- Tempered, high quality tape keeps its stability as it glides between surfaces for effective pushing and pulling of wire under carpets, through insulated walls and over suspended ceilings.
- 25' length with no snag tip, is perfect for short wire runs associated with light commercial, residential and voice-datavideo-audio installations (Cat. No. 56005).

Tape Size



56005 has a no snag plastic tip



1' permanent laser etched descending increments.



6.8 lbs. (3.08 kg)

 Reel Diameter
 Weight

 7" (178 mm)
 1.1 lbs. (0.50 kg)

All dimensions are in inches and (millimeters) unless otherwise specified.

25' L x 1/4" W x .030" H (7 m L x 6.3 mm W x .7 mm H)

100' L x 1/4" W x .062" H (30 m L x 6.3 mm W x 1.5 mm H)

AWARNING: Always wear approved eye protection.

AWARNING: Never remove screws while fish tape is coiled inside reel.

AWARNING: NEVER use on or near live electrical circuits.

13" (330 mm)

AWARNING: Use a safe work position to avoid loss of balance.



