# EST. 1857

## **Wire Strippers/Cutters**

#### **Wire Stripper/Cutter**

- Strips six standard wire sizes without nicking wire.
- Scissors action of 1/2" (13 mm) wide cutter makes clean cuts with little effort.
- Serrated nose jaws to bend, shape or pull wire; holes for looping wire ends.
- Spring-loaded for self-opening action.
- Comfortable, plastic-covered handles.

Cat. No.	Overall Length	Strips and Cuts	Handle Color	Weight (lbs.)
1011	6-1/8" (156 mm)	10 - 20 AWG solid & stranded (4.0 mm <sup>2</sup> 50 mm <sup>2</sup> )	blue	.23
1011M	6-1/8" (156 mm)	0.15 - 4.0 mm <sup>2</sup> stranded wire	blue	.23



1011

#### Adjustable Wire Strippers/Cutters — Solid and Stranded Wire

- A handy, light, compact tool for stripping insulation.
- Convenient hole for looping or bending wire.
- Black-oxide finish with plastic-dipped handles.
- Cuts, strips, and loops 12-26 solid and stranded wire.
- Adjustable slide stop with set screw for repeat stripping work.

Cat. No.	Hold-Open Spring	Overall Length	Strips and Cuts	Handle Color	Weight (lbs.)
1004	yes	5" (127 mm)	12 – 26 AWG solid & stranded (2.5 mm² – 0.14 mm²)	yellow	.18
1003	no	5" (127 mm)	12 – 26 AWG solid & stranded (2.5 mm² – 0.14 mm²)	yellow	.14





1004

#### Adjustable Wire Stripper — Solid and Stranded Wire

- Simply dial desired wire size for fast, easy stripping.
- Adjustable tool makes short work of cutting and stripping operations.
- Finely honed nose cutter easily gets into tight areas.
- Wire gauge dial sets stripping dies to proper size, helps prevent nicked wire.
- Black-oxide finish with plastic-dipped handles.
- Spring-loaded design tool opens automatically after each action.

Cat. No.	Overall Length	Strips and Cuts	Handle Color	Weight (lbs.)
74007	5-1/8" (130 mm)	12 – 24 AWG solid & stranded (2.5 mm² – .25 mm²)	yellow	.15



### Katapult® Wire Stripper/Cutter

- Quick and easy 8-22 AWG wire stripping and cutting.
- Compound action wire stripping: grip and strip via single action squeezing motion.
- Precision machined stripping holes easily remove jacket insulation without damaging the wire.
- Remove up to 1" (24 mm) in length of the insulation layer (jacket layer) in a single step.
- Tension loaded wire-grip gently holds the cable in place while retaining the cable geometry.
- Recoil spring design returns tool to ready position upon cycle completion.
- Cast alloy chassis with heavy-duty Ecoat finish for corrosion resistance and durability.
- Additional precision machined steel cutting blades available.

Cat. No.	Color	Strips	Overall Length	Weight
11063W	blue/black	8-22 AWG (6 mm² – .34 mm²)	6.6" (168 mm)	12.1 oz. (0.34 g)





11063W

Cat. No.		Weight		
Replacement Blades Sets				
VDV110-046	RG6 coaxial cable replacement blades	.01		
11082	10 AWG max wire cutting blades	.01		
11073	16 – 26 AWG (1.0 mm <sup>2</sup> – .14 mm <sup>2</sup> )	.01		
Wire Stop/Gaug	ge			
11081	adjustable wire stop	.01		

All dimensions are in inches and (millimeters).

AWARNING: NOT insulated. Will NOT protect against electrical shock.

**AWARNING:** Never use on or near live electrical circuits.

**AWARNING:** Always wear approved eye protection.

58