Insulated High-Leverage Diagonal-Cutting Pliers – Angled Head

Additional Features:

- Angled head for easier work in confined spaces.
- High-leverage design. Rivet is closer to the cutting edge for 36% greater cutting power than other plier designs.



| Cat. No. | Overall Length | Jaw Length | Jaw Width | Jaw Thickness | Cutting Knives | |
|------------------|---------------------------|----------------|-----------------|---------------|----------------|--|
| D248-8-INS | 8-1/4" (210 mm) | 13/16" (21 mm) | 1-3/16" (30 mm) | 7/16" (11 mm) | standard | |
| 2000 Series* – H | Heavy-duty cutting knives | | | | | |
| D2000-48-INS | 8-1/4" (210 mm) | 13/16" (21 mm) | 1-3/16" (30 mm) | 7/16" (11 mm) | standard | |
| *** | | | | | | |

*Cuts ACSR, screws, nails, and most hardened wire. Features combination polished and black-oxide finish.

Insulated Heavy-Duty Diagonal-Cutting Pliers – Tapered Nose

Additional Features:

- Heavy-duty tapered nose design.
- One-inch deep jaws easily reach into confined spaces.



D220-7-INS

| Cat. No. | Overall Length | Jaw Length | Jaw Width | Jaw Thickness | Cutting Knives | |
|------------|-----------------|------------|----------------|---------------|----------------|--|
| D220-7-INS | 7-7/8" (200 mm) | 1" (25 mm) | 31/32" (25 mm) | 1/2" (13 mm) | standard | |

Insulated Heavy-Duty Long-Nose Pliers - Side-Cutting

Additional Features:

- Induction hardened cutting knives for long life.
- Heavier design for easier, more comfortable cutting.
- Extended handles provide added reach and leverage.
- Cat. No. D203-8N-INS has skinning hole for No. 12 AWG wire.



| Defail This bases | |
|-------------------|-----|
| | _ |
| | |
| | |
| | |
| | |
| | V V |
| | |
| | |
| | |
| | |

| Cat. No. | Overall Length | Jaw Length | Jaw Width | Jaw Thickness | Knife Length | Point Thickness |
|-------------|-----------------|-----------------|------------|---------------|--------------|-----------------|
| D203-8-INS | 8-7/8" (225 mm) | 2-5/16" (59 mm) | 1" (25 mm) | 1/2" (13 mm) | 5/8" (16 mm) | 1/8" (3 mm) |
| D203-8N-INS | 8-7/8" (225 mm) | 2-5/16" (59 mm) | 1" (25 mm) | 1/2" (13 mm) | 5/8" (16 mm) | 1/8" (3 mm) |

All dimensions are in inches and (millimeters).

AWARNING: Only use tools that are marked with the official international 1000-volt rating symbol shown below, if there is any chance that the tools will make contact with an energized source. 1000 V

AWARNING: Wear approved eye protection. Always inspect your tools before use. Do not use if orange coating cracks, breaks or becomes damaged. Destroy tool if white layer shows through orange layer.

AWARNING: Do NOT use screwdrivers to pry or chisel.

AWARNING: Do NOT touch uninsulated portion of the tool or any conductive object when either might contact an energized source.

AWARNING: Whenever possible, always de-energize lines and equipment prior to working on or around them. Klein insulated tools are designed only to reduce the chance of injury where the tool may make contact with an energized source.

AWARNING: Because moisture, films, or other surface contaminants are conductive, Klein insulated tools must be kept clean, dry, and free of any surface contaminants.

