

NOW available in  
16" length



## Robust pliers for very hard applications

A new addition to the Alligator® Family. The KNIPEX Alligator® XL offers the performance and comfort of a water pump pliers while being 50% lighter in weight and having a greater gripping capacity (3 ½") than comparable pipe wrenches. The new 16" size is more robust and powerful than ever before. There is a place for the KNIPEX Alligator® XL in every toolbox.

- gripping surfaces with special hardened teeth, teeth hardness approx. 61 HRC: low wear and stable gripping
- self-locking on pipes and nuts= no slipping off the workpiece and low handforce required
- forged box-joint design for very high stability providing a true top and bottom grip
- thin head and joint area fits into tight places
- 11-notch adjustment for a gripping capacity up to 3 ½", optimized adjustment to the workpiece and comfortable handle position
- German Chrome vanadium electric steel, forged, oil-hardened
- Applications: Industrial, plumbing, STAFDA, automotive, heavy equipment, electrical, etc.



Alligator® XL



The KNIPEX full line of Alligator Water Pump Pliers is unsurpassed in the market. We have an Alligator Pliers to meet all of your applications.

| Product Number           | ↔ inch | ↔ mm | Carded Packaging |  | Head          | Handles  | ∅ inch | inch  | ∅ mm | mm | Adjustment positions | Ounces |
|--------------------------|--------|------|------------------|--|---------------|--|--------|-------|------|----|----------------------|--------|
| 88 01 180                | 7 1/4  | 180  | n                |  | polished      | with non-slip plastic coating                    | 1 1/2  | 1 3/8 | 42   | 36 | 9                    | 6.3    |
| 88 01 180 SBA            | 7 1/4  | 180  | y                |  |               |  | 1 1/2  | 1 3/8 | 42   | 36 | 9                    | 6.3    |
| 88 01 250                | 10     | 250  | n                |  |               |  | 2      | 1 3/4 | 50   | 46 | 9                    | 11.3   |
| 88 01 250 SBA            | 10     | 250  | y                |  |               |  | 2      | 1 3/4 | 50   | 46 | 9                    | 11.3   |
| 88 01 300                | 12     | 300  | n                |  |               |  | 2 3/4  | 2 3/8 | 70   | 60 | 9                    | 18.0   |
| 88 01 300 SBA            | 12     | 300  | y                |  |               |  | 2 3/4  | 2 3/8 | 70   | 60 | 9                    | 18.0   |
| 88 01 400 <b>NEW</b>     | 16     | 400  | n                |  |               |  | 3 1/2  | 3 3/4 | 90   | 95 | 11                   | 42.5   |
| 88 01 400 SBA <b>NEW</b> | 16     | 400  | y                |  |               |  | 3 1/2  | 3 3/4 | 90   | 95 | 11                   | 42.5   |
| 88 02 180                | 7 1/4  | 180  | n                |  | polished      | with multi-component grips                       | 1 1/2  | 1 3/8 | 42   | 36 | 9                    | 7.6    |
| 88 02 180 SBA            | 7 1/4  | 180  | y                |  |               |  | 1 1/2  | 1 3/8 | 42   | 36 | 9                    | 7.6    |
| 88 02 250                | 10     | 250  | n                |  |               |  | 2      | 1 3/4 | 50   | 46 | 9                    | 12.6   |
| 88 02 250 SBA            | 10     | 250  | y                |  |               |  | 2      | 1 3/4 | 50   | 46 | 9                    | 12.6   |
| 88 02 300                | 12     | 300  | n                |  |               |  | 2 3/4  | 2 3/8 | 70   | 60 | 9                    | 20.0   |
| 88 02 300 SBA            | 12     | 300  | y                |  |               |  | 2 3/4  | 2 3/8 | 70   | 60 | 9                    | 20.0   |
| 88 07 250                | 10     | 250  | y                |  | chrome plated | plastic dipped insulated                         | 2      | 1 3/4 | 50   | 46 | 9                    | 11.3   |
| 88 08 250                | 10     | 250  | n                |  | polished      | insulated with multi-component grips, VDE-tested | 2      | 1 3/4 | 50   | 46 | 9                    | 13.7   |
| 88 08 250 SBA            | 10     | 250  | y                |  |               |  | 2      | 1 3/4 | 50   | 46 | 9                    | 13.7   |

## KNIPEX Tools LP

2035 South Arlington Heights Rd.  
Suite 110  
Arlington Heights, IL 60005

Tel.: +1 (847) 398 8520  
Fax: +1 (847) 398 8526

info@knipex-tools.com  
www.knipex-tools.com

Your distributor