

LIQUIDTIGHT

90° Malleable Liquidtight Fittings - Non-Insulated and Insulated



Features

- Tapered threaded male hub - NPT
- Compact, slim diameter
- Steel locknut
- Liquidtight/Raintight/Oiltight/Concrete tight
- Suitable for wet locations
- Long ferrule prevents pullout & tight bend conduit pop out
- RoHS compliant

Standard Materials

- Malleable iron
- Nylon
- Steel ferrule
- Steel locknut

Standard Finish


- Zinc plated

Applicable Third Party Standards


- UL Standard: 514B
- Fed. Spec. W-F-408E
- NEMA: FB-1
- UL Listed File # E207875



Non-Insulated



Insulated



LIQUIDTIGHT

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	DIM D	INNER PACK	MASTER PACK	WEIGHT PER C
90° Non-Insulated								
LT3890KON	3/8"	1.250	0.500	1.188	1.563	15	150	25.4
LT5090KON	1/2"	1.438	0.500	1.313	1.563	15	150	28.9
LT7590KON	3/4"	2.000	0.500	1.563	1.813	10	100	44.1
LT10090KON	1"	1.125	0.625	1.875	2.188	5	50	74.5
LT12590KON	1-1/4"	2.875	0.625	2.250	2.188	4	40	96.1
LT15090KON	1-1/2"	2.688	0.750	2.500	2.500	3	30	121.6
LT20090KON	2"	3.188	0.750	3.000	2.875	2	20	176.4
LT25090KON	2-1/2"	8.313	1.063	1.063	2.875	—	1	837.7
LT30090KON	3"	9.500	1.125	4.875	9.500	—	1	1234.6
LT35090KON	3-1/2"	7.438	1.188	5.438	11.875	—	1	1896.0
LT40090KON	4"	13.813	1.188	6.063	12.938	—	1	2381.0
90° Insulated								
LT3890-ICKON	3/8"	1.250	0.500	1.188	1.563	15	150	25.7
LT5090-ICKON	1/2"	1.438	0.500	1.313	1.563	15	150	29.2
LT7590-ICKON	3/4"	2.000	0.500	1.563	1.813	10	100	44.6
LT10090-ICKON	1"	1.125	0.625	1.875	2.188	5	50	75.3
LT12590-ICKON	1-1/4"	2.875	0.625	2.250	2.188	4	40	97.1
LT15090-ICKON	1-1/2"	2.688	0.750	2.500	2.500	3	30	122.5
LT20090-ICKON	2"	3.188	0.750	3.000	2.875	2	20	178.2
LT25090-ICKON	2-1/2"	8.300	1.063	1.063	2.875	—	1	846.1
LT30090-ICKON	3"	9.500	1.125	4.875	9.500	—	1	1246.9
LT35090-ICKON	3-1/2"	7.438	1.188	5.438	11.875	—	1	1914.9
LT40090-ICKON	4"	12.813	1.188	6.063	12.938	—	1	2404.8