



Die Cast Conduit Hubs with Insulated Throat

Features

- Tapered threaded male hub NPT
- Compact
- Liquidtight/Raintight/Oiltight/Concrete tight
- Suitable for wet locations

Standard Materials

- Zinc Die Cast
- Insuliner - Polycarbonate

Standard Finish

- Vibratory Finish

Applicable Third Party Standards

- UL Standard: 514B
- UL Listed File E207875
- RoHS



Catalog Number	Trade Size (in)	Dim A (in)	Dim B (in)	Inner Pack	Master Pack	Weight Per C (lb)
NHUBD50-ICKON	1/2	1.42	1.22	25	250	16.3
NHUBD75-ICKON	3/4	1.61	1.50	25	150	26.5
NHUBD100-ICKON	1	1.87	1.89	25	100	36.3
NHUBD125-ICKON	1 1/4	2.01	2.24	10	60	44.2
NHUBD150-ICKON	1 1/2	2.13	2.52	10	60	61.2
NHUBD200-ICKON	2	2.2	3.03	10	40	89.3
NHUBD250-ICKON	2 1/2	2.64	3.54	2	12	156.5
NHUBD300-ICKON	3	2.64	4.17	2	12	175.5
NHUBD400-ICKON	4	2.7	5.35	1	6	256.8

