

## Wire Mesh Grips

### Single-Weave, Flexible-Eye Pulling Grips



KPJ-50

| Cat. No. | Cable Diameter                     | Mesh Length      | Maximum Safe Load | Weight            |
|----------|------------------------------------|------------------|-------------------|-------------------|
| KPJ50    | 0.50" to 0.61" (12.70 to 15.59 mm) | 8.5" (215.9 mm)  | 260 lb (118 kg)   | 0.80 oz (22.7 g)  |
| KPJ75    | 0.75" to 0.99" (19.05 to 25.15 mm) | 10" (254.0 mm)   | 560 lb (254 kg)   | 0.10 lb (0.05 kg) |
| KPJ100   | 1.00" to 1.24" (25.4 to 31.50 mm)  | 11.5" (292.1 mm) | 780 lb (354 kg)   | 0.28 lb (0.13 kg) |
| KPL125-1 | 1.25" to 1.49" (31.75 to 37.85 mm) | 14" (355.6 mm)   | 1060 lb (481 kg)  | 0.40 lb (0.18 kg) |
| KPL150-1 | 1.50" to 1.74" (38.10 to 44.20 mm) | 15" (381.0 mm)   | 1360 lb (617 kg)  | 0.40 lb (0.18 kg) |
| KPL200-1 | 2.00" to 2.49" (50.80 to 63.25 mm) | 18" (457.2 mm)   | 1700 lb (771 kg)  | 0.65 lb (0.29 kg) |

### Double-Weave, Flexible-Eye Pulling Grips



KPM-075

| Cat. No. | Cable Diameter                     | Mesh Length    | Maximum Safe Load | Weight            |
|----------|------------------------------------|----------------|-------------------|-------------------|
| KPM050   | 0.50" to 0.61" (12.70 to 15.59 mm) | 13" (330.2 mm) | 480 lb (218 kg)   | 0.10 lb (0.05 kg) |
| KPM075   | 0.75" to 0.99" (19.05 to 25.15 mm) | 16" (406.4 mm) | 1030 lb (467 kg)  | 0.20 lb (0.09 kg) |
| KPM100   | 1.00" to 1.37" (25.4 to 34.80 mm)  | 18" (457.2 mm) | 1420 lb (644 kg)  | 0.40 lb (0.18 kg) |
| KP075-24 | 0.75" to 0.99" (19.05 to 25.15 mm) | 24" (609.6 mm) | 1360 lb (617 kg)  | 0.50 lb (0.23 kg) |
| KP100-24 | 1.00" to 1.49" (25.4 to 37.85 mm)  | 24" (609.6 mm) | 1920 lb (871 kg)  | 1.1 lb (0.5 kg)   |
| KP075-36 | 0.75" to 0.99" (19.05 to 25.15 mm) | 36" (914.4 mm) | 1360 lb (617 kg)  | 0.74 lb (0.34 kg) |
| KP100-36 | 1.00" to 1.49" (25.4 to 37.85 mm)  | 36" (914.4 mm) | 1920 lb (871 kg)  | 1.0 lb (0.5 kg)   |
| KP150-36 | 1.50" to 1.99" (38.10 to 50.55 mm) | 36" (914.4 mm) | 3280 lb (1488 kg) | 1.6 lb (0.7 kg)   |

### Double-Weave, Rotating-Eye Pulling Grips



KPS-062-1

| Cat. No. | Cable Diameter                       | Mesh Length    | Maximum Safe Load | Weight            |
|----------|--------------------------------------|----------------|-------------------|-------------------|
| KPS050-2 | 0.50" to 0.61" (12.70 to 15.59 mm)   | 16" (406.4 mm) | 1120 lb (508 kg)  | 0.45 lb (0.20 kg) |
| KPS062-2 | 0.620" to 0.740" (15.74 to 18.79 mm) | 16" (406.4 mm) | 1360 lb (617 kg)  | 0.50 lb (0.23 kg) |
| KPS075-2 | 0.75" to 0.99" (19.05 to 25.15 mm)   | 20" (508.0 mm) | 1360 lb (617 kg)  | 0.85 lb (0.39 kg) |
| KPS100-2 | 1.00" to 1.24" (25.4 to 31.50 mm)    | 20" (508.0 mm) | 2560 lb (1161 kg) | 1.9 lb (0.9 kg)   |
| KPS125-2 | 1.25" to 1.49" (31.75 to 37.85 mm)   | 21" (533.4 mm) | 2560 lb (1161 kg) | 1.9 lb (0.9 kg)   |
| KPS150-2 | 1.50" to 1.99" (38.10 to 50.55 mm)   | 25" (635.0 mm) | 3280 lb (1488 kg) | 2.2 lb (1.0 kg)   |
| KPS200-2 | 2.00" to 2.49" (50.80 to 63.25 mm)   | 26" (660.4 mm) | 5440 lb (2468 kg) | 4.1 lb (1.9 kg)   |
| KPS250-2 | 2.50" to 2.99" (63.50 to 75.95 mm)   | 28" (711.2 mm) | 6600 lb (2994 kg) | 5.3 lb (2.4 kg)   |
| KPS300-2 | 3.00" to 3.49" (76.20 to 88.65 mm)   | 30" (762.0 mm) | 8200 lb (3720 kg) | 6.1 lb (2.8 kg)   |
| KPS350-2 | 3.5" to 3.99" (88.90 to 101.35 mm)   | 32" (812.8 mm) | 9600 lb (4354 kg) | 6.8 lb (3.1 kg)   |
| KPS100-3 | 1.00" to 1.49" (25.4 to 37.85 mm)    | 33" (838.2 mm) | 3280 lb (1488 kg) | 2.4 lb (1.1 kg)   |
| KPS150-3 | 1.50" to 1.99" (38.10 to 50.55 mm)   | 34" (863.6 mm) | 3280 lb (1488 kg) | 2.5 lb (1.1 kg)   |
| KPS200-3 | 2.00" to 2.49" (50.80 to 63.25 mm)   | 36" (914.4 mm) | 5440 lb (2468 kg) | 4.7 lb (2.1 kg)   |

### Slack-Pulling, Offset Flexible-Eye Pulling Grips



KSCK-100-1

| Cat. No.  | Cable Diameter                     | Mesh Length    | Maximum Safe Load | Weight            |
|-----------|------------------------------------|----------------|-------------------|-------------------|
| KSCK100-1 | 1.00" to 1.24" (25.4 to 31.50 mm)  | 15" (381.0 mm) | 800 lb (363 kg)   | 0.50 lb (0.23 kg) |
| KSSK125-1 | 1.25" to 1.49" (31.75 to 37.85 mm) | 16" (406.4 mm) | 800 lb (363 kg)   | 0.25 lb (0.11 kg) |