

# 2613



**Color :**  Black-White

**UPC Code :** 078477807873

**Country Of Origin :** Mexico

**NEMA :**  L5-30R

#### Available Colors :



Black



Yellow-White

Locking Connector, 30 Amp, 125 Volt, Industrial Grade - Black & White

30 Amp, 125 Volt, NEMA L5-30R, 2P, 3W, Locking Connector, Industrial Grade, Grounding - Black/White

**ROHS Compliant :** Yes

Leviton's Black & White line of industrial grade plugs, connectors, flanged inlets, and outlets offer superior performance, long lasting reliability and features that are backed by a limited lifetime warranty:

- One piece contacts reduce friction and overheating
- Unique cord clamp accepts wide range of cord sizes
- Rugged nylon construction resists impact, sunlight, chemicals, and rough use
- Industry exclusive limited lifetime warranty

## Technical Information

### Electrical Specifications

**Amperage :** 30 A

**Current Interrupting :** Certified for current interrupting at full rated current

**Dielectric Voltage :** Withstands 2000V per UL498

**Grounding :** Grounding

**Pole :** 2

**Temperature Rise :** Max 30C after 250 cycles OL at 200 percent rated current

**Voltage :** 125 VAC

**Wire :** 3

### Environmental Specifications

**Environment :** Dry

**Flammability :** Rated HB or better UL94

**Operating Temperature :** -40° C to 60°C

### Material Specifications

**Assembly Screws :** Steel, Zinc Plated

**Back Cover :** Thermoplastic

**Blades/Contacts :** Solid Brass

**Body Material :** Impact Modified Nylon

**Clamp Insert :** Nylon

**Color :** Black-White

**Cord-Clamp :** Nylon

**Terminal Screws :** Brass

### Mechanical Specifications

**At Rated Voltage :** 2 HP

**Cord Range :** 0.520 to 0.930

**Product ID :** Ratings are permanently marked on device

**Terminal Accom. :** 18-10 AWG

**Terminal ID :** Brass-Hot, Green-Ground, Silver-Neutral

**Torque Range :** 10-14 in-lbs

**Wire Gauge :** 16-8 AWG

## Wire Module : Nylon

### Product Features

**Brand** : Black and White

**Color** : Black-White

**Device Type** : Locking  
Connector

**NEMA** : L5-30R

### Standards and Certifications

**ANSI** : C-73

**CSA C22.2 No. 42** : File LR-406

**NEMA** : WD-6


**NOM** : 057

**UL Fed Spec WC-596** : File  
E13393

**UL498** : File E13393

**Warranty** : Limited Lifetime  
Warranty

## Dimensional Drawing



### **Leviton Manufacturing Co., Inc**

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.  
T. Monday-Friday): +1-800-824-3005

### **Leviton Manufacturing of Canada, Ltd.**

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·  
FAX: +1-800-824-3005 · [www.leviton.com/canada](http://www.leviton.com/canada)

### **Leviton S. de R.L. de C.V.**

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)  
5386- 1797 · [www.leviton.com.mx](http://www.leviton.com.mx)

### **Visit our Website at: [www.leviton.com](http://www.leviton.com)**

© 2024 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without  
notice.

### **Leviton has a global presence.**

If you would like to know where your local Leviton office is located please go to:  
[www.leviton.com/international/contacts](http://www.leviton.com/international/contacts)

© 2024 Leviton Manufacturing Co., Inc.